	BLE STAN				STORAGE				
	TEMPERATURE RANGE		-35°C TO 85°C(NOTE 1)		TEMPERATURE RANGE		-10°C TO 60°C		
RATING	VOLTAGE		30V AC		APPLICABLE CONNECTOR		BM14B(0.8)-10DS-0.4V(**		**)
	CURRENT		0. 3A						
			SPEC	IFICA	FIONS				
П	ΓEM	TEST METHOD				REG	QUIREMENTS	QT	A
	RUCTION								
-	EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.			IT. ACCO	RDING TO	DRAWING.	Х	Х
			IED VISUALLY.					Х	Х
	IC CHARA		OR LESS 1kHz,1mA .		100m	2 MAX.		<u> </u>	1
									-
INSULATION RESISTANCE		100V DC.			50MΩ	50MΩ MIN.			-
VOLTAGE PROOF		100V AC FOR 1 min.			NO FL	NO FLASHOVER OR BREAKDOWN.			
		ARACTERISTICS							
			RISTICS		0.00		SISTANCE: 100mΩ MAX.	T	<u>т</u>
OPERATION					2 NC	 2 NO DAMAGE, CRACK OR LOOSENESS OF PARTS. 			_
VIBRATION		FREQUENCY 10 TO 55 TO 10 Hz,APPROX 5min, SINGLE AMPLITUDE 0.75 mm,10CYCLES,			② NO	 NO ELECTRICAL DISCONTINUITY OF 1 μs. NO DAMAGE, CRACK OR LOOSENESS OF DAPTS 			_
SHOCK		FOR 3 DIRECTIONS. 490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.			IMES ① NO ② NO	② NO DAMAGE, CRACK OR LOOSENESS OF			_
					PA	RTS.			
RAPID CHA			CTERISTICS ATURE -55 → +85°C		1 00		SISTANCE: 100mΩ MAX.	1	
TEMPERATURE		TIME $30 \rightarrow 30$ min UNDER 5 CYCLES. (RELOCATION TIME TO CHANBER : WITHIN 2-3 min)			 INS NC 	 INSULATION RESISTANCE: 50MΩ MIN. NO DAMAGE, CRACK OR LOOSENESS OF PARTS. 			_
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.			 INS NC 	 CONTACT RESISTANCE: 100mΩ MAX. INSULATION RESISTANCE: 25MΩ MIN. NO DAMAGE, CRACK OR LOOSENESS OF PARTS. 			-
SULPHUR D	DIIOXIDE	EXPOSED IN 25 PPM FOR 96h,25°C,75%. (REFER TO JIS C 60068)			① CC ② NC AF	 CONTACT RESISTANCE: 100mΩ MAX. NO EVIDENCE OF CORROSION WHICH AFFECTS TO OPERATION OF CONNECTOR. 			-
	IT D	ESCRIPTIC	N OF REVISIONS	[DESIGNED		CHECKED	DA	TE
REMARKS						APPROVE	D MO. ISHIDA	17.0	1 1
NOTE1: INCLU	UDE THE TEMP	PERATURE R	RATURE RISING BY CURRENT ed, refer to JIS C 5402 and IEC 60512.			CHECKE		17.01.1 0 17.01.1	
Inless othe	erwise sneci	fied refer f				DESIGNE	D NY. YAMASHIRO		
	-		urance Test X:Applicable T			DRAWN	SN. NUMAZAKI ELC-319845-5		
							4B (0. 8) –10DP–0. 4V (53)		
RS		OSE ELECTRIC CO., LTD.							1/
								~~	• *