

Professional Construction site cable reel KA 5100 5 IP 44, 50 m H07RN-F 3G1.5

For construction site use in accordance with DGUV 203-006 (formerly BGI 608) and permanent outdoor use IP 44.



**MADE IN
GERMANY**

5 YEARS
MANUFACTURER
GUARANTEE



Product number

9201500110

EAN

4007123687527

DESCRIPTION

- Professional drum with all-round roll-over protection.
- Stable on all four sides - perfect cable routing on all four sides.
- Large, sturdy folding twist handle for effortless winding and unwinding of the cable.
- Robust carrying handles and plug garage on all four sides.
- Housing and reel material made of a plastic-rubber mix - extremely shock and impact resistant and suitable for continuous use under the toughest conditions.
- Reel body cold impact resistant down to -25 °C and reel brake.
- The RN cable is very robust, oil-resistant and particularly suitable for professional use.
- RN cable is approved for harsh building conditions in accordance with VDE 0100 Part 704.
- 5 splash-proof 230 V protective contact sockets.
- Overheating protection with indicator light in the event of overheating and overloading.
- With visual readiness indicator in the socket insert.
- Category 2 equipment (K2 DGUV 203-005): For use in harsh operating conditions with high mechanical, physical and chemical influences.

Professional Construction site cable reel KA 5100 5 IP 44, 50 m H07RN-F 3G1.5

For construction site use in accordance with DGUV 203-006 (formerly BGI 608) and permanent outdoor use IP 44.



Product number 9201500110
EAN 4007123687527

TECHNICAL DATA

Cable quality	Rubber-Neoprene	Plug system socket	Type F (Protective contact)
Cable length	50 m	Plug system plug	Type E and F (Protective contact with earth hole)
Cable designation	H07RN-F 3G1,5	Max. current carrying capacity	16 A
Cable colour	black	Nominal input voltage	230 V
Reel diameter	320 mm	Degree of protection (IP)	IP44
Plug system CEE socket	Without		

PACKAGING, DIMENSIONS AND WEIGHTS

UP	1	Weight of product (including packaging)	10.33 kg
Weight of product (without packaging)	10.33 kg	Dimension LxWxH (incl. packing)	25 cm x 38 cm x 40 cm
Dimension LxWxH (without packing)	21 cm x 37 cm x 37 cm		

SCOPE OF DELIVERY

Professional construction site cable reel KA 5100 5