



## Dual N-Channel Enhancement-Mode Vertical DMOS FET

### Features

- ▶ Dual N-channel devices
- ▶ Low threshold – 2.0V max.
- ▶ High input impedance
- ▶ Low input capacitance – 125pF max.
- ▶ Fast switching speeds
- ▶ Low on-resistance
- ▶ Free from secondary breakdown
- ▶ Low input and output leakage

### Applications

- ▶ Logic level interfaces – ideal for TTL and CMOS
- ▶ Solid state relays
- ▶ Battery operated systems
- ▶ Photo voltaic drives
- ▶ Analog switches
- ▶ General purpose line drivers
- ▶ Telecom switches

### General Description

This low threshold, enhancement-mode (normally-off) transistor utilizes a vertical DMOS structure and Supertex's well-proven, silicon-gate manufacturing process. This combination produces a device with the power handling capabilities of bipolar transistors and the high input impedance and positive temperature coefficient inherent in MOS devices. Characteristic of all MOS structures, this device is free from thermal runaway and thermally-induced secondary breakdown.

Supertex's vertical DMOS FETs are ideally suited to a wide range of switching and amplifying applications where very low threshold voltage, high breakdown voltage, high input impedance, low input capacitance, and fast switching speeds are desired.

### Ordering Information

| Part Number | Package Option | Packing   |
|-------------|----------------|-----------|
| TD9944TG-G  | 8-Lead SOIC    | 2000/Reel |

-G denotes a lead (Pb)-free / RoHS compliant package.

### Product Summary

| $BV_{DSS}/BV_{DGS}$ | $R_{DS(ON)}$<br>(max) | $I_{D(ON)}$<br>(min) | $V_{GS(th)}$<br>(max) |
|---------------------|-----------------------|----------------------|-----------------------|
| 240V                | 6.0Ω                  | 1.0A                 | 2.0V                  |

### Absolute Maximum Ratings

| Parameter                         | Value           |
|-----------------------------------|-----------------|
| Drain-to-source voltage           | $BV_{DSS}$      |
| Drain-to-gate voltage             | $BV_{DGS}$      |
| Gate-to-source voltage            | ±20V            |
| Operating and storage temperature | -55°C to +150°C |

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied. Continuous operation of the device at the absolute rating level may affect device reliability. All voltages are referenced to device ground.


### Typical Thermal Resistance

| Package           | $\theta_{ja}$ |
|-------------------|---------------|
| TO-243AA (SOT-89) | 133°C/W       |

**Note:**

Mounted on FR5 Board, 25mm x 25mm x 1.57mm

### Pin Configuration



8-Lead SOIC

### Product Marking



YY = Year Sealed  
WW = Week Sealed  
— = "Green" Packaging

Package may or may not include the following marks: Si or

8-Lead SOIC


## Electrical Characteristics ( $T_A = 25^\circ\text{C}$ unless otherwise specified)

| Sym                 | Parameter                                  | Min | Typ | Max  | Units    | Conditions                                                            |
|---------------------|--------------------------------------------|-----|-----|------|----------|-----------------------------------------------------------------------|
| $BV_{DSS}$          | Drain-to-source breakdown voltage          | 240 | -   | -    | V        | $V_{GS} = 0V, I_D = 2.0mA$                                            |
| $V_{GS(th)}$        | Gate threshold voltage                     | 0.6 | -   | 2.0  | V        | $V_{GS} = V_{DS}, I_D = 1.0mA$                                        |
| $\Delta V_{GS(th)}$ | Change in $V_{GS(th)}$ with temperature    | -   | -   | -5.0 | mV/°C    | $V_{GS} = V_{DS}, I_D = 1.0mA$                                        |
| $I_{GSS}$           | Gate body leakage                          | -   | -   | 100  | nA       | $V_{GS} = \pm 20V, V_{DS} = 0V$                                       |
| $I_{DSS}$           | Zero gate voltage drain current            | -   | -   | 10   | $\mu A$  | $V_{GS} = 0V, V_{DS} = \text{Max Rating}$                             |
|                     |                                            | -   | -   | 1.0  | mA       | $V_{DS} = 0.8\text{Max Rating}, V_{GS} = 0V, T_A = 125^\circ\text{C}$ |
| $I_{D(ON)}$         | ON-state drain current                     | 0.5 | 1.9 | -    | A        | $V_{GS} = 4.5V, V_{DS} = 25V$                                         |
|                     |                                            | 1.0 | 2.8 | -    |          | $V_{GS} = 10V, V_{DS} = 25V$                                          |
| $R_{DS(ON)}$        | Static drain-to-source on-state resistance | -   | 4.0 | 6.0  | $\Omega$ | $V_{GS} = 4.5V, I_D = 250mA$                                          |
|                     |                                            | -   | 4.0 | 6.0  |          | $V_{GS} = 10V, I_D = 0.5A$                                            |
| $\Delta R_{DS(ON)}$ | Change in $R_{DS(ON)}$ with temperature    | -   | -   | 1.4  | %/°C     | $V_{GS} = 10V, I_D = 0.5A$                                            |
| $G_{FS}$            | Forward transconductance                   | 300 | 600 | -    | mmho     | $V_{DS} = 20V, I_D = 0.5A$                                            |
| $C_{ISS}$           | Input capacitance                          | -   | 65  | 125  | pF       | $V_{GS} = 0V, V_{DS} = 25V, f = 1.0MHz$                               |
| $C_{OSS}$           | Common source output capacitance           | -   | 35  | 70   |          |                                                                       |
| $C_{RSS}$           | Reverse transfer capacitance               | -   | 10  | 25   |          |                                                                       |
| $t_{d(ON)}$         | Turn-on delay time                         | -   | -   | 10   | ns       | $V_{DD} = 25V, I_D = 1.0A, R_{GEN} = 25\Omega$                        |
| $t_r$               | Rise time                                  | -   | -   | 10   |          |                                                                       |
| $t_{d(OFF)}$        | Turn-off delay time                        | -   | -   | 20   |          |                                                                       |
| $t_f$               | Fall time                                  | -   | -   | 20   |          |                                                                       |
| $V_{SD}$            | Diode forward voltage drop                 | -   | -   | 1.8  | V        | $V_{GS} = 0V, I_{SD} = 1.0A$                                          |
| $t_{rr}$            | Reverse recovery time                      | -   | 300 | -    | ns       | $V_{GS} = 0V, I_{SD} = 1.0A$                                          |







### Notes:

1. All D.C. parameters 100% tested at  $25^\circ\text{C}$  unless otherwise stated. (Pulse test: 300 $\mu s$  pulse, 2% duty cycle.)
2. All A.C. parameters sample tested.




## Switching Waveforms and Test Circuit




## Typical Performance Curves



## Typical Performance Curves (cont.)



# 8-Lead SOIC (Narrow Body) Package Outline (TG) 4.90x3.90mm body, 1.75mm height (max), 1.27mm pitch



**Note:**  
1. This chamfer feature is optional. A Pin 1 identifier must be located in the index area indicated. The Pin 1 identifier can be: a molded mark/identifier; an embedded metal marker; or a printed indicator.

JEDEC Registration MS-012, Variation AA, Issue E, Sept. 2005.

\* This dimension is not specified in the JEDEC drawing.

**Drawings are not to scale.**

**Supertex Doc. #:** DSPD-8SOLGTG, Version I041309.

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to <http://www.supertex.com/packaging.html>.)

**Supertex inc.** does not recommend the use of its products in life support applications, and will not knowingly sell them for use in such applications unless it receives an adequate "product liability indemnification insurance agreement." **Supertex inc.** does not assume responsibility for use of devices described, and limits its liability to the replacement of the devices determined defective due to workmanship. No responsibility is assumed for possible omissions and inaccuracies. Circuitry and specifications are subject to change without notice. For the latest product specifications refer to the **Supertex inc.** (website: <http://www.supertex.com>)