

Tapered roller bearings 31307-A (Series 313)

main dimensions to DIN ISO 355 / DIN 720, separable, adjusted or in pairs

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp) or by telephone on +49 (91 32) 82 - 28 97.

d	35 mm
D	80 mm
T	22,75 mm
a	26 mm ≈
B	21 mm
C	15 mm
C _{a min}	4 mm
C _{b min}	7,5 mm
d ₁	59,9 mm ≈
D _{a max}	71 mm
d _{a max}	44 mm
D _{a min}	62 mm

Db min	76 mm	
db min	44 mm	
r1, 2 min	2 mm	
r3, 4 min	1,5 mm	
ra max	2 mm	
rb max	1,5 mm	
m	0,514 kg	≈ Mass
Cr	60000 N	Basic dynamic load rating, radial
C0r	64000 N	Basic static load rating, radial
e	0,83	
Y	0,73	
Y0	0,4	
Cur	7600 N	Fatigue limit load, radial
nG	9100 1/min	Limiting speed
n9r	5700 1/min	Reference speed
	T7FB035	Comparative designation to DIN ISO 355

