
Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

HAMMERITE RED OXIDE PRIMER #297-3742, 297-3758

SYNOMYS

"Manufacturer's Code: 297-3742, 297-3758"

PROPER SHIPPING NAME

PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

PRODUCT USE

■ Apply by brush, hand roller or spray atomisation.
Red oxide primer.

SUPPLIER

Company: RS Components Pty Ltd

Address:

Units 30 & 31, 761 Great South Road

Penrose

Auckland, 1006

New Zealand

Telephone: +64 9 526 1600

Fax: +64 9 579 1700

Company: RS Components Pty Ltd

Address:

25 Pavesi Street

Smithfield

NSW, 2164

Australia

Telephone: +1 300 656 636

Emergency Tel: 1800 039 008 (24 hours)

Emergency Tel: +61 3 9573 3112

Fax: +1 300 656 696

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.



RISK

■ Flammable.
■ Harmful by inhalation.
■ Irritating to skin.
■ Risk of serious damage to eyes.
■ Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
■ HARMFUL- May cause lung damage if swallowed.

SAFETY

- Do not breathe gas/fumes/vapour/spray.
- Avoid contact with skin.
- Avoid contact with eyes.
- Wear suitable protective clothing.
- Wear suitable gloves.
- Wear eye/face protection.
- Use only in well ventilated areas.
- Keep container in a well ventilated place.
- To clean the floor and all objects contaminated by this material, use water and detergent.
- Keep container tightly closed.
- Keep away from food, drink and animal feeding stuffs.
- In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
- If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).
- This material and its container must be disposed of as hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
1, 2, 4- trimethyl benzene	95-63-6	5-10
white spirit	8052-41-3.	5-10
1, 3, 5- trimethyl benzene	108-67-8	1-5
xylene	1330-20-7	1-5
isobutanol	78-83-1	1-5
dimethylbenzylammonium chloride	1875-92-9	1-5

Section 4 - FIRST AID MEASURES

SWALLOWED

- If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.
- If poisoning occurs, contact a doctor or Poisons Information Centre.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Avoid giving milk or oils.
- Avoid giving alcohol.

EYE

- If this product comes in contact with the eyes:
 - Immediately hold eyelids apart and flush the eye continuously with running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
 - Transport to hospital or doctor without delay.

SKIN

- If skin contact occurs:
 - Immediately remove all contaminated clothing, including footwear.
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

NOTES TO PHYSICIAN

- Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are flammable.
- Moderate fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Moderate explosion hazard when exposed to heat or flame.

Combustion products include: carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM

- 3Y

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- DO NOT allow clothing wet with material to stay in contact with skin.
- Electrostatic discharge may be generated during pumping - this may result in fire.
- Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<=1 m/sec until fill pipe submerged to twice its diameter, then <= 7 m/sec).
- Avoid splash filling.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of overexposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

SUITABLE CONTAINER

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used.

STORAGE INCOMPATIBILITY

- Avoid reaction with oxidising agents.
- Avoid strong acids, bases.

STORAGE REQUIREMENTS

- Store in original containers in approved flammable liquid storage area.
- Store away from incompatible materials in a cool, dry, well-ventilated area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	STEL ppm	STEL mg/m ³	Notes
Australia Exposure Standards	Hammerite Red Oxide Primer #297- 3742, 297-3758 (Xylene (o-, m-, p- isomers))	80	150	655	NOHSC documentation available for these values.
Australia Exposure Standards	isobutanol (Isobutyl alcohol)	50			American Conference of Governmental Industrial Hygienists (ACGIH) ^{4, 5} is the documentation source

The following materials had no OELs on our records

- 1, 2, 4- trimethyl benzene: CAS:95- 63- 6
- 1, 3, 5- trimethyl benzene: CAS:108- 67- 8
- dimethylbenzylammonium chloride: CAS:1875- 92- 9

MATERIAL DATA

1,2,4-TRIMETHYL BENZENE:

1,3,5-TRIMETHYL BENZENE:

HAMMERITE RED OXIDE PRIMER #297-3742, 297-3758:

- For trimethyl benzene as mixed isomers (of unstated proportions)

Odour Threshold Value: 2.4 ppm (detection)

Use care in interpreting effects as a single isomer or other isomer mix. Trimethylbenzene is an eye, nose and respiratory irritant.

HAMMERITE RED OXIDE PRIMER #297-3742, 297-3758:

ISOBUTANOL:

- For isobutanol:

Odour Threshold Value: 0.66-40 ppm (detection), 1.8-53 ppm (recognition) Although there do not appear to be reports of isobutyl alcohol causing auditory impairment or vestibular damage in humans (as with n-butanol) the recommended TLV-TWA recognises the slightly greater acute toxic potential of isobutanol versus n-butanol. Exposure at or below this limit is thought to significantly reduce the risk of skin irritation.

Odour Safety Factor (OSF)

OSF=31 (ISOBUTYL ALCOHOL).

HAMMERITE RED OXIDE PRIMER #297-3742, 297-3758:

XYLENE:

- for xylenes:

IDLH Level: 900 ppm

Odour Threshold Value: 20 ppm (detection), 40 ppm (recognition)

NOTE: Detector tubes for o-xylene, measuring in excess of 10 ppm, are available commercially. (m-xylene and p-xylene give almost the same response).<>.

WHITE SPIRIT:

- For white spirit:

Low and high odour thresholds of 5.25 and 157.5 mg/m³, respectively, were considered to provide a rather useful index of odour as a warning property.

The TLV-TWA is calculated from data on the toxicities of the major ingredients and is intended to minimise the potential for irritative and narcotic effects, polyneuropathy and kidney damage produced by vapours.<>.

XYLENE:

■ Exposure limits with "skin" notation indicate that vapour and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard.

ISOBUTANOL:

- Exposed individuals are reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class A or B.

continued...

HAMMERITE RED OXIDE PRIMER #297-3742, 297-3758

Chemwatch Independent Material Safety Data Sheet

Issue Date: 14-Aug-2013

9317SP

CHEMWATCH 4544-76

Version No:5.1.1.1

CD 2013/2 Page 5 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

DIMETHYLBENZYLAMMONIUM CHLORIDE:

■ It is the goal of the ACGIH (and other Agencies) to recommend TLVs (or their equivalent) for all substances for which there is evidence of health effects at airborne concentrations encountered in the workplace.

At this time no TLV has been established, even though this material may produce adverse health effects (as evidenced in animal experiments or clinical experience).

NOTE: The ACGIH occupational exposure standard for Particles Not Otherwise Specified (P.N.O.S) does NOT apply.

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations.

PERSONAL PROTECTION

RESPIRATOR

•Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

HANDS/FEET

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
- For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets), non sparking safety footwear.

continued...

ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES**APPEARANCE**

Red viscous flammable liquid with an aromatic odour; does not mix with water.

PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Sinks in water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	145	Solubility in water (g/L)	Immiscible
Flash Point (°C)	35	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	230	Vapour Pressure (kPa)	0.44 @ 20 deg.C
Upper Explosive Limit (%)	8	Specific Gravity (water=1)	1.31
Lower Explosive Limit (%)	0.9	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	0.63 BuAc=1

Section 10 - STABILITY AND REACTIVITY**CONDITIONS CONTRIBUTING TO INSTABILITY**

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION**POTENTIAL HEALTH EFFECTS****ACUTE HEALTH EFFECTS****SWALLOWED**

■ Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733).

EYE

■ If applied to the eyes, this material causes severe eye damage.

SKIN

■ This material can cause inflammation of the skin on contact in some persons.

The material may accentuate any pre-existing dermatitis condition.

Open cuts, abraded or irritated skin should not be exposed to this material.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.

Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

■ Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.

There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such

irritation can cause further lung damage.

Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.

CHRONIC HEALTH EFFECTS

■ Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).

Respiratory sensitisation may result in allergic/asthma like responses; from coughing and minor breathing difficulties to bronchitis with wheezing, gasping.

TOXICITY AND IRRITATION

■ For trimethylbenzenes:

Absorption of 1,2,4-trimethylbenzene occurs after oral, inhalation, or dermal exposure. Occupationally, inhalation and dermal exposures are the most important routes of absorption although systemic intoxication from dermal absorption is not likely to occur due to the dermal irritation caused by the chemical prompting quick removal.

CARCINOGEN

white spirit	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	3	Not classifiable as to its carcinogenicity to humans
xylene	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	3	Not classifiable as to its carcinogenicity to humans

SKIN

1, 2, 4- trimethyl benzene	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	(1)
1, 2, 4- trimethyl benzene	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	1
1, 2, 4- trimethyl benzene	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	2
white spirit	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	1
1, 3, 5- trimethyl benzene	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	(1)
1, 3, 5- trimethyl benzene	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	1
1, 3, 5- trimethyl benzene	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	2
xylene	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	2
xylene	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	1
isobutanol	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	2

Section 12 - ECOLOGICAL INFORMATION

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This material and its container must be disposed of as hazardous waste.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
1, 2, 4- trimethyl benzene	LOW	LOW	LOW	MED
white spirit	No Data	No Data	No Data	No Data
1, 3, 5- trimethyl benzene	Available	Available	Available	Available
xylene	HIGH	No Data	LOW	MED
		Available		
		LOW	LOW	No Data
isobutanol	LOW	MED	LOW	Available HIGH

continued...

HAMMERITE RED OXIDE PRIMER #297-3742, 297-3758

Chemwatch Independent Material Safety Data Sheet

Issue Date: 14-Aug-2013

9317SP

CHEMWATCH 4544-76

Version No:5.1.1.1

CD 2013/2 Page 8 of 10

Section 12 - ECOLOGICAL INFORMATION

dimethylbenzylammonium chloride	No Data Available	No Data Available	No Data Available	No Data Available
---------------------------------	-------------------	-------------------	-------------------	-------------------

Section 13 - DISPOSAL CONSIDERATIONS

■ Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction.
- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE LIQUID

HAZCHEM:

•3Y (ADG7)

ADG7:

Class or Division:	3	Subsidiary Risk:	None
UN No.:	1263	Packing Group:	III
Special Provision:	163 223 *	Limited Quantity:	5 L
Portable Tanks & Bulk Containers -	T2	Portable Tanks & Bulk Containers - Special Provision:	TP1 TP29
Instruction:		Packagings & IBCs - Special Packing Provision:	PP1
Packagings & IBCs -	P001 IBC03 LP01		
Packing Instruction:			

Name and Description: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) (see 3.2.5 for relevant [AUST.] entries)

Air Transport IATA:

ICAO/IATA Class:	3	ICAO/IATA Subrisk:	None
UN/ID Number:	1263	Packing Group:	III
Special provisions:	A3		

Shipping name:PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1263	Packing Group:	III
EMS Number:	F- E, S- E	Special provisions:	163 223 955
Limited Quantities:	5 L		
Shipping name:PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)			

continued...

Section 15 - REGULATORY INFORMATION

Indications of Danger:**Xn****Harmful****POISONS SCHEDULE None****REGULATIONS****Hammerite Red Oxide Primer #297-3742, 297-3758 (CAS:) is found on the following regulatory lists;**

"Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - organic compounds)", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm - Domestic water supply quality", "Australia Drinking Water Guideline Values For Physical and Chemical Characteristics", "Australia Exposure Standards", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Hazardous Substances", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix I", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards", "OECD List of High Production Volume (HPV) Chemicals", "WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water"

Regulations for ingredients**1,2,4-trimethyl benzene (CAS: 95-63-6) is found on the following regulatory lists;**

"Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 7", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR List of Chemicals for Priority Action", "OSPAR National List of Candidates for Substitution – United Kingdom", "Sigma-AldrichTransport Information"

white spirit (CAS: 8052-41-3) is found on the following regulatory lists;

"Acros Transport Information", "Australia Exposure Standards", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "Australia Therapeutic Goods Administration (TGA) Substances that may be used as active ingredients in Listed medicines", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Air Transport Association (IATA) Dangerous Goods Regulations", "International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft", "International Chemical Secretariat (ChemSec) SIN List ("Substitute It Now!)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "International Numbering System for Food Additives", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR List of Chemicals for Priority Action", "OSPAR National List of Candidates for Substitution – Norway", "Sigma-AldrichTransport Information", "United Nations Consolidated List of Products Whose Consumption and/or Sale Have Been Banned, Withdrawn, Severely Restricted or Not Approved by Governments"

1,3,5-trimethyl benzene (CAS: 108-67-8) is found on the following regulatory lists;

"Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 7", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR List of Chemicals for Priority Action", "Sigma-AldrichTransport Information"

xylene (CAS: 1330-20-7) is found on the following regulatory lists;

"Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - organic compounds)", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm - Domestic water supply quality", "Australia Drinking Water Guideline Values For Physical and Chemical Characteristics", "Australia Exposure Standards", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix I", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 7", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by

HAMMERITE RED OXIDE PRIMER #297-3742, 297-3758

Chemwatch Independent Material Safety Data Sheet

Issue Date: 14-Aug-2013

9317SP

CHEMWATCH 4544-76

Version No:5.1.1.1

CD 2013/2 Page 10 of 10

Section 15 - REGULATORY INFORMATION

weight of components already assessed by IMO, presenting safety hazards", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR List of Chemicals for Priority Action", "WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water"

isobutanol (CAS: 78-83-1) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "IOFI Global Reference List of Chemically Defined Substances", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution – Norway", "Sigma-AldrichTransport Information"

dimethylbenzylammonium chloride (CAS: 1875-92-9) is found on the following regulatory lists;

"Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - inorganic chemicals)", "Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (STOCK - inorganic chemicals)", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm - Domestic water supply quality", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm (IRRIG)", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm (STOCK)", "Australia Drinking Water Guideline Values For Physical and Chemical Characteristics", "Australia National Pollutant Inventory", "WHO Guidelines for Drinking-water Quality - Chemicals for which guideline values have not been established"

Section 16 - OTHER INFORMATION

Denmark Advisory list for selfclassification of dangerous substances

Substance	CAS	Suggested codes
dimethylbenzylammonium chloride	1875- 92- 9	Xn; R22

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.
A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 14-Aug-2013

Print Date: 27-Aug-2013

This is the end of the MSDS.