



Chemical protection

FLUOTECH 344

continuous wear

Comfort and flexibility for extended wear



CHEMICAL PROTECTION
TYPE A

EN388



3121X

EN ISO 374-1



TYPE A
ACDEFGJLMN

EN ISO 374-5



EN407



X1XXXX

CATEGORY 3



0334

DEXTERITY

EN ISO 21420:
2/5

SPECIFIC ADVANTAGES



Comfort

- Excellent comfort for long tasks, due to the cotton-knit interior
- Freedom of movement: good glove flexibility



Durability

- High mechanical resistance and long service life, due to textile support



Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

INDUSTRIES

- Mechanical industry
- Chemical industry
- Other industries

APPLICATIONS

- Metal degreasing and etching
- Chemical treatments (solvents)
- Galvanoplasty
- Handling and transporting chemicals (solvents)
- Manufacturing paints and varnishes
- Resin and adhesive manufacturing
- Emergency interventions on chemical accidents
- Petrochemical refining
- Printing
- Site pollution control



Chemical protection

FLUOTECH 344

continous wear

LEGENDS

EN388	MECHANICAL HAZARDS
	PERFORMANCE LEVELS (X = NOT TESTED)
3 1 2 1 X	
0-4 0-5 0-4 0-4 A-F P	
	Impact protection (optional)
	Cut resistance according to ISO 13997
	Puncture resistance
	Tear resistance
	Blade cut resistance
	Abrasion resistance

EN407	THERMAL RISKS (HEAT AND FIRE)
	PERFORMANCE LEVELS (X = NOT TESTED)
X 1 X X X X	
0-4 0-4 0-4 0-4 0-4 0-4	
	Resistance to large quantities of molten metal
	Small splashes of molten metal
	Radiant heat resistant
	Convective heat resistance
	Contact heat resistance
	Limited flame spread

EN ISO 374-1	CHEMICAL RISKS
	A: Methanol
TYPE A	C: Acetonitrile
	D: Dichloromethane
	E: Carbon Disulfide
	F: Toluene
	G: Diethylamine
	J: n-Heptane
	L: Sulphuric acid 96%
	M: Nitric acid 65%
	N: Acetic acid 99%

EN ISO 374-5	MICRO-ORGANISMS
	Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Textile support
Exterior finish	Smooth
Material	Fluoroelastomer
Cuff characteristic	Feston Cuff
Colour.s	Black
Length (cm)	37
Thickness (mm)	1.6
European sizes	9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	2.7E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	4.3E+10 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 1 pair/carton
-----------	-----------------------------

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/02/19/0479
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France