sixton SAFETY SHOES peak

**EN ISO 20345:2011**

MODULAR

# BRESCIA

**83296-07LL**

**S3 *CI SRC**

**Size:** 41-47 Modular-fit L
**Weight:** 580 gr.

**Fit:** 12,5

**Working Environment:**
Finishing-off building, Logistics and Light Industry, Components and Automotive, ESD Areas

## FEATURES

**UPPER**
Drummed leather Hydro 1,8-2,0 mm
Pu Coated Leather 1,8-2,0 mm
Reflex insert

**LINING**
3D Air circulation 320 gr.

**ANTISLIP LINING**
DUALMICRO

**INSOLE**
Climaction-Fit 337

**TOE CAP**
Fiber cap SXT

**RESISTANCE TO PERFORATION**
KX Antiperforation PS

**TYPE**
Low Shoe

**SOLE**
**PU / PU ESD-PLUS SRC**
Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

S E FO A WRU P SRC CI AVAILABLE

## SRC (SRA+SRB)

SOLE 82
**PU - PU**

| | | |
|---|---|---|
| SRA CERAMIC + DETERGENT SOLUTION | FLAT ≥0.32 | 0.47 |
| | HEEL (CONTACT ANGLE 7°) ≥0.28 | 0.43 |
| SRB STEEL + GLYCEROL | FLAT ≥0.18 | 0.21 |
| | HEEL (CONTACT ANGLE 7°) ≥0.13 | 0.16 |

EN ISO 20344:2011

## TECHNOLOGIES

**Removable Insole**

climaction 337 fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort .

**Protection elements**

KX RESISTANT TO 3.0 mm. NAILS — fibercap sxt

Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail.Protection over the entire sole of the foot. Flexible and comfortable

**Lateral stability**

dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

**Torsional stability**

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.

**Electrical features**

ESD

ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

**Other**

DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.

**Maspica Srl a Socio Unico** Via Einstein,6 - 35020 Casalserugo - Padova / Italy - Cap. Soc. 1.050.000 i.v. - cod. fisc. e Reg. Imp. 04009100282 p. iva IT04009100282
C.C.I.A.A./R.E.A.354572 tel. +39 049 8740771 fax +39 049 8741376 www.sixton.it - info@maspica.it

Questo documento è di proprietà di Maspica Srl a Socio Unico, che si riserva di modificarne i contenuti. È vietata ogni riproduzione, anche parziale