



Main

Range	Acti 9
Product name	Acti 9 Smartlink
Product or component type	Smart communication module
Device application	Basic energy metering E Improved load monitoring E, U, I, P, Pf Load alarming
Connected auxiliaries	Up to 7 More than 7
Device short name	Smartlink SI D
[Us] rated supply voltage	110 V AC 230 V AC
Mounting location	On DIN rail
Product compatibility	Wireless energy sensor
Communication service	Ethernet Modbus TCP/IP server Web server
Web server	Embedded web page BMS controller compatible
Transmission support medium	Radio frequency 2.4 GHz PowerTag 20

Complementary




Application specific I/O	Pulse totalising counter
Immunity to microbreaks	10 ms
Reset	Factory reset on front face
Mounting support	DIN rail
9 mm pitches	6 modules useful on Din rail
Height	85 mm
Width	54 mm
Depth	62 mm
Range compatibility	Acti 9 iEM1500 wireless energy sensor

Commissioning interface	Acti 9 Smart test Web page
Web services	Web page

Environment

Standards	EN/IEC 61131-2 EN/IEC 62053-31
-----------	-----------------------------------

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1631 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available  Product environmental
Product end of life instructions	Available  End of life manual