Eaton 266645

Catalog Number: 266645

Eaton Moeller series NZM - Molded Case Circuit Breaker. Main switch assembly kit, right, frame size 2

General specifications



Eaton Moeller series NZM operating

element

Product Length/Depth

190 mm

Product Width

120 mm

Compliances

UL/CSA IEC

RoHS conform

Catalog Number

266645

EAN

4015082666453

Product Height

110 mm

Product Weight

0.991 kg

Certifications

CE marking CSA certified

CSA (Class No. 1437-01)

UL489

UL (File No. E140305)

UL listed

UL (Category Control Number DIHS)

CSA (File No. 22086)

IEC60947

CSA-C22.2 No. 5-09





Product specifications

Used with

N(S)2(-4)

NZM2(-4)

PN2(-4)

Туре

Accessory

Main switch assembly kit for side panel mounting

Special features

External warning

plate/designation label can

be clipped on.

For enhanced busbar tag

shroud on the incomer side,

please order IP2X protection

against contact with a finger.

Kit for use as a main switch

Features

Lockable

Standard: black / gray

Switch mounting on mounting plate

Actuation of the switch on the control panel side wall

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

Resources

Brochures

 $eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf \\ eaton-digital-nzm-brochure-br013003en-en-us.pdf$

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM2

Drawings

eaton-circuit-breaker-switch-nzm-mccb-dimensions-005.eps eaton-circuit-breaker-switch-nzm-mccb-3d-drawing-004.eps

Installation instructions

eaton-side-wall-actuator-nzm2-xzb-xs-il01206004z.pdf

Installation videos

Introduction of the new digital circuit breaker NZM

The new digital NZM Range

mCAD model

nzm2_xs_r.stp

nzm2_xs_r

Technical data sheets

eaton-nzm-technical-information-sheet

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects $\,$

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Color

Black

Fitted with:

Black and yellow lightning symbol

Extension shaft

Door coupling rotary handle

External warning plate/marking plate in German/English

NZM...-XV4 extension shaft

Padlock

Frame

NZM2

Activation type

Actuation on the right

Suitable for

Switch disconnector

Power circuit breaker

Cover/door type

Door interlock lockable in the 0 position using up to 3 padlocks

on the handle

Door interlock can also be modified in I position

Degree of protection / NEMA enclosure type

IP66

4X. 12



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia