



SERIES 1045 - SUBMINIATURE SNAP-ACTION SWITCH IP 67

TO 10(3) A 250 V AC 1E4




PRODUCT FEATURES

- Dust and water protected switching system according IP 67
- Rating from low DC signal currents to ratings of 10 (3)A 250 VAC
- Versions for high motor rating up to 6 (6) A 250 VAC
- Versions with integrated mechanism for breaking contact weldings
- IEC 60335 Chapter 30 approved for household appliances
- More than 10 million switching cycles

ON REQUEST

- Versions with reduced difference travel
- Versions with mounting pegs to the side
- With asymmetric pinning
- With customized wiring

Design	DIN 41635 B
Mechanical life endurance	10E6, tightness up to 1.5E6 cycles 1E6 (versions with auxiliary actuator)
Contact resistance (new condition)	< 100 mOhm (1 A 12 V DC)
Insulation resistance (new condition)	> 100 MOhm (500 V DC)
Proof tracking	250 PTI
Protection type	IP 00 terminal side basic types 1045 and 1046 IP 40 actuator side basic type 1046 IP 67 actuator side basic type 1045, terminal and actuator side basic type 1048
Ambient temperature	-40 °C ... +100 °C
Flammability	UL 94 V-0
Glow wire test temperature	850 °C
Material additional actuator housing terminals	stainless steel spring steel PA Latamid glass fiber-reinforced tinned / faston terminals blank
Bounce time	< 5 ms
Approval marks	 (61058)
Suitable for appliances of protection class II under compliance with the installation conditions required on the equipment side	

ROCKER SWITCHES
 PUSHBUTTON SWITCHES
 TOGGLE SWITCHES
 SLIDE SWITCHES
 ROTARY SWITCHES
 FOOT SWITCHES
 TACT AND KEY SWITCHES
 SNAP-ACTION SWITCHES
 MICRO-SIGNAL SWITCHES
 SENSORS
 ECO
 PUSH N' DRIVE



SERIES 1045 - SUBMINIATURE SNAP-ACTION SWITCH IP 67

TO 10(3) A 250 V AC 1E4

		Changeover switch (SPDT momentary)				
5 (5) A 250 V AC 10E3					1048.1102	
1 A 250 V AC 100E3						○
3 (3) A 250 V AC 30E3	○					
6 (1) A 250 V AC 30E3						
2 (1) A 250 V AC 100E3						
3 A 250 V AC 100E3						
10 (3) A 250 V AC 10E3						○
6 (6) A 250 V AC 30E3						
Terminal type					⇓	⇓
Terminal description						
Contact material		Ag	Au	Ag		
Operating force (N)		≤ 2.6	≤ 1.9	≤ 2.0		
Operating position (OP) (mm)		8.4 ± 0.3	8.4 ± 0.3	15 ± 1		
Difference travel max. (mm)		0.2	0.2	0.7		
Free position (FP) max. (mm)		9.3	9.3	17		
Permissible total travel position (TP) (mm)		7.6	7.6	13.6		
Actuator		IP 67	IP 67	IP 67		
Actuator description		□	□			
Lever drawing				L22		
Miscellaneous		cable outlet on actuator side	cable outlet down	lever on NC side mounted		
Stock version		○	○	○		

ROCKERSWITCHES

PUSHBUTTON SWITCHES

TOGGLE SWITCHES

SLIDE SWITCHES

ROTARY SWITCHES

FOOT SWITCHES

TACT AND KEY SWITCHES

SNAP-ACTION SWITCHES

MIKRO-SIGNALSCHALTER

SENSORS

ECO

PUSH'DRIVE




SERIES 1045 - SUBMINIATURE SNAP-ACTION SWITCH IP 67


TO 10(3) A 250 V AC 1E4




Basic type 1045




Quick-connect terminal 2.8 x 0.5 sealed




Solder terminal sealed




PCB terminal sealed, coded, cranked



PCB terminal sealed, cranked



PCB terminal sealed, left angled



PCB terminal sealed, right angled

ROCKER SWITCHES

PUSHBUTTON SWITCHES

TOGGLE SWITCHES

SLIDE SWITCHES

ROTARY SWITCHES

FOOT SWITCHES

TACT AND KEY SWITCHES

SNAP-ACTION SWITCHES

MICRO-SIGNAL SWITCHES

SENSORS


ECO

PUSH N' DRIVE



SERIES 1045 - SUBMINIATURE SNAP-ACTION SWITCH IP 67

TO 10(3) A 250 V AC 1E4




Basic type 1046


Quick-connect terminal 2.8 x 0.5 sealed



Basic type 1048




Cable, outlet down




Cable, outlet NC side

Wires potted with switch, wire ends tinned



Cable, outlet C side



Cable, outlet down, normally open contact, mounting pegs

ROCKERSWITCHES

PUSHBUTTON SWITCHES

TOGGLE SWITCHES

SLIDE SWITCHES

ROTARY SWITCHES

FOOT SWITCHES

TACT AND KEY SWITCHES

SNAP-ACTION SWITCHES

MICRO-SIGNAL SWITCHES

SENSORS

ECO

PUSH'N'DRIVE



SERIES 1045 - SUBMINIATURE SNAP-ACTION SWITCH IP 67


TO 10(3) A 250 V AC 1E4




Auxiliary actuators

The auxiliary actuators are available as additional parts for later assembly or are already pre-assembled depending on the product. In the adjustable versions the operating position can be set application-specifically by the set screw.


Switch versions without positive action feature a lever mounting point on the C and NC side, those with positive action only on the C side.




L01: straight lever
191.071.011




L02: straight lever
191.071.021




L02: straight lever, mounted on NC side
191.071.021




L03: straight lever
191.071.101




L11: roller lever
191.078.023




L12: roller lever
191.078.023




L12: roller lever, mounted on NC side
191.078.023



L21: simulated roller
191.071.041



L22: simulated roller
191.071.051



L22: simulated roller, mounted on NC side
191.071.051

ROCKER SWITCHES
PUSHBUTTON SWITCHES
TOGGLE SWITCHES
SLIDE SWITCHES
ROTARY SWITCHES
FOOT SWITCHES
TACT AND KEY SWITCHES
SNAP-ACTION SWITCHES
MICRO-SIGNAL SWITCHES
SENSORS
ECO
PUSH-N-DRIIVE




SERIES 1045 - SUBMINIATURE SNAP-ACTION SWITCH IP 67


TO 10(3) A 250 V AC 1E4




Auxiliary actuators
(continue from page 195)




L32: simulated roller, mounted on NC side
190.372.041



L41: adjustable plastic lever
190.075.013



L43: adjustable roller lever
190.072.013



L45: adjustable simulated roller
190.074.013

Further information under



WWW.MARQUARDT-SWITCHES.COM

THIS DRAWING IS THE EXCLUSIVE PROPERTY OF MARQUARDT. WITHOUT THEIR CONSENT IT MAY NOT BE REPRODUCED OR GIVEN TO THIRD PARTIES.


CONFIDENTIAL

VERTRAULICH


Alle Rechte bei Marquardt, auch fuer den Fall von Schutzrechtsanmeldungen. Jede Veruegungsbefuegnis, wie Kopier- und Weitergaberecht, bei uns.




Empfohlenes Lochbild Bestueckungsseite
Toleranzen nach DIN IEC 326 Teil 3 sehr fein
Recommended hole pattern component side
tolerances acc. to DIN IEC 326 item 3 very fine



Aufschrift
Marking



NC NO
2 4



Wechsler 1-polig
single pole changeover

Schaltbetaetigungskraft ≤ 1.9 N
actuating force

Rueckschaltkraft ≥ 0.5 N
release force

Differenzweg ≤ 0.2 mm
movement differential

IP Schutzklasse nach EN 60529 IP 67
protection class acc to EN 60529 IP 67

G: Konform nach IEC 60335-1:2001 Kap. 30
G: matching IEC 60335-1:2001 clause 30

fuer Form und Lage FOR SHAPE AND LOC.	⊙ =	0.1	Allgemeintoleranzen UNTOLERANCED DIMENSIONS			Pause COPY	Blatt SHEET 01	TYP K	Zeichn./DRAWING NO. 10452101	Index f
	fuer Winkel FOR ANGLE ± 2	↙ +0.25 ↘ +0.1 ↙ -0.25	PROJEKTION	Abmasse und Nennmassbereiche Angaben in mm	Loeenge LENGTH					
			ALL DIMENSIONS ARE IN MILLIMETRES	0-6 ± 0.1 ± 0.2	>6-15 ± 0.15 ± 0.3			SCHNAPPSCHALTER		
				>15-30 ± 0.2 ± 0.5	>30-70 ± 0.3 ± 10%			snap action switch		
				>70-120 ± 0.4	>120 ± 0.8			Ersatz fuer/REPLACEMENT OF		
Ausg. ISSUE	Aenderung REVISION	gez. DRAWN BY	Ausg. ISSUE	Aenderung REVISION	gez. DRAWN BY	CAD: NX v6.0		MARQUARDT		