

# ZXTN2018F

## 60V, SOT23, NPN medium power transistor

### Summary

$V_{(BR)CEV} > 140V$ ,  $V_{(BR)CEO} > 60V$


$I_{C(cont)} = 5A$

$R_{CE(sat)} = 25\ m\Omega$  typical

$V_{CE(sat)} < 45\ mV$  @ 1A


$P_D = 1.2W$

Complementary part number : ZXTP2027F



### Description

Advanced process capability and package design have been used to maximize the power handling and performance of this small outline transistor. The compact size and ratings of this device make it ideally suited to applications where space is at a premium.




### Features

- Higher power dissipation SOT23 package
- High peak current
- Low saturation voltage
- 140V forward blocking voltage

### Applications

- MOSFET and IGBT gate driving
- Motor drive
- Relay, lamp and solenoid drive



Pinout - top view

### Ordering information

| Device      | Reel size (inches) | Tape width (mm) | Quantity per reel |
|-------------|--------------------|-----------------|-------------------|
| ZXTN2018FTA | 7                  | 8               | 3,000             |

### Device marking

851

**Absolute maximum ratings**

| Parameter                                                   | Symbol        | Limit       | Unit                   |
|-------------------------------------------------------------|---------------|-------------|------------------------|
| Collector-base voltage                                      | $V_{CBO}$     | 140         | V                      |
| Collector-emitter voltage                                   | $V_{(BR)CEV}$ | 140         | V                      |
| Collector-emitter voltage                                   | $V_{CEO}$     | 60          | V                      |
| Emitter-base voltage                                        | $V_{EBO}$     | 7           | V                      |
| Peak pulse current                                          | $I_{CM}$      | 12          | A                      |
| Continuous collector current <sup>(a)</sup>                 | $I_C$         | 5           | A                      |
| Base current                                                | $I_B$         | 1           | A                      |
| Power dissipation @ $T_A=25^{\circ}\text{C}$ <sup>(a)</sup> | $P_D$         | 1.0         | W                      |
| Linear derating factor                                      |               | 8.0         | mW/ $^{\circ}\text{C}$ |
| Power dissipation @ $T_A=25^{\circ}\text{C}$ <sup>(b)</sup> | $P_D$         | 1.2         | W                      |
| Linear derating factor                                      |               | 9.6         | mW/ $^{\circ}\text{C}$ |
| Power dissipation @ $T_A=25^{\circ}\text{C}$ <sup>(c)</sup> | $P_D$         | 1.56        | W                      |
| Linear derating factor                                      |               | 12.5        | mW/ $^{\circ}\text{C}$ |
| Operating and storage temperature                           | $T_j:T_{stg}$ | -55 to +150 | $^{\circ}\text{C}$     |

**Thermal resistance**

| Parameter                          | Symbol         | Value | Unit                        |
|------------------------------------|----------------|-------|-----------------------------|
| Junction to ambient <sup>(a)</sup> | $R\theta_{JA}$ | 125   | $^{\circ}\text{C}/\text{W}$ |
| Junction to ambient <sup>(b)</sup> | $R\theta_{JA}$ | 104   | $^{\circ}\text{C}/\text{W}$ |
| Junction to ambient <sup>(c)</sup> | $R\theta_{JA}$ | 80    | $^{\circ}\text{C}/\text{W}$ |






**NOTES:**

(a) Mounted on 18mm x 18mm X 1.6mm FR4 PCB with a very high coverage of 2 oz weight copper in still air conditions.

(b) Mounted on 30mm x 30mm X 1.6mm FR4 PCB with a very high coverage of 2 oz weight copper in still air conditions.

(c) as (b) above measured at  $t < 5\text{secs}$ .

## Characteristics








## Electrical characteristics (at $T_{amb} = 25^{\circ}\text{C}$ unless otherwise stated)

| Parameter                             | Symbol        | Min.                   | Typ.                               | Max.                                | Unit                             | Conditions                                                                                                                                                                                                                                                                     |
|---------------------------------------|---------------|------------------------|------------------------------------|-------------------------------------|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Collector-base breakdown voltage      | $V_{(BR)CBO}$ | 140                    | 180                                |                                     | V                                | $I_C=100\mu\text{A}$                                                                                                                                                                                                                                                           |
| Collector-emitter breakdown voltage   | $V_{(BR)CEV}$ | 140                    | 180                                |                                     | V                                | $I_C=1\mu\text{A}$ ,<br>$-1\text{V} < V_{BE} < +0.3\text{V}$                                                                                                                                                                                                                   |
| Collector-emitter breakdown voltage   | $V_{(BR)CEO}$ | 60                     | 80                                 |                                     | V                                | $I_C=10\text{mA}$ <sup>(a)</sup>                                                                                                                                                                                                                                               |
| Emitter-base breakdown voltage        | $V_{(BR)EBO}$ | 7                      | 8                                  |                                     | V                                | $I_E=100\mu\text{A}$                                                                                                                                                                                                                                                           |
| Collector-emitter cut-off current     | $I_{CEV}$     |                        | <1                                 | 20                                  | nA                               | $V_{CE}=110\text{V}$ ,<br>$V_{BE} = -1\text{V}$                                                                                                                                                                                                                                |
| Collector-base cut-off current        | $I_{CBO}$     |                        | <1                                 | 20                                  | nA                               | $V_{CB}=110\text{V}$                                                                                                                                                                                                                                                           |
| Emitter-base cut-off current          | $I_{EBO}$     |                        | <1                                 | 10                                  | nA                               | $V_{EB}=6\text{V}$                                                                                                                                                                                                                                                             |
| Static forward current transfer ratio | $H_{FE}$      | 100<br>100<br>40<br>15 | 220<br>200<br>65<br>25             | 300                                 |                                  | $I_C=10\text{mA}$ , $V_{CE}=1\text{V}^{(a)}$<br>$I_C=2\text{A}$ , $V_{CE}=1\text{V}^{(a)}$<br>$I_C=5\text{A}$ , $V_{CE}=1\text{V}^{(a)}$<br>$I_C=10\text{A}$ , $V_{CE}=1\text{V}^{(a)}$                                                                                        |
| Collector-emitter saturation voltage  | $V_{CE(sat)}$ |                        | 15<br>35<br>40<br>85<br>145<br>170 | 30<br>45<br>55<br>110<br>170<br>210 | mV<br>mV<br>mV<br>mV<br>mV<br>mV | $I_C=0.1\text{A}$ , $I_B=5\text{mA}^{(a)}$<br>$I_C=1\text{A}$ , $I_B=100\text{mA}^{(a)}$<br>$I_C=1\text{A}$ , $I_B=50\text{mA}^{(a)}$<br>$I_C=2\text{A}$ , $I_B=50\text{mA}^{(a)}$<br>$I_C=5\text{A}$ , $I_B=250\text{mA}^{(a)}$<br>$I_C=6\text{A}$ , $I_B=300\text{mA}^{(a)}$ |
| Base-emitter saturation voltage       | $V_{BE(sat)}$ |                        | 0.92                               | 1.00                                | V                                | $I_C=5\text{A}$ , $I_B=250\text{mA}^{(a)}$                                                                                                                                                                                                                                     |
| Base-emitter turn-on voltage          | $V_{BE(on)}$  |                        | 0.85                               | 0.95                                | V                                | $I_C=5\text{A}$ , $V_{CE}=1\text{V}^{(a)}$                                                                                                                                                                                                                                     |
| Transition frequency                  | $f_T$         |                        | 130                                |                                     | MHz                              | $I_C=100\text{mA}$ , $V_{CE}=10\text{V}$ ,<br>$f=50\text{MHz}$                                                                                                                                                                                                                 |
| Output capacitance                    | $C_{obo}$     |                        | 28                                 |                                     | pF                               | $V_{CB}=10\text{V}$ , $f=1\text{MHz}$                                                                                                                                                                                                                                          |
| Turn-on time                          | $t_{(on)}$    |                        | 33                                 |                                     | ns                               | $V_{CC}=10\text{V}$ , $I_C=1\text{A}$ ,                                                                                                                                                                                                                                        |
| Turn-off time                         | $t_{(off)}$   |                        | 668                                |                                     | ns                               | $I_{B1}=I_{B2}=100\text{mA}$                                                                                                                                                                                                                                                   |


### NOTES:

(a) Measured under pulsed conditions. Pulse width=300 $\mu\text{s}$ . Duty cycle  $\leq 2\%$ .

## Typical characteristics



## Packaging details - SOT23



| Dim. | Millimeters |      | Inches    |        | Dim. | Millimeters |      | Inches     |        |
|------|-------------|------|-----------|--------|------|-------------|------|------------|--------|
|      | Min.        | Max. | Min.      | Max.   |      | Min.        | Max. | Max.       | Max.   |
| A    | 2.67        | 3.05 | 0.105     | 0.120  | H    | 0.33        | 0.51 | 0.013      | 0.020  |
| B    | 1.20        | 1.40 | 0.047     | 0.055  | K    | 0.01        | 0.10 | 0.0004     | 0.004  |
| C    | -           | 1.10 | -         | 0.043  | L    | 2.10        | 2.50 | 0.083      | 0.0985 |
| D    | 0.37        | 0.53 | 0.015     | 0.021  | M    | 0.45        | 0.64 | 0.018      | 0.025  |
| F    | 0.085       | 0.15 | 0.0034    | 0.0059 | N    | 0.95 NOM    |      | 0.0375 NOM |        |
| G    | 1.90 NOM    |      | 0.075 NOM |        | -    | -           | -    | -          | -      |

**Note:** Controlling dimensions are in millimeters. Approximate dimensions are provided in inches

| Europe                                                                            | Americas                                                                    | Asia Pacific                                                                             | Corporate Headquarters                                                                             |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------|------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| Zetex GmbH<br>Streitfeldstraße 19<br>D-81673 München<br>Germany                   | Zetex Inc<br>700 Veterans Memorial Highway<br>Hauppauge, NY 11788<br>USA    | Zetex (Asia Ltd)<br>3701-04 Metroplaza Tower 1<br>Hing Fong Road, Kwai Fong<br>Hong Kong | Zetex Semiconductors plc<br>Zetex Technology Park, Chadderton<br>Oldham, OL9 9LL<br>United Kingdom |
| Telefon: (49) 89 45 49 49 0<br>Fax: (49) 89 45 49 49 49<br>europe.sales@zetex.com | Telephone: (1) 631 360 2222<br>Fax: (1) 631 360 8222<br>usa.sales@zetex.com | Telephone: (852) 26100 611<br>Fax: (852) 24250 494<br>asia.sales@zetex.com               | Telephone (44) 161 622 4444<br>Fax: (44) 161 622 4446<br>hq@zetex.com                              |

These offices are supported by agents and distributors in major countries world-wide.

This publication is issued to provide outline information only which (unless agreed by the company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contact or be regarded as a representation relating to the products or services concerned. The company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.