


# Electrical Application Labels




## CABLE MARKING LABELS



Repositional Vinyl Cloth (B-400), Self-Laminating Vinyl (B-427),  
Nylon Cloth (B-499), Self-Laminating Tedlar® (B-642)

Diagram	Reference	Labels Per Roll	Label Dimensions		Write-On Height C mm	Maximum Characters Per Line For Font:			Maximum Lines Of Text For Font:			Max. Cable diameter mm
			A mm	B mm		2	7	10	2	7	10	
▲	PTL-21-400	100	25.40	63.50		24	10	7	23	14	9	14
◐	PTL-21-427**	100	25.40	63.50	19.05	24	10	7	8	4	2	14
◑	BPTL-21-427	1000	25.40	63.50	19.05	24	10	7	8	4	2	14
▲	PTL-21-499	100	25.40	63.50		24	10	7	23	14	9	14
◐	PTL-21-642	100	25.40	63.50	19.05	24	10	7	8	4	2	14
▲	PTL-23-400	100	25.40	101.60		24	10	7	23	22	15	24
◐	PTL-23-427**	100	25.40	101.60	25.40	24	10	7	10	5	3	24
◑	BPTL-23-427	1000	25.40	101.60	25.40	24	10	7	10	5	3	24
▲	PTL-33-400	100	38.10	101.60		37	15	10	23	22	15	24
◐	PTL-33-427**	100	38.10	101.60	25.40	37	15	10	10	5	3	24
◑	BPTL-33-427	1000	38.10	101.60	25.40	37	15	10	10	5	3	24
▲	PTL-34-400	50	38.10	152.40		37	15	10	22	22	21	36
◐	PTL-34-427**	50	38.10	152.40	38.10	37	15	10	16	8	5	36
◑	BPTL-34-427	500	38.10	152.40	38.10	37	15	10	16	8	5	36
◒	PTL-66-427	100	49.23	80.00	25.40	46	19	13	10	5	3	24

\*\*Also available in: OR=orange, GN=green, GY=grey, PL=purple, BL=blue, BR=brown, YL=yellow, RD=red.  
To order a colour, add a dash "-" after the reference, then add the colour suffix.  
Standard product: Contact your BRADY Identification Solutions distributor or Customer Service representative for ordering information.



## White or Yellow Tedlar® Film (B-437)


Reference	Roll Length m	Label Dimensions		Maximum Characters Per Line For Font:			Maximum Lines Of Text For Font:		
		A mm	B mm	2	7	10	2	7	10
PTLCM-41-437-W	15m	38.10	continuous	37	15	10	14	7	4
PTLCM-41-437-YL	15m	38.10	continuous	37	15	10	14	7	4

Tedlar® is a registered trademark of DuPont.

TLS2200® / TLS PC LINK™ ELECTRICAL APPLICATION LABELS

# Electrical Application Labels

CONTINUED



## WIRE MARKING LABELS

Repositional Vinyl Cloth (B-400), Self-Laminating Vinyl (B-427),  
Nylon Cloth (B-499), Self-Laminating Tedlar® (B-642)

Diagram	Reference	Labels Per Roll	Label Dimensions		Write-On Height C mm	Maximum Characters Per Line For Font:			Maximum Lines Of Text For Font:			Max. Wire diam. mm
			A mm	B mm		2	7	10	2	7	10	
▶	PTL-10-427*	750	6.35	19.05	9.53	5	2	1	3	1	1	3
▶	PTL-11-427*	500	12.70	19.05	9.53	11	5	3	3	1	1	3
▶	BPTL-11-427	5000	12.70	19.05	9.53	11	5	3	3	1	1	3
▲	PTL-7-400	500	12.70	12.70		11	5	3	5	2	1	4
▲	PTL-7-499	500	12.70	12.70		11	5	3	5	2	1	4
▶	PTL-17-427*	500	12.70	25.40	9.53	11	5	3	3	1	1	5
▶	BPTL-17-427	5000	12.70	25.40	9.53	11	5	3	3	1	1	5
▶	PTL-18-427*	250	19.05	25.40	9.53	18	7	5	3	1	1	5
▶	BPTL-18-427	2500	19.05	25.40	9.53	18	7	5	3	1	1	5
▶	PTL-19-427**	250	25.40	25.40	9.53	24	10	7	3	1	1	5
▶	BPTL-19-427	2500	25.40	25.40	9.53	24	10	7	3	1	1	5
▶	PTL-19-642	250	25.40	25.40	9.53	24	10	7	3	1	1	5
▲	PTL-11-400	500	12.70	19.05		11	5	3	8	4	2	6
▲	BPTL-11-400	5000	12.70	19.05		11	5	3	8	4	2	6
▲	PTL-11-499	500	12.70	19.05		11	5	3	8	4	2	6
▲	BPTL-11-499	5000	12.70	19.05		11	5	3	8	4	2	6
▶	PTL-28-427**	750	6.35	38.10	12.70	5	2	1	5	2	1	8
▶	PTL-29-427**	500	12.70	38.10	12.70	11	5	3	5	2	1	8
▶	PTL-30-427**	250	19.05	38.10	12.70	18	7	5	5	2	1	8
▶	BPTL-30-427	2500	19.05	38.10	12.70	18	7	5	5	2	1	8
▶	PTL-31-427**	250	25.40	38.10	12.70	24	10	7	5	2	1	8
▶	BPTL-31-427	2500	25.40	38.10	12.70	24	10	7	5	2	1	8
▶	PTL-31-642	250	25.40	38.10	12.70	24	10	7	5	2	1	8
▶	PTL-32-427**	250	38.10	38.10	12.70	37	15	10	5	2	1	8
▶	BPTL-32-427	2500	38.10	38.10	12.70	37	15	10	5	2	1	8
▲	PTL-16-400	500	9.52	25.40		8	3	2	10	5	3	8
▲	PTL-16-499	500	9.52	25.40		8	3	2	10	5	3	8
▲	PTL-18-400	250	19.05	25.40		18	7	5	10	5	3	8
▲	BPTL-18-400	2500	19.05	25.40		18	7	5	10	5	3	8
▲	PTL-18-499	250	19.05	25.40		18	7	5	10	5	3	8
▲	PTL-19-400	250	25.40	25.40		24	10	7	10	5	3	8
▲	BPTL-19-400	2500	25.40	25.40		24	10	7	10	5	3	8
▲	PTL-19-499	250	25.40	25.40		24	10	7	10	5	3	8
▲	PTL-28-499	750	6.35	38.10		5	2	1	16	8	5	12
▲	PTL-28-400	750	6.35	38.10		5	2	1	16	8	5	12
▲	PTL-29-400	500	12.70	38.10		11	5	3	16	8	5	12
▲	BPTL-29-400	5000	12.70	38.10		11	5	3	16	8	5	12
▲	PTL-29-499	500	12.70	38.10		11	5	3	16	8	5	12
▲	PTL-30-400	250	19.05	38.10		18	7	5	16	8	5	12
▲	PTL-30-499	250	19.05	38.10		18	7	5	16	8	5	12
▲	PTL-31-499	250	25.40	38.10		24	10	7	16	8	5	12
▲	PTL-31-400	250	25.40	38.10		24	10	7	16	8	5	12

Tedlar® is a registered trademark of DuPont.

\* Also available in: YL=Yellow

\*\*Also available in: OR=orange, GN=green, GY=grey, PL=purple, BL=blue, BR=brown, YL=yellow, RD=red.  
To order a colour, add a dash "-" after the reference, then add the colour suffix.

Standard product: Contact your BRADY Identification Solutions distributor or Customer Service representative for ordering information.

# Electrical Application Labels

CONTINUED




## TUBESLEEVE™ WIRE MARKERS - THE SLIDE-ON, SELF-LAMINATING MARKING SOLUTION.

This marking solution combines the advantages of a non-adhesive repositionable marker with the advantages of a computer printable self-laminating label.

Reference	Outside wire diameter	Tube length	Corresponding BRADY Wire Markers
TS 1/4-13	1-4mm	13mm	PTL-17-427
TS 1/4-26	1-4mm	26mm	PTL-19-427
TS 4/6-13	4-6mm	13mm	PTL-17-427
TS 4/6-26	4-6mm	26mm	PTL-19-427
TS 6/8-13	6-8mm	13mm	PTL-29-427
TS 6/8-26	6-8mm	26mm	PTL-21-427
			PTL-23-427

## PERMASLEEVE™ WIRE MARKING SLEEVES

Heat-Shrinkable White Polyolefin (B-342)



Reference	Sleeves Per Roll	Sleeve Dimensions		Range of Wire Min mm	Diameter Max mm	Maximum Characters Per Line For Font:			Maximum Lines Of Text For Font:		
		A mm	B mm			2	7	10	2	7	10

### 25.78 mm Marker width

#### WHITE 3:1 SHRINK RATIO

PSPT-094-1W	100	25.78	4.62	0.58	2.03	22	0	0	1	0	0
BPSPT-094-1W	1000	25.78	4.62	0.58	2.03	22	0	0	1	0	0
PSPT-125-1W	100	25.78	5.96	1.17	2.79	22	0	0	1	0	0
BPSPT-125-1W	1000	25.78	5.96	1.17	2.79	22	0	0	1	0	0
PSPT-187-1W	100	25.78	8.50	1.57	3.81	22	9	0	2	1	0
BPSPT-187-1W	1000	25.78	8.50	1.57	3.81	22	9	0	2	1	0
PSPT-250-1W	100	25.78	11.15	2.39	5.46	22	9	6	3	1	1
BPSPT-250-1W	1000	25.78	11.15	2.39	5.46	22	9	6	3	1	1
PSPT-375-1W	100	25.78	16.38	3.18	8.13	22	9	6	5	2	1
PSPT-500-1W	100	25.78	21.61	4.75	11.43	22	9	6	7	3	2
PSPT-1000-1W	50	25.78	42.16	11.43	24.13	22	9	6	16	8	5

#### YELLOW 3:1 SHRINK RATIO

PSPT-094-1YL	100	25.78	4.62	0.58	2.03	22	0	0	1	0	0
PSPT-125-1YL	100	25.78	5.96	1.17	2.79	22	0	0	1	0	0
PSPT-187-1YL	100	25.78	8.50	1.57	3.81	22	9	0	2	1	0
PSPT-250-1YL	100	25.78	11.15	2.39	5.46	22	9	6	3	1	1
PSPT-375-1YL	100	25.78	16.38	3.18	8.13	22	9	6	5	2	1
PSPT-500-1YL	100	25.78	21.61	4.75	11.43	22	9	6	7	3	2
PSPT-1000-1YL	50	25.78	42.16	11.43	24.13	22	9	6	16	8	5

### 44.83 mm Marker width

#### WHITE 3:1 SHRINK RATIO


PSPT-094-175W	100	44.83	4.62	0.58	2.03	41	0	0	1	0	0
BPSPT-094-175W	1000	44.83	4.62	0.58	2.03	41	0	0	1	0	0
PSPT-125-175W	100	44.83	5.96	1.17	2.79	41	0	0	1	0	0
BPSPT-125-175W	1000	44.83	5.96	1.17	2.79	41	0	0	1	0	0
PSPT-187-175W	100	44.83	8.50	1.57	3.81	41	17	11	3	1	1
BPSPT-187-175W	1000	44.83	8.50	1.57	3.81	41	17	11	3	1	1
PSPT-250-175W	100	44.83	11.15	2.39	5.46	41	17	11	3	1	1
BPSPT-250-175W	1000	44.83	11.15	2.39	5.46	41	17	11	3	1	1
PSPT-375-175W	100	44.83	16.38	3.18	8.13	41	17	11	5	2	1
BPSPT-375-175W	1000	44.83	16.38	3.18	8.13	41	17	11	5	2	1
PSPT-500-175W	100	44.83	21.61	4.75	11.43	41	17	11	7	3	2
BPSPT-500-175W	1000	44.83	21.61	4.75	11.43	41	17	11	7	3	2
PSPT-1000-175W	50	44.83	42.16	11.43	24.13	41	17	11	16	8	5
BPSPT-1000-175W	500	44.83	42.16	11.43	24.13	41	17	11	16	8	5

#### YELLOW 3:1 SHRINK RATIO

PSPT-094-175YL	100	44.83	4.62	0.58	2.03	41	0	0	1	0	0
PSPT-125-175YL	100	44.83	5.96	1.17	2.79	41	0	0	1	0	0
BPSPT-125-175YL	100	44.83	5.96	1.17	2.79	41	0	0	1	0	0
PSPT-187-175YL	100	44.83	8.50	1.57	3.81	41	17	11	3	1	1
BPSPT-187-175YL	100	44.83	8.50	1.57	3.81	41	17	11	3	1	1
PSPT-250-175YL	100	44.83	11.15	2.39	5.46	41	17	11	3	1	1
BPSPT-250-175YL	100	44.83	11.15	2.39	5.46	41	17	11	3	1	1
PSPT-375-175YL	100	44.83	16.38	3.18	8.13	41	17	11	5	2	1
PSPT-500-175YL	100	44.83	21.61	4.75	11.43	41	17	11	7	3	2
PSPT-1000-175YL	50	44.83	42.16	11.43	24.13	41	17	11	16	8	5

# Electrical Application Labels

CONTINUED




## BRADYSLEEVE™ WIRE MARKING SLEEVES

### Heat-Shrinkable White Polyolefin (B-321)

Reference	Sleeves Per Roll	Sleeve Dimensions		Range of Wire Min. mm	Diameter Max. mm	Maximum Characters Per Line For Font:			Maximum Lines Of Text For Font:		
		A mm	B mm			2	7	10	2	7	10
<b>11.43 mm Sleeve Width</b>											
PTS.45-350-321	500	11.43	8.89	1.90	4.06	9	3	0	2	1	0
PTS.45-500-321	500	11.43	12.70	4.06	5.97	9	3	2	4	2	1
<b>24.13 mm Sleeve Width</b>											
PTS.95-350-321	500	24.13	8.89	1.90	4.06	21	9	0	2	1	0
PTS.95-500-321	500	24.13	12.70	4.06	5.97	21	9	6	4	2	1
PTS.95-750-321	250	24.13	19.05	8.51	9.91	21	9	6	7	3	2
PTS.95-1000-321	250	24.13	25.40	9.53	13.72	21	9	6	10	5	3
<b>48.26 mm Sleeve Width</b>											
PTS.190-350-321	500	48.26	8.89	1.90	4.06	44	18	0	2	1	0
PTS.190-500-321	500	48.26	12.70	4.06	5.97	44	18	12	4	2	1
PTS.190-750-321	250	48.26	19.05	8.51	9.91	44	18	12	7	3	2
PTS.190-1000-321	250	48.26	25.40	9.53	13.72	44	18	12	10	5	3

*Note: Labels are sorted in order by width, height, 3 digit material number (within reference).*



## DURASLEEVE™ WIRE MARKING SLEEVES

### Vinyl Tag Material (B-7596)

Reference	Inserts Per Roll	Insert Dimensions		Maximum Characters Per Line For Font:			Maximum Lines For Font:		
		A mm	B mm	2	7	10	2	7	10
PTDSU-15-7596	2500	15.00	4.20	14	0	0	1	0	0
PTDSU-15-7596-YL	2500	15.00	4.20	14	0	0	1	0	0
PTDSU-30-7596	2500	30.00	4.10	27	0	0	1	0	0
PTDSU-30-7596-YL	2500	30.00	4.10	27	0	0	1	0	0


## DURASLEEVE™ WIRE MARKING CARRIERS

Reference	Carrier Length mm	Wire diameter mm	Carriers per Box
DMC-1.5/2.5-15	15.00	1.5 - 2.5	1000
DMC-1.5/2.5-30	30.00		500
DMC-2/4-15	15.00	2.0 - 4.0	1000
DMC-2/4-30	30.00		500
DMC-4/7-15	15.00	4.0 - 7.0	500
DMC-4/7-30	30.00		200
DMC-6/10-15	15.00	6.0 - 10.0	500
DMC-6/10-30	30.00		200

ELECTRICAL APPLICATION LABELS / TLS2200® / TLS PC LINK™

# Electrical Application Labels



CONTINUED



## ▶ **BRADYTAGS® PRINTABLE TAGS** **Polyethylene (B-109)**

Diagram	Reference	Tags Per Roll	Tag Dimensions		Maximum Characters Per Line For Font:			Maximum Lines Of Text For Font:			Applications/Description
			A mm	B mm	2	7	10	2	7	10	
▲	PTL-12-109	100	19.05	76.20	45	19	12	6	3	2	Product ID for harsh environments/tear resistant
▲	BPTL-12-109	1000	19.05	76.20	45	19	12	6	3	2	Product ID for harsh environments/tear resistant
▶	PTL-36-109	250	44.45	28.57	34	14	9	12	6	4	Product ID for harsh environments/tear resistant
▲	PTL-60-109	100	12.00	50.00	41	17	11	5	2	1	Product ID for harsh environments/tear resistant

## ▶ **TERMINAL BLOCK MARKERS** **Repositional Vinyl Cloth (B-400) - Translucent polyester (B-7551)**



Reference	Roll Length m	Label Dimensions		Maximum Characters Per Line For Font:			Maximum Lines Of Text For Font:		
		A mm	B mm	2	7	10	2	7	10
PTLTB-5-7551	15m	4.50	continuous	4	2	1	-----	N/A	-----
PTLTB-400-240	9m	6.09	continuous	5	2	1	-----	N/A	-----
BPTLTB-400-240	91m	6.09	continuous	5	2	1	-----	N/A	-----
PTLTB-8-7551	15m	8.00	continuous	7	3	2	-----	N/A	-----
PTLTB-400-318	9m	8.07	continuous	7	3	2	-----	N/A	-----
BPTLTB-400-318	91m	8.07	continuous	7	3	2	-----	N/A	-----
PTLTB-400-375	9m	9.53	continuous	8	3	2	-----	N/A	-----
BPTLTB-400-375	91m	9.53	continuous	8	3	2	-----	N/A	-----

## ▶ **ELECTRICAL COMPONENT MARKERS**



## **Nylon Cloth (B-499)/Polyethylene-Foam laminate (B-7595) Polypropylene (B-412)**

Reference	Labels per roll	Label Dimensions		Maximum Characters Per Line For Font:			Maximum Lines Of Text For Font:		
		A mm	B mm	2	7	10	2	7	10
PTL-47-499-YL	750	20.00	8.00	18	7	5	2	1	0
PTL-67-499-YL	750	15.00	9.00	14	5	3	3	1	1
PTL-57-412	15m	12.70	continuous	50	50	50	5	2	1
PTLEP-01-7595	250	27.00	8.00	26	11	0	3	1	1
PTLEP-02-7595	250	27.00	12.50	26	11	7	5	2	1
PTLEP-03-7595	150	27.00	15.00	26	11	7	6	3	2
PTLEP-04-7595	150	27.00	18.00	26	11	7	8	4	2
BPTLEP-05-7595	750	30.00	40.00	29	12	8	5	2	1
BPTLEP-05-7595-GN	750	30.00	40.00	29	12	8	5	2	1
BPTLEP-05-7595-RD	750	30.00	40.00	29	12	8	5	2	1

TL2200® / TLS PC LINK™ ELECTRICAL APPLICATION LABELS