

Project..... **Comments**.....

Fixture Type..... **Prepared By**.....

Product Description:

Get the strong performance and convenience you need, along with easy installation in minimal ceiling voids, with our compact form E9 fire rated downlight. Integrated LED driver technology eliminates the need for selecting and installing a separate, remote driver. Suitable for use in 30, 60 and 90-minute fire rated ceilings, the E9 is acoustic rated to maintain the ability for an internal or separating floor to provide sound insulation. It is also rated IP65 to resist water vapour and has a colour rendering index (CRI) of 80. With a 25,000-hour lifetime to L70, E9 comes with a 3 year warranty.

Product Image:



Product Features:

- IP65 Rated
- Integrated LED driver
- ErP compliant - High colour rendering index (Ra) >80
- Non-dimmable
- Tested in 30, 60 & 90 minute fire rated ceilings - BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- UK Patent Application - 1212923.5
- Registered Community Designs - 001861261/001926940
- Life to 70% lumen maintenance (L70) - 25,000 hours
- 3 year warranty

Product Specs:

| | |
|-----------------|-------------------------------|
| Input Voltage | 100~240V AC |
| Input Frequency | 50/60Hz |
| Power Factor | 0.5 |
| Dimmable | No |
| Dimensions | 105mm (H) x 88mm x 105mm (RD) |
| Number of LEDs | 3 |

Compliance & Approvals:



SKU Table and Ordering

| Cat. No. | Color | lm | Wattage | Lumens/Watt | Quantity |
|------------|-------|-------|---------|-------------|----------|
| EN-E9W/40 | 4000K | 430lm | 9W | 47.78 | |
| EN-E9W/30 | 3000K | 420lm | 9W | 46.67 | |
| EN-E9SN/40 | 4000K | 430lm | 9W | 47.78 | |
| EN-E9SN/30 | 3000K | 420lm | 9W | 46.67 | |
| EN-E9PC/40 | 4000K | 430lm | 9W | 47.78 | |
| EN-E9PC/30 | 3000K | 420lm | 9W | 46.67 | |

Warranty:

This product has a warranty period of 3 Years from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, and removal of the Q.C. date label; installation in an improper working environment or installation not according to the current edition of the National Electric Code. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Sales

16 Alban Park Hatfield Road
St. Albans AL4 0JJ

United Kingdom

Tel : +44 (0) 1727 83 66 11

Fax : +44 (0) 1727 83 66 22

UK Distribution

Apex Park 6 Little Burrow
Welwyn Garden City AL7
4SW

United Kingdom

Tel : +44 (0) 1707 35 18 20

Fax : +44 (0) 1727 35 18 21