ALTO 298

Prolonged contact (or immersion) | short wear

Good mechanical performance for long-lasting chemical protection

SPECIFIC ADVANTAGES



Durability

 Longer service life and good impact protection, due to the thickness of the material



Guaranteed quality

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



Additional benefits

Longer length provides forearm protection

INDUSTRIES

- Mechanical industry
- Other industries

APPLICATIONS

- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Maintenance in wet environments
- Pharmaceutical industry



CHEMICAL PROTECTION

TYPE A





EN ISO 374-1



AKLMPT

EN ISO 374-5



CATEGORY 3

DEXTERITY



EN420: 5/5

0334



ALTO 298

Prolonged contact (or immersion) | short wear

LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

	•			ILJI	LD)		
,	1		3	1	X		
4	0-5	0	-4	0-4	A-F	Impact protection (optional)	
						out resistance according to ISO 3997	
Ab			cut	ar resi t resis	esistance		
		В	0-5 0	Tea Blade cu	1 3 1 4 0-5 0-4 0-4	Punctu Tear resistance Blade cut resistance	

EN ISO 374-1



TYPE A

CHEMICAL RISKS

A: Methanol K: Sodium hydroxide 40% L: Sulphuric acid 96%

M: Nitric acid 65%

P: Hydrogen peroxide 30% T: Formaldehyde 37%

1: Formaid



MICRO-ORGANISMS

Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Chlorinated
Exterior finish	Smooth
Material	Natural latex
Cuff characteristic	Feston Cuff
Colour.s	Blue
Length (cm)	43
Thickness (mm)	1.05
European sizes	8 9 10

LOGISTIC DETAILS

Packaging	1 pair/bag 5 pairs/bag
	50 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1704
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

