



## ZEROSMOG SHIELD „Black Edition“ FUME EXTRACTION

ORDER NO: FT91019190

- > Efficient EPA E10 particle and gas filtration, odour removal for single workbench
- > Illuminated work area for an optimal work environment
- > Powerful blower with adjustable extraction power
- > Low maintenance extraction unit with easy to change filter
- > Low noise level of 50dB
- > Stackable with soldering stations of all brands (max. footprint 13 cm x 18 cm)
- > Antistatic housing (ESD safe)



### Cheers to 80 Years of Weller - Designed for the innovators of tomorrow

Breathe clean air while at your workbench working on your next soldering task with the Weller ZeroSmog Shield, a true filtration unit that keeps your work environment clean and fresh. Its compact design, which can be stacked with soldering stations, helps maximize your workspace. With the ZeroSmog Shield, you can breathe easy and focus on your soldering.

## + KEY FEATURES

- > **BREATHE IN THE ESSENCE OF CLEAN AIR**  
The ZeroSmog Shield ensures better air quality by capturing solder particles and gases. Our filters consist of EPA E10 (for particles) and activated carbon (for gases).
- > **ENHANCE YOUR EXPERIENCE**  
The extraction system keeps the workplace quiet. Low noise levels create a calm atmosphere and ensure a pleasant and comfortable experience.
- > **COUNT ON SMART DESIGN**  
The compact design is a space-saving marvel. It is slim and stackable. This not only saves valuable bench space, but also adds a touch of modern sophistication to your work area.
- > **SEAMLESS CONVENIENCE FOR YOU**  
A quick and easy filter change improves the user experience.
- > **WORK ZONE IDENTIFICATION**  
The best extraction area for efficient filtration is clearly indicated by a bright working light.

TECHNICAL DATA ZEROSMOG SHIELD BLACK EDITION	
<b>Dimensions L x W x H</b>	269.5 x 212 x 110 mm 10.6 x 8.3 x 4.3 inch
<b>Mains supply voltage</b>	100-240 V AC 50/60 Hz
<b>Operating voltage</b>	24 V DC
<b>Power consumption</b>	10 W
<b>Weight</b>	2 kg
<b>Safety class</b>	III
<b>Combined filter</b>	E10 EPA / Activated carbon foam
<b>Maximum vacuum</b>	285 Pa
<b>Maximum airflow</b>	26 m <sup>3</sup> /h
<b>Operating sound level from 1 m distance</b>	50 dBA at full speed
<b>Subject to technical alterations and amendments.</b>	

