

Power base, TeSys U, 3P, 38A/690V

Local distributor code:

425225583 LUB38

EAN Code: 3389111493688

Main

Mairi		
Range	TeSys	
product name	TeSys Ultra	
Device short name	LUB	
Product or component type	Non reversing power base	
Device application	Motor control Motor protection	
Poles description	3P	
Suitability for isolation	Yes	
[Ue] rated operational voltage	690 V AC for power circuit	
Network frequency	4060 Hz	
[lth] conventional free air thermal current	38 A	
[le] rated operational current	35 A at <= 440 V 28 A at 500 V 24 A at 690 V	
Utilisation category	AC-43 AC-41	
[lcs] rated service breaking capacity	25 kA at 230 V 25 kA at 440 V 10 kA at 500 V 4 kA at 690 V	
Auxiliary contact composition	1 NO + 1 NC	
Auxiliary contacts type	type linked contacts (1 NO + 1 NC) conforming to IEC 60947-4-1 type mirror contact (1 NC) conforming to IEC 60947-1	
[Uc] control circuit voltage	24 V AC 50/60 Hz 24 V DC 4872 V AC 50/60 Hz 4872 V DC 110240 V AC 50/60 Hz 110220 V DC	

Complementary

Typical current consumption	200 mA at 24 V DC I maximum while closing with LUCM 220 mA at 24 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD 220 mA at 24 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD 25 mA at 110220 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD 25 mA at 110220 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD 280 mA at 110220 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD 280 mA at 110240 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD 280 mA at 4872 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD 280 mA at 4872 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD 45 mA at 4872 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD 45 mA at 4872 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD 75 mA at 24 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD 90 mA at 24 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD	
Heat dissipation	3 W for control circuit with LUCA, LUCB, LUCC, LUCD 1.8 W for control circuit with LUCM	
Safety reliability level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1	
Operating time	35 ms opening with LUCA, LUCB, LUCC, LUCD, LUCM for control circuit 50 ms at >= 72 V closing with LUCA, LUCB, LUCC, LUCD for control circuit 60 ms at 48 V closing with LUCA, LUCB, LUCC, LUCD for control circuit 70 ms at 24 V closing with LUCA, LUCB, LUCC, LUCD for control circuit 65 ms closing with LUCM for control circuit	
Mechanical durability	15 Mcycles	
Maximum operating rate	3600 cyc/h	
Product certifications	CE UL CSA CCC EAC	
Standards	EN 60947-6-2 IEC 60947-6-2 UL 60947-4-1, with phase barrier CSA C22.2 No 60947-4-1, with phase barrier	
[Ui] rated insulation voltage	690 V conforming to IEC 60947-6-2 (pollution degree 3) 600 V conforming to UL 60947-4-1 600 V conforming to CSA C22.2 No 60947-4-1	
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-6-2	
Safe separation of circuit	400 V SELV between the control and auxiliary circuits conforming to IEC 60947-1 appendix N 400 V SELV between the control or auxiliary circuit and the main circuit conforming to IEC 60947-1 appendix N	
Fixing mode	Clipped (DIN rail) Screw-fixed (plate)	
Connections - terminals	Control circuit: screw clamp terminals 1 cable(s) 0.341.5 mm² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 0.751.5 mm² flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 0.751.5 mm² rigid Control circuit: screw clamp terminals 2 cable(s) 0.341.5 mm² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 0.751.5 mm² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 0.751.5 mm² rigid Power circuit: screw clamp terminals 1 cable(s) 110 mm² rigid Power circuit: screw clamp terminals 1 cable(s) 16 mm² flexible with cable end Power circuit: screw clamp terminals 1 cable(s) 2.510 mm² flexible without cable	

ir degree or protection	n IP20 conforming to IEC 60947-1 (front panel and wired terminals) IP20 conforming to IEC 60947-1 (other faces) IP40 conforming to IEC 60947-1 (front panel outside connection zone)	
Environment IP degree of protection	IP20 conforming to IEC 60047.1 (front panel and wired terminals)	
Compatibility code	LUB	
Net weight	0.9 kg	
Depth	126 mm	
Height	154 mm	
Width	45 mm	
	Power circuit: 1.92.5 N.m pozidriv No 2 screwdriver 6 mm	
	Power circuit: 1.92.5 N.m flat screwdriver 6 mm Power circuit: 1.92.5 N.m Philips No 2 screwdriver 6 mm	
Tightening torque	Control circuit: 0.81.2 N.m flat screwdriver 5 mm Control circuit: 0.81.2 N.m Philips no 1 screwdriver 5 mm	

IP degree of protection	IP20 conforming to IEC 60947-1 (front panel and wired terminals) IP20 conforming to IEC 60947-1 (other faces) IP40 conforming to IEC 60947-1 (front panel outside connection zone)	
Protective treatment	TH conforming to IEC 60068	
Ambient air temperature for operation	-2560 °C with LUCM -2570 °C with LUCA, LUCB, LUCC, LUCD	
Ambient air temperature for storage	-4085 °C	
Fire resistance	960 °C parts supporting live components conforming to IEC 60695-2-12 650 °C conforming to IEC 60695-2-12	
Operating altitude	2000 m	
Shock resistance	10 gn power poles open conforming to IEC 60068-2-27 15 gn power poles closed conforming to IEC 60068-2-27	
Vibration resistance	2 gn (f= 5300 Hz) power poles open conforming to IEC 60068-2-27 4 gn (f= 5300 Hz) power poles closed conforming to IEC 60068-2-27	
Resistance to electrostatic discharge	8 kV level 3 in open air conforming to IEC 61000-4-2 8 kV level 4 on contact conforming to IEC 61000-4-2	
Non-dissipating shock wave	1 kV serial mode 24240 V AC conforming to IEC 60947-6-2 1 kV serial mode 48220 V DC conforming to IEC 60947-6-2 2 kV common mode 24240 V AC conforming to IEC 60947-6-2 2 kV common mode 48220 V DC conforming to IEC 60947-6-2	
Resistance to fast transients	2 kV class 3 serial link conforming to IEC 61000-4-4 4 kV class 4 all circuits except for serial link conforming to IEC 61000-4-4	
Resistance to radiated fields	10 V/m 3 conforming to IEC 61000-4-3	
Immunity to radioelectric fields	10 V conforming to IEC 61000-4-6	
Immunity to microbreaks	3 ms for control circuit	
Immunity to voltage dips	70 % / 500 ms conforming to IEC 61000-4-11	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.200 cm
Package 1 Width	17.000 cm
Package 1 Length	14.500 cm
Package 1 Weight	848.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	10

Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	8.756 kg

Logistical informations

Country of origin FR

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	44
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
SCIP Number	61f5a085-dfde-4214-b2cf-ba3cfe0c33b4
REACh Regulation	REACh Declaration
Halogen content performance	Product contains halogen above thresholds
PVC free	Yes

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

Assembly's dimensions



