

# Eaton 183724

Catalog Number: 183724

Eaton Moeller series IZMX/INX - ACB. Circuit-breaker, 3p, 3200A, 105 kA, Selective operation, IEC, Fixed

General specifications



Product Name	Catalog Number
Eaton Moeller series IZMX/INX circuit-breaker	183724
	EAN
	4015081794607
Product Length/Depth	Product Height
584 mm	597 mm
Product Width	Product Weight
521 mm	45 kg
Compliances	
IEC/EN 60947	
IEC	
RoHS conform	

## Delivery program

### Type

Air circuit breakers/switch-  
disconnecter  
Open circuit breaker

### Frame

IZMX40

### Number of poles

Three-pole

### Amperage Rating

3200 A

### Release system

Electronic release

## Technical data - electrical

### Voltage rating at AC

690 V AC

### Rated operating voltage (Ue) - min

690 V

### Rated operating voltage (Ue) - max

690 V

### Rated insulation voltage (Ui)

1000 V

### Rated impulse withstand voltage (Uimp)

12 kV AC

### Rated uninterrupted current (Iu)

3200 A

### Rated uninterrupted current (Iu) at 50°C

3200 A

### Rated uninterrupted current (Iu) at 60°C

3200 A

### Rated uninterrupted current (Iu) at 70°C

3200 A

### Rated short-time withstand current (t = 1 s)

85 kA

### Rated short-time withstand current at 50/60 Hz (t = 3 s)

66 kA

### Overload release current setting - min

1280 A

### Overload release current setting - max

3200 A

### Short-circuit release delayed setting - min

2400 A

### Short-circuit release delayed setting - max

32000 A

### Short-circuit release non-delayed setting

1.5 - 10 x I<sub>r</sub>

### Short-circuit release non-delayed setting - min

0 A

### Short-circuit release non-delayed setting - max

48000 A

Adjustment range short-term delayed short-circuit release - min  
1920 A

Adjustment range short-term delayed short-circuit release - max  
32000 A

Adjustment range undelayed short-circuit release - min  
6400 A

Adjustment range undelayed short-circuit release - max  
48000 A

Rated short-circuit breaking capacity at 400 V, 50 Hz  
105 kA

Rated short-circuit making capacity up to 440 V, 50/60 Hz  
231 kA

Rated short-circuit making capacity up to 690 V, 50/60 Hz  
166 kA

Power loss  
385 W

Closing delay via spring release  
35 ms

Electrical connection type of main circuit  
Rail connection

Number of standard mechanical operations per hour - max  
60

Operating sequence up to 690 V, 50/60 Hz (IEC/EN 60947)  
85 kA

Utilization category  
B

Overvoltage category  
III

Pollution degree  
3

Direction of incoming supply  
As required

Lifespan, electrical  
10000 operations (switching cycles ON/OFF, with maintenance)  
5000 operations (switching capacity)

## Technical data - mechanical

### Device construction

Built-in device fixed built-in technique

### Mounting Method

Fixed

### Degree of protection

IP55 with protective cover

IP31

IP31 with door seals

### Protection

Selective operation

### Number of auxiliary contacts (change-over contacts)

2

### Number of auxiliary contacts (normally closed contacts)

0

### Number of auxiliary contacts (normally open contacts)

0

### Position of connection for main current circuit

Back side

### Weight of fixed mounting version (3-pole)

43 kg

### Actuator type

Push button

### Terminal capacity (copper bar)

80 mm x 10 mm (3x) for fixed mounting (black)

### Lifespan, mechanical

10000 switching cycles (ON/OFF)

20000 operations (switching capacity, with maintenance)

## Design verification as per IEC/EN 61439 - technical data

### Rated operational current for specified heat dissipation (In)

3200 A

### Equipment heat dissipation, current-dependent

385 W

### Heat dissipation at rated current with fixed mounting

385 W

#### Ambient operating temperature details

-20 °C - 70 °C

#### Ambient operating temperature - min

-20 °C

#### Ambient operating temperature - max

70 °C

#### Ambient storage temperature - min

-20 °C

#### Ambient storage temperature - max

70 °C

## Design verification as per IEC/EN 61439

### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.7 Inscriptions

Meets the product standard's requirements.

### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

### 10.8 Connections for external conductors

Is the panel builder's responsibility.

### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Additional information

### Features

Motor drive optional

Complete device with protection unit

### Fitted with:

Switched-off indicator

### Special features

Main terminals must be separately ordered.

suitable for zone selectivity

optionally fittable by user

with comprehensive accessories

Terminal capacity hint:

These are values used in separate switchgear. The actual values will depend on the temperature around the circuit breaker, which is influenced by the ambient temperature, the degree of protection (IP), the mounting height, the partitions, and any external ventilation.

Depending on the specific switchgear design, this may result in derating, which can then be compensated for by increasing the cross-sectional area. Temperature rise tests in the specific switchgear can provide specific and detailed information.

### Used with

Open circuit breaker

Air circuit breakers/switch-disconnector

## Resources

### Catalogs

[eaton-acb-izmx-catalog-ca01305001z-en-us.pdf](#)

### Declarations of conformity

[DA-DC-03\\_IZMX40](#)

[DA-DC-03\\_IZMX40\\_111017](#)

## Drawings

[eaton-circuit-breaker-mounting-izmx-inx-mccb-dimensions.eps](#)

[eaton-circuit-breaker-mounting-izmx-inx-mccb-dimensions-002.eps](#)

[eaton-circuit-breaker-izmx-inx-mccb-dimensions-013.eps](#)

## eCAD model

[DA-CE-ETN.IZMX40H3-V32F-1](#)

## Installation videos

[Air Circuit Breakers Series IZMX](#)

## Manuals and user guides

[MN013002\\_EN](#)

## mCAD model

[DA-CD-izmx40\\_3pol\\_f](#)

[DA-CS-izmx40\\_3pol\\_f](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](#)