

Turbo 2 ultrafast high voltage rectifier

Main product characteristics


| | |
|----------------|--------|
| $I_{F(AV)}$ | 30 A |
| V_{RRM} | 600 V |
| T_j | 175° C |
| V_F (typ) | 1.10 V |
| t_{rr} (max) | 50 ns |

Features and benefits

- Ultrafast switching
- Low reverse current
- Low thermal resistance
- Reduces switching & conduction losses
- Package insulation voltage:
DOP3I : 2500 V_{RMS}

Description

The STTH3006 uses ST Turbo 2 600 V technology and is especially suited for use in switching power supplies, and industrial applications, such as rectification and continuous mode PFC boost diode.



Order Codes

| Part Number | Marking |
|-------------|------------|
| STTH3006D | STTH3006D |
| STTH3006W | STTH3006W |
| STTH3006PI | STTH3006PI |

Table 1. Absolute Ratings (limiting values)

| Symbol | Parameter | | Value | Unit |
|--------------|--|-------------------|--------------|------|
| V_{RRM} | Repetitive peak reverse voltage | | 600 | V |
| $I_{F(RMS)}$ | RMS forward voltage | | 50 | A |
| $I_{F(AV)}$ | Average forward current | TO-220AC / DO-247 | 30 | A |
| | | DOP3I | | |
| I_{FSM} | Surge non repetitive forward current | | 160 | A |
| T_{stg} | Storage temperature range | | -65 to + 175 | ° C |
| T_j | Maximum operating junction temperature | | 175 | ° C |

1 Characteristics

Table 2. Thermal resistance

| Symbol | Parameter | | Value (max). | Unit |
|---------------|------------------|-------------------|--------------|------|
| $R_{th(j-c)}$ | Junction to case | TO-220AC / DO-247 | 1.1 | °C/W |
| | | DOP3I | 1.7 | |

Table 3. Static electrical characteristic

| Symbol | Parameter | Test conditions | | Min. | Typ | Max. | Unit |
|-------------|-------------------------|---------------------|-----------------|------|------|------|---------|
| $I_R^{(1)}$ | Reverse leakage current | $T_j = 25^\circ C$ | $V_R = V_{RRM}$ | | | 25 | μA |
| | | $T_j = 150^\circ C$ | | | 80 | 800 | |
| $V_F^{(2)}$ | Forward voltage drop | $T_j = 25^\circ C$ | $I_F = 30 A$ | | | 1.85 | V |
| | | $T_j = 150^\circ C$ | | | 1.10 | 1.40 | |

1. Pulse test: $t_p = 5 ms, \delta < 2\%$
2. Pulse test: $t_p = 380 \mu s, \delta < 2\%$

To evaluate the conduction losses use the following equation:

$$P = 1.07 \times I_{F(AV)} + 0.011 I_F^2(RMS)$$

Table 4. Dynamic characteristics

| Symbol | Parameter | Test conditions | | Min. | Typ | Max. | Unit |
|----------|--------------------------|---------------------|---|------|-----|------|------|
| t_{rr} | Reverse recovery time | $T_j = 25^\circ C$ | $I_F = 0.5 A \quad I_{rr} = 0.25 A \quad I_R = 1 A$ | | | 50 | ns |
| | | | $I_F = 1 A \quad dl_F/dt = -50 A/\mu s \quad V_R = 30 V$ | | 50 | 70 | |
| I_{RM} | Reverse recovery current | $T_j = 125^\circ C$ | $I_F = 30 A \quad V_R = 400 V \quad dl_F/dt = -100 A/\mu s$ | | 8 | 11 | A |
| t_{fr} | Forward recovery time | $T_j = 25^\circ C$ | $I_F = 30 A \quad dl_F/dt = 100 A/\mu s \quad V_{FR} = 1.1 \times V_{Fmax}$ | | | 500 | ns |
| V_{FP} | Forward recovery voltage | $T_j = 25^\circ C$ | $I_F = 30 A \quad dl_F/dt = 100 A/\mu s \quad V_{FR} = 1.1 \times V_{Fmax}$ | | 2.5 | | V |

Figure 1. Conduction losses versus average forward current




Figure 2. Forward voltage drop versus forward current




Figure 3. Relative variation of thermal impedance junction to case versus pulse duration




Figure 4. Peak reverse recovery current versus dIF/dt (typical values)




Figure 5. Reverse recovery time versus dIF/dt (typical values)




Figure 6. Reverse recovery charges versus dIF/dt (typical values)




Figure 7. Softness factor versus di_F/dt (typical values)




Figure 8. Relative variations of dynamic parameters versus junction temperature




Figure 9. Transient peak forward voltage versus di_F/dt (typical values)




Figure 10. Forward recovery time versus di_F/dt (typical values)





Figure 11. Junction capacitance versus reverse voltage applied (typical values)




2 Package information

- Epoxy meets UL94, V0
- Cooling method: by conduction (C)
- Recommended torque value: 0.55 Nm (TO-220AC)
- Maximum torque value: 0.70 Nm (TO-220AC)

Table 5. DO247 dimensions

| Ref. | Dimensions | | | | | |
|------|-------------|-------|-------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 4.85 | | 5.15 | 0.191 | | 0.203 |
| D | 2.20 | | 2.60 | 0.086 | | 0.102 |
| E | 0.40 | | 0.80 | 0.015 | | 0.031 |
| F | 1.00 | | 1.40 | 0.039 | | 0.055 |
| F2 | | 2.00 | | | 0.078 | |
| F3 | 2.00 | | 2.40 | 0.078 | | 0.094 |
| G | | 10.90 | | | 0.429 | |
| H | 15.45 | | 15.75 | 0.608 | | 0.620 |
| L | 19.85 | | 20.15 | 0.781 | | 0.793 |
| L1 | 3.70 | | 4.30 | 0.145 | | 0.169 |
| L2 | | 18.50 | | | 0.728 | |
| L3 | 14.20 | | 14.80 | 0.559 | | 0.582 |
| L4 | | 34.60 | | | 1.362 | |
| L5 | | 5.50 | | | 0.216 | |
| M | 2.00 | | 3.00 | 0.078 | | 0.118 |
| V | | 5° | | | 5° | |
| V2 | | 60° | | | 60° | |
| Dia. | 3.55 | | 3.65 | 0.139 | | 0.143 |

Table 6. TO-220AC dimensions



| Ref. | Dimensions | | | |
|---------|-------------|-------|------------|-------|
| | Millimeters | | Inches | |
| | Min. | Max. | Min. | Max. |
| A | 4.40 | 4.60 | 0.173 | 0.181 |
| C | 1.23 | 1.32 | 0.048 | 0.051 |
| D | 2.40 | 2.72 | 0.094 | 0.107 |
| E | 0.49 | 0.70 | 0.019 | 0.027 |
| F | 0.61 | 0.88 | 0.024 | 0.034 |
| F1 | 1.14 | 1.70 | 0.044 | 0.066 |
| G | 4.95 | 5.15 | 0.194 | 0.202 |
| H2 | 10.00 | 10.40 | 0.393 | 0.409 |
| L2 | 16.40 typ. | | 0.645 typ. | |
| L4 | 13.00 | 14.00 | 0.511 | 0.551 |
| L5 | 2.65 | 2.95 | 0.104 | 0.116 |
| L6 | 15.25 | 15.75 | 0.600 | 0.620 |
| L7 | 6.20 | 6.60 | 0.244 | 0.259 |
| L9 | 3.50 | 3.93 | 0.137 | 0.154 |
| M | 2.6 typ. | | 0.102 typ. | |
| Diam. I | 3.75 | 3.85 | 0.147 | 0.151 |

Table 7. DOP3I dimensions

| Ref. | Dimensions | | | |
|------|-------------|-------|------------|-------|
| | Millimeters | | Inches | |
| | Min. | Max. | Min. | Max. |
| A | 4.40 | 4.60 | 0.173 | 0.181 |
| b | 1.20 | 1.40 | 0.047 | 0.055 |
| c | 1.45 | 1.55 | 0.057 | 0.061 |
| c1 | 0.50 | 0.70 | 0.020 | 0.028 |
| D | 12.15 | 13.10 | 0.474 | 0.516 |
| E | 15.10 | 15.50 | 0.594 | 0.610 |
| E1 | 7.55 | 7.75 | 0.297 | 0.305 |
| e | 10.80 | 11.30 | 0.425 | 0.445 |
| G | 20.4 | 21.10 | 0.815 | 0.831 |
| L | 14.35 | 15.60 | 0.565 | 0.614 |
| P | 4.08 | 4.17 | 0.161 | 0.164 |
| Q | 2.70 | 2.90 | 0.106 | 0.114 |
| R | 4.60 typ. | | 0.181 typ. | |
| Y | 15.80 | 16.50 | 0.622 | 0.650 |

3 Ordering information

| Ordering type | Marking | Package | Weight | Base qty | Delivery mode |
|---------------|------------|----------|--------|----------|---------------|
| STTH3006D | STTH3006D | TO-220AC | 1.90 g | 50 | Tube |
| STTH3006W | STTH3006W | DO-247 | 4.40 g | 30 | Tube |
| STTH3006PI | STTH3006PI | DOP3I | 4.46 g | 30 | Tube |

4 Revision history

| Date | Revision | Changes |
|-------------|----------|---|
| 22-May-2006 | 1 | Initial release. |
| 10-Aug-2006 | 2 | Added Package insulation voltage on page 1 for DOP3I. |

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2006 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com