

https://www.phoenixcontact.com/gb/products/1884924



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing, Range of articles: VARIOCON, design: VC4, color: gray, When using fiber optics, the bending radii of the cable manufacturers must be observed.

Commercial data

Item number	1884924
Packing unit	5 pc
Minimum order quantity	5 pc
Note	Made to order (non-returnable)
Sales key	ABLAAB
Product key	ABLAAB
Catalog page	Page 369 (PC-2009)
GTIN	4017918187057
Weight per piece (including packing)	390.047 g
Weight per piece (excluding packing)	390.047 g
Customs tariff number	85369010
Country of origin	PL

1884924

https://www.phoenixcontact.com/gb/products/1884924



Technical data

Notes

General	When using fiber optics, the bending radii of the cable manufacturers must be observed.
Safety note	
Safety note	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.
	 WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.
	 WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
	 The products are suitable for applications in plant, controller, and electrical device engineering.
	 When operating the connectors in outdoor applications, they must be separately protected against environmental influences.
	 Assembled products may not be manipulated or improperly opened.
	 Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).
	 When using the product in direct connection with third-party manufacturers, the user is responsible.
	 For operating voltages > 50 V AC, conductive connector housings must be grounded
	 Ensure that the protective or functional ground has been properly connected.
	VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector
	Observe the corresponding technical data. You will find information: o On the product o On the packing label o In the supplied documentation o Online at phoenixcontact.com/products under the product
	Only use tools recommended by Phoenix Contact
	 The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product.
	 Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products
	Operate the connector only when it is fully plugged in.



https://www.phoenixcontact.com/gb/products/1884924



 Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.
 Observe the minimum bending radius of the cable. Lay the cable without twisting it.
 The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).

Product properties

Product type	Sleeve housings
Product family	VARIOCON
Туре	VC4
No. of cable outlets	1
Number of module slots	5
Type of the screw connection	1x Pg21
Shielded	no
Cable outlet	slanted

Connection data

Tightening torque	1.2 1.8 Nm
-------------------	------------

Dimensions

Dimensional drawing	2.6
Width	33 mm
Height	78 mm
Length	111 mm
Thread type on seal side	Pg21

Material specifications

Color	gray
Color of the housing part	gray
Material Housing	Die-cast zinc
Material	NBR (O-ring)
Material Seal	EPDM
Flammability rating according to UL 94	V0
Material of locking screw	Stainless steel

Mechanical properties

Mechanical data

Type of the screw connection	1x Pg21



1884924

https://www.phoenixcontact.com/gb/products/1884924

Locking type	Screw	
Environmental and real-life conditions		
Ambient conditions		
Degree of protection	IP67 (IEC 60529)	
	IP65/IP66/IP67	
Ambient temperature (operation)	-40 °C 125 °C	


1884924

https://www.phoenixcontact.com/gb/products/1884924




Drawings

Dimensional drawing



Dimensional drawing






https://www.phoenixcontact.com/gb/products/1884924



Dimensional drawing





1884924

https://www.phoenixcontact.com/gb/products/1884924

Classifications

ECLASS

	ECLASS-13.0	27440202	
ETIM			
	ETIM 9.0	EC000437	
UNSPSC			
	UNSPSC 21.0	31261500	



https://www.phoenixcontact.com/gb/products/1884924



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT Ltd Halesfield 13, Telford Shropshire, TF7 4PG 01952 681700 info@phoenixcontact.co.uk