
SYLVANIA

Product selected: Sylproof Superia PC T5 16mmØ 1x35W lamp with A2 ballast

Moisture proof diffuser luminaire. Housing made of polycarbonate. Colour light grey. With top and fitting end cut outs for mains supply and further wiring as well as for through wiring by means of heat resistant internal wiring. Injection mulded diffuser with internal prism for even lighting distribution. Diffuser fixed to the body by using stainless steel clips. Inject gasket for high IP rate. Aluminium reflector. Gear tray made of steel, saved by maintenance cord. D-Mark for electronic ballast version. Polyurethane seal gasket


Product Image







Light distribution



120°	1
_ \	105°
	105
	90°
_	75°
V	
<i>]</i> }	60°
<	
\rightarrow	45°
\ ,	
30°	

Certifications











Product Details Order code Item name Sylproof Superia PC T5 16mmØ 1x35W lamp with A2 ballast Mounting Ceiling pendant, Ceiling surface Technical description Polycarbonate body & diffuser. Stainless steel fixing Place of use Interior Colour Grey Length (mm) 1565 Width (mm) 92 Height (mm) 99 Weight (kg) 2.4 Housing Polycarbonate Shock resistance 2 J Distribution type Symmetric Diffuser finish Prismatic Diffuser material LOR (%) Reflector material Lor (%) Reflector material Polycarbonate Lamps description 1 x 35W T16 G5 Lamp included No Number of heads Control gear availability Control gear description Control gear mounting Integral T Class Max 25°C Cottod (%) Voltage (V) 200-240		
Order code 0056197 Item name Sylproof Superia PC T5 16mmØ 1x35W lamp with A2 ballast Mounting Ceiling pendant, Ceiling surface Technical description Polycarbonate body & diffuser. Stainless steel fixing Place of use Interior Colour Grey Length (mm) 1565 Width (mm) 92 Height (mm) 99 Weight (kg) 2.4 Housing Polycarbonate Shock resistance 2 J Distribution type Symmetric Diffuser finish Prismatic Diffuser material Polycarbonate LOR (%) 80% Reflector finish Aluminium Reflector material Polycarbonate Lamps description 1 x 35W T16 G5 Lamp included No Number of heads 1 Control gear availability Included Control gear type Electronic Control gear mounting Integral T Class Max 25°C T Class Min 0°C	Product Details	
Mounting Ceiling pendant, Ceiling surface Technical description Polycarbonate body & diffuser. Stainless steel fixing Place of use Interior Colour Grey Length (mm) 1565 Width (mm) 92 Height (mm) 99 Weight (kg) 2.4 Housing Polycarbonate Shock resistance 2 J Distribution type Symmetric Diffuser finish Prismatic Diffuser material Polycarbonate LOR (%) 80% Reflector finish Aluminium Reflector material Polycarbonate Lamps description 1 x 35W T16 G5 Lamp included No Number of heads 1 Control gear availability Included Control gear description Electronic Control gear mounting Integral T Class Max 25°C T Class Min 0°C		0056197
Technical description Polycarbonate body & diffuser. Stainless steel fixing Place of use Interior Grey Length (mm) 1565 Width (mm) 92 Height (mm) 99 Weight (kg) 2.4 Housing Polycarbonate Shock resistance 2 J Distribution type Symmetric Diffuser finish Prismatic Diffuser material LOR (%) Reflector finish Reflector material Lamps description 1 x 35W T16 G5 Lamp included No Number of heads Control gear availability Control gear description Electronic Control gear mounting T Class Max 25°C T Class Min	Item name	Sylproof Superia PC T5 16mmØ 1x35W lamp with A2 ballast
Place of use Colour Grey Length (mm) 1565 Width (mm) 92 Height (mm) 99 Weight (kg) 2.4 Housing Polycarbonate Shock resistance 2 J Distribution type Symmetric Diffuser finish Prismatic Diffuser material LOR (%) Reflector finish Reflector material Lamps description Lamp included No Number of heads Control gear availability Control gear description Control gear mounting T Class Max 25°C T Class Min Pg Included Infegral Infegral Infegral Infegral Infegral T Class Max 25°C T Class Min	Mounting	Ceiling pendant, Ceiling surface
Colour Length (mm) 1565 Width (mm) 92 Height (mm) 99 Weight (kg) 2.4 Housing Polycarbonate Shock resistance 2 J Distribution type Symmetric Diffuser finish Prismatic Diffuser material LOR (%) Reflector finish Aluminium Reflector material Polycarbonate Lamps description 1 x 35W T16 G5 Lamp included No Number of heads 1 Control gear availability Control gear description Electronic Control gear mounting T Class Max 25°C T Class Min Oe Polycarbonate 1.565 2.4 Housing Polycarbonate Polycarbonate Polycarbonate 1 x 35W T16 G5 Electronic Electronic Electronic Control gear availability Included Integral T Class Max 25°C T Class Min O°C	Technical description	Polycarbonate body & diffuser. Stainless steel fixing
Length (mm) Width (mm) 92 Height (mm) 99 Weight (kg) 2.4 Housing Polycarbonate Shock resistance 2 J Distribution type Symmetric Diffuser finish Prismatic Diffuser material LOR (%) Reflector finish Aluminium Reflector material Lamps description 1 x 35W T16 G5 Lamp included No Number of heads 1 Control gear availability Control gear description Electronic Control gear description Integral T Class Max 25°C T Class Min	Place of use	Interior
Width (mm) Height (mm) 99 Weight (kg) 2.4 Housing Polycarbonate Shock resistance 2 J Distribution type Symmetric Diffuser finish Prismatic Diffuser material LOR (%) Reflector finish Reflector material Lamps description Lamp included No Number of heads Control gear availability Control gear description Control gear description Electronic Control gear mounting T Class Max 25°C T Class Min	Colour	Grey
Height (mm) Weight (kg) 2.4 Housing Polycarbonate Shock resistance 2 J Distribution type Symmetric Diffuser finish Prismatic Diffuser material LOR (%) Reflector finish Reflector material Lamps description Lamp included No Number of heads Control gear availability Control gear description Electronic Control gear description Electronic ballast with reduced losses Control gear mounting T Class Max 25°C T Class Min	Length (mm)	1565
Weight (kg) Housing Polycarbonate Shock resistance 2 J Distribution type Symmetric Diffuser finish Prismatic Diffuser material LOR (%) Reflector finish Reflector material Lamps description Lamps included No Number of heads Control gear availability Control gear description Control gear description Electronic Electronic ballast with reduced losses Control gear mounting T Class Max 25°C T Class Min	Width (mm)	92
Housing Shock resistance 2 J Distribution type Symmetric Diffuser finish Prismatic Diffuser material LOR (%) Reflector finish Reflector material Lamps description 1 x 35W T16 G5 Lamp included No Number of heads 1 Control gear availability Control gear description Electronic Control gear mounting T Class Max T Class Min Polycarbonate 1 x 35W T16 G5 Included Electronic Electronic Control gear description Electronic ballast with reduced losses	Height (mm)	99
Shock resistance Distribution type Symmetric Diffuser finish Prismatic Diffuser material Polycarbonate LOR (%) Reflector finish Reflector material Polycarbonate Lamps description 1 x 35W T16 G5 Lamp included No Number of heads 1 Control gear availability Control gear type Electronic Control gear description Electronic ballast with reduced losses Control gear mounting T Class Max T Class Min Prismatic Prismatic Polycarbonate 1 x 35W T16 G5 Lamp included No No Number of heads 1 Control gear availability Included Control gear type Electronic Control gear description Control gear description Control gear mounting O°C	Weight (kg)	2.4
Distribution type Diffuser finish Prismatic Diffuser material Polycarbonate LOR (%) Reflector finish Reflector material Polycarbonate Lamps description 1 x 35W T16 G5 Lamp included No Number of heads 1 Control gear availability Control gear type Electronic Control gear description Electronic ballast with reduced losses Control gear mounting T Class Max 25°C T Class Min Prismatic Prismatic Prismatic No Row Reflector Row Row Reflector finish Aluminium Reflector finish Aluminium Integral Polycarbonate Integral Polycarbonate Integral Integral O°C	Housing	Polycarbonate
Diffuser finish Prismatic Diffuser material Polycarbonate LOR (%) Reflector finish Aluminium Reflector material Polycarbonate Lamps description 1 x 35W T16 G5 Lamp included No Number of heads 1 Control gear availability Included Control gear type Electronic Control gear description Electronic ballast with reduced losses Control gear mounting Integral T Class Max 25°C T Class Min	Shock resistance	2 J
Diffuser material LOR (%) Reflector finish Reflector material Lamps description Lamp included No Number of heads Control gear availability Control gear type Control gear description Electronic Control gear mounting T Class Max Diffuser material Polycarbonate 1 x 35W T16 G5 No No No No Rumber of heads 1 Lamp included Electronic Electronic Electronic Electronic Diffuser material Polycarbonate 1 x 35W T16 G5 No No No Number of heads 1 Control gear availability Included Electronic Electronic Control gear description Electronic ballast with reduced losses Control gear mounting T Class Max O°C	Distribution type	Symmetric
LOR (%) Reflector finish Reflector material Lamps description 1 x 35W T16 G5 Lamp included No Number of heads 1 Control gear availability Control gear type Electronic Control gear description Electronic ballast with reduced losses Control gear mounting T Class Max 25°C T Class Min	Diffuser finish	Prismatic
Reflector finish Reflector material Polycarbonate Lamps description 1 x 35W T16 G5 Lamp included No Number of heads 1 Control gear availability Included Control gear type Electronic Control gear description Electronic ballast with reduced losses Control gear mounting T Class Max 25°C T Class Min O°C	Diffuser material	Polycarbonate
Reflector material Lamps description 1 x 35W T16 G5 Lamp included No Number of heads 1 Control gear availability Control gear type Electronic Control gear description Electronic ballast with reduced losses Control gear mounting T Class Max 25°C T Class Min Polycarbonate 1 x 35W T16 G5 No No No No Electronic description Electronic Control gear availability Included 25°C T Class Min O°C	LOR (%)	80%
Lamps description 1 x 35W T16 G5 Lamp included No Number of heads 1 Control gear availability Included Control gear type Electronic Control gear description Electronic ballast with reduced losses Control gear mounting Integral T Class Max 25°C T Class Min 0°C	Reflector finish	Aluminium
Lamp included No Number of heads Control gear availability Control gear type Electronic Control gear description Electronic ballast with reduced losses Control gear mounting T Class Max 25°C T Class Min No Included Electronic Electronic Electronic ballast with reduced losses O°C	Reflector material	Polycarbonate
Number of heads Control gear availability Control gear type Electronic Control gear description Electronic ballast with reduced losses Control gear mounting T Class Max 25°C T Class Min 1 Included Electronic Electronic Dallast with reduced losses O°C	Lamps description	1 x 35W T16 G5
Control gear availability Control gear type Electronic Control gear description Electronic ballast with reduced losses Control gear mounting T Class Max 25°C T Class Min O°C	Lamp included	No
Control gear type Control gear description Control gear mounting T Class Max T Class Min Electronic Electronic ballast with reduced losses Control gear mounting Integral 25°C T Class Min 0°C	Number of heads	1
Control gear description Electronic ballast with reduced losses Control gear mounting T Class Max 25°C T Class Min 0°C	Control gear availability	Included
Control gear mounting T Class Max 25°C T Class Min 0°C	Control gear type	Electronic
T Class Max 25°C T Class Min 0°C	Control gear description	Electronic ballast with reduced losses
T Class Min 0°C	Control gear mounting	Integral
	T Class Max	25°C
Voltage (V) 220-240	T Class Min	0°C
	Voltage (V)	220-240