

The trusted value of OSRAM Digital Systems continues with Inventronics Global – where experience meets innovation.

PL-CN50-COB -1400-930-15D-G3

PL COIN 50 COB G3 | Spot-, Down- and Wallmount Light Engines and Modules



Product family features

- Color consistency < 2 SDCM (15D version <3 SDCM)
- TM30 compliant
- High flux output up to 1500 lm
- Beam angle: 15°, 24°, 40°, 60°
- Type of protection: IP20

Product family benefits

- Compatible with conventional MR16 lamps
- Precise optical control and free from multi-shadow issue
- Replaceable front cover to maximize optics flexibility and future extension



Areas of application

- Retail, shop, restaurant, hospitality
- High-end residential
- Suitable for indoor applications
- Connecting multiple modules in parallel on one LED driver is not permitted
- Connecting multiple modules in series on one LED driver is not recommended
- Do not use in sealed fixtures
- Avoid covering the lens with dust or any object

Technical data

Electrical data

Nominal current	0.35 A
Type of current	DC
On-mode power	12.7 W
Energy consumption in on-mode	12.7 kWh/1000h
Maximum forward voltage	38 V

Photometrical data

Luminous efficacy	88 lm/W
Peak luminous intensity	9549
Correlated color temperature CCT	3000 K
Colour consistency (McAdam ellipses)	2
Useful luminous flux (Φ_{use})	1059 lm
Color rendering index Ra	90

Light technical data

Beam angle	15 °
Starting time	0 s
Warm-up time (60 %)	0 s

LED module information

Number of LEDs per module	1
---------------------------	---

Dimensions & weight

Product weight	91.00 g
Height EPREL	55 mm
Length EPREL	50 mm
Width EPREL	50 mm

Temperatures & operating conditions

Performance temp. acc. to IEC 62717	75 °C
Maximum temperature at tc test point	95 °C

Lifespan

Number of switching cycles	>15000
Lumen maintenance factor LMF	96
L70B50 lifetime	50000 h

Additional product data

Lighting technology used	LED
--------------------------	-----

Capabilities

Dimmable	Yes
----------	-----

Certificates & standards

Standards	IEC 62778 / IEC 60598-1 / EN 62031 / EN 55015 / EN 61547 / IEC 61000-3-2 / IEC 61000-3-3
Type of protection	IP20
Energy efficiency class	F

Logistical data

Commodity code	85395100000
----------------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	13-01-2026
Primary Article Identifier	6937186151018
Declaration No. in SCIP database	In work
SCIP_ID	

Download Data

File		
Certificates	PDF	▶ CB CERTIFICATE 331284_70044 PL COIN 35 50 111 G3
Certificates	PDF	▶ PL ENEC 40031612 05082025
CAD data	Compressed	▶ PL-CN50-1400-G3 STEP 171225
User instruction	PDF	▶ UI PL-CN35 50 111 COB G3

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
6937186151018 INVENTRONICS	PL-CN50-COB -1400- 930-15D-G3	Shipping carton box 20 Pieces	268 x 110 x 138 mm	4.07 dm ³	104.33 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit