



## Notice : *BOA COOL*

Index : 1

### GUYARD SAS

22-24 Rue Lucien Rouzet  
Z.A Villedieu sur Indre/Niherne  
France

### Intermediate risks – PPE category II

#### FEATURES :

- HPPE glove, high-density polyethylene, nitrile foam coating on palm and fingertips.
- Reinforced thumb and index crotch.
- Gauge 15.
- Color-coded wrist indicating size.
- Tactile glove.

#### AVAILABLE SIZES :

- Sizes 6 to 11

#### USAGE PRECAUTIONS :

- Wear gloves on dry and clean hands. It is recommended to perform a preliminary test of the gloves. Actual usage conditions may differ from the type tests under EU regulations.
- Before reuse, check that the gloves do not show defects, holes, tears, or abnormal wear.
- Shelf life: 5 years from the date of manufacture indicated on the glove.

#### SAFETY, COMFORT AND DEXTERITY :

- Dexterity level 5
- The glove does not contain substances at levels known or suspected to have harmful effects on the hygiene or health of the user under foreseeable conditions of use.

#### PACKAGING

- In case of unpacking, a copy of the instructions must be included with the smallest packaging.
- Bag of 10 pairs
- Carton of 100 pairs

#### MARKING

- The CE marking on this glove signifies compliance with the essential health and safety requirements of European Regulation 2016/425 related to personal protective equipment (PPE).

EN 388 :2016

EN 407 :2020



4 X 4 3 C

X 1 X X X X

#### PERFORMANCES LEVELS :

##### EN 388 :2016+A1 2018

- |                                |     |
|--------------------------------|-----|
| • Abrasion :                   | 4/4 |
| • Cut resistance :             | X/5 |
| • Tear resistance :            | 4/4 |
| • Puncture resistance :        | 3/4 |
| • Cut resistance (ISO 13997) : | C/F |

##### EN 407 :2004

- |                                    |     |
|------------------------------------|-----|
| • Fire behavior                    | X/4 |
| • Contact heat :                   | 1/4 |
| • Convective heat :                | X/4 |
| • Radiante heat :                  | X/4 |
| • Small splashes of molten metal : | X/4 |
| • Large splashes of molten metal : | X/4 |

#### LIMITS OF PROTECTION

- Do not use for handling objects with temperatures above 50°C.
- Do not use for handling chemicals or liquids.

#### RECOMMENDED USES :

- Handling of dry or very slightly oily parts.
- Precision assembly, electronics, mechanical industry.

#### CARE AND STORAGE

- No special maintenance is required. It is recommended to store the products in a place protected from light, cool, dry, and well-ventilated.

#### END OF LIFE

- End-of-life disposal must be controlled and comply with European requirements for traceability and environmental protection.

EU Type Certificate issued in accordance with Module B of Regulation (EU) 2016/425 ON n°

The EU Declaration of Conformity is available on

[www.guyard-sa.com](http://www.guyard-sa.com)