



Notice : *NIT GRIP 3/4*

Index : 2

GUYARD SAS

22-24, rue Lucien Rouzet
Z.A. Villedieu sur Indre/Niherne
36250 NIHERNE FRANCE

Intermediate risks - Category II PPE

EN ISO 21420 EN 388 :2016 + A1 :2018
EN 407 :2020 EN ISO 13997 :1999

FEATURES :

- 5-finger gloves polyamide knit, spandex 250g/m², grey color, 15 gauge.
- Nitrile coating on palm and ¾ of back, blue and black.
- Elasticated wrist with colored overlock to indicate size.
- Lengths from 22 to 27 cm.

AVAILABLE SIZE :

- Size 6 to 11.

PRECAUTIONS FOR USE :

- Wear the gloves on dry and clean hands. It is recommended to test the gloves first. Actual use conditions may be different from the EU type tests.
- Before reusing, check the gloves for defects, holes, tears, unusual wear, etc.
- Expiration date : 5 years from the date of manufacture stated on the glove.

SAFETY COMFORT AND DEXTERITY :

- Dexterity level 5.
- The glove does not contain substances at levels which are known or suspected to have harmful effects on the hygiene or health of the user under the expected conditions of use.

PACKAGING :

- In case of unpacking, a copy of the instruction sheet must be enclosed with the next smallest package.
- Bag of 10 pairs.
- Box of 100 pairs.

MARKING :

- The CE marking on this glove indicates compliance with the essential health and safety requirements of the European regulation 2016/425 on personal protective equipment (PPE).

EN ISO 21420 EN 388 :2016+A1 :2018 EN 407 :2020



4 1 2 1 X

X 1 X X X X

PERFORMANCE LEVELS :

EN 388 :2016+A1 :2018

- | | |
|--|-----|
| • Abrasion : | 4/4 |
| • Blade cut : | 1/5 |
| • Tear : | 2/4 |
| • Puncture : | 1/4 |
| • Cutting by sharp objects (ISO 13997) : | X/F |

EN 407 :2020

- | | |
|------------------------------------|-----|
| • Flame behavior : | X/4 |
| • Contact heat : | 1/4 |
| • Convective heat : | X/4 |
| • Radiant heat : | X/4 |
| • Small splashes of liquid metal : | X/4 |
| • Large splashes of liquid metal : | X/4 |

PROTECTION LIMITS :

- Do not use for handling objects with a temperature higher than 50°C.
- Do not use for handling chemical or liquids products.

RECOMMENDED USES:

- Handling oily parts.
- Precision assembly, electronics, mechanical industry.

MAINTENANCE AND STORAGE

- No special maintenance is recommended. It is advisable to store the products in a cool, dry and ventilated place, keep away from light.

END OF LIFE

- End-of-life destruction must be controlled and comply
- with European traceability and environmental requirements

EU type certificate issued in accordance with module B Regulation (EU) 2016/425

ZVD n° : 1493

The EU declaration of conformity is available on

www.guyard-sa.com