Endress+Hauser Pressure switch PTP31B-AA7M1SGBWJJ

Pressure switch with metal sensor for safe measurement and monitoring of absolute and gauge pressure.



The Ceraphant PTP31B is a pressure switch with piezoresistive sensor for safe measurement and monitoring of absolute and gauge pressure. The pressure switch with compact design is extremely stable and overload resistant for up to +400 bar. The IO-Link capability allows easy integration and parametrization of the device.

Picture for reference only. Product appearance may vary based on configuration

- Function check and information on-site thanks to LEDs and digital display
- IO-Link reduces costs and complexity due to easy configuration and flexible integration in all fieldbus systems.

Configuration of PTP31B-AA7M1SGBWJJ:

Approval:	AA	Non-hazardous area
Output:	7	PNP + 4-20mA, IO-Link, 4-wire
Electrical Connection:	Μ	Plug M12, IP65/67 NEMA Type 4X Encl.
Sensor Range:	15	40bar/4MPa/600psi gauge, overload: 160bar/16MPa/2400psi
Reference Accuracy:	G	Standard 0.5%
Calibration; Unit:	В	Sensor range; mbar/bar
Process Connection:	WJJ	Thread ISO228 G1/2 DIN3852,shape E,316L, flush mount

Alternative part number: PTP31B-7383/0

