




	1	2	3	4	5	6	7	8																																										
A	<table><tr><th>Richtlänge Datum length [mm]</th><th>Längentoleranz Length tolerance</th><th>Satztoleranz Set tolerance [mm]</th></tr><tr><td>0 < Ld ≤ 900</td><td>± 0,85 %</td><td>2</td></tr><tr><td>901 < Ld ≤ 1174</td><td>± 0,85 %</td><td>4</td></tr><tr><td>1175 < Ld ≤ 2000</td><td>± 2 mm</td><td>4</td></tr><tr><td>2001 < Ld < 3150</td><td>± 2 mm</td><td>8</td></tr><tr><td>3151 < Ld < 5000</td><td>± 2 mm</td><td>12</td></tr><tr><td>5001 < Ld < 8000</td><td>± 4 mm</td><td>20</td></tr><tr><td>8001 < Ld < 10000</td><td>± 6 mm</td><td>32</td></tr><tr><td>10001 < Ld < 12500</td><td>± 8 mm</td><td>32</td></tr><tr><td>12501 < Ld < 15000</td><td>± 10 mm</td><td>48</td></tr><tr><td>15001 < Ld < 20000</td><td>± 24 mm</td><td>48</td></tr></table>		Richtlänge Datum length [mm]	Längentoleranz Length tolerance	Satztoleranz Set tolerance [mm]	0 < Ld ≤ 900	± 0,85 %	2	901 < Ld ≤ 1174	± 0,85 %	4	1175 < Ld ≤ 2000	± 2 mm	4	2001 < Ld < 3150	± 2 mm	8	3151 < Ld < 5000	± 2 mm	12	5001 < Ld < 8000	± 4 mm	20	8001 < Ld < 10000	± 6 mm	32	10001 < Ld < 12500	± 8 mm	32	12501 < Ld < 15000	± 10 mm	48	15001 < Ld < 20000	± 24 mm	48	Prinzip-Skizze Principle sketch 		<table><tr><th colspan="3">Profil / Section: B/17</th></tr><tr><th>b [mm]</th><th>h [mm]</th><th>α [°]</th></tr><tr><td>16,6 ± 0,8</td><td>11,0 +1,0/-0,5</td><td>38 ± 2</td></tr></table> Aufbau des Riemens: 1. Umhüllungsgewege 2. SBR/NR Mischung 3. Polyester 4. SBR/NR Mischung V-Belt construction: 1. Standard cover fabric 2. SBR/NR compound 3. Polyester 4. SBR/NR compound			Profil / Section: B/17			b [mm]	h [mm]	α [°]	16,6 ± 0,8	11,0 +1,0/-0,5	38 ± 2	A
Richtlänge Datum length [mm]	Längentoleranz Length tolerance	Satztoleranz Set tolerance [mm]																																																
0 < Ld ≤ 900	± 0,85 %	2																																																
901 < Ld ≤ 1174	± 0,85 %	4																																																
1175 < Ld ≤ 2000	± 2 mm	4																																																
2001 < Ld < 3150	± 2 mm	8																																																
3151 < Ld < 5000	± 2 mm	12																																																
5001 < Ld < 8000	± 4 mm	20																																																
8001 < Ld < 10000	± 6 mm	32																																																
10001 < Ld < 12500	± 8 mm	32																																																
12501 < Ld < 15000	± 10 mm	48																																																
15001 < Ld < 20000	± 24 mm	48																																																
Profil / Section: B/17																																																		
b [mm]	h [mm]	α [°]																																																
16,6 ± 0,8	11,0 +1,0/-0,5	38 ± 2																																																
B	Riemensätze müssen im Satz bestellt werden Belt sets must be ordered as a set Kennzeichnungsbeispiel / Marking example: Made in ... optibelt-VB B 965 L_d 17 x 925 L_i B 37 1 2 Werkscode / Plant code Profil und Länge / Section and Length Jahreszeichen / Year code							B																																										
C	$L_a \approx L_i + 69$ $L_d \approx L_i + 40$ Längen-Messbedingungen nach DIN 2215 und ISO 4183 Length measurement according to DIN 2215 and ISO 4183 <table><tr><td>d_d [mm]</td><td>127,32 ± 0,05</td></tr><tr><td>U_d [mm]</td><td>400</td></tr><tr><td>d_a [mm]</td><td>135,72 ± 0,05</td></tr><tr><td>b_d [mm]</td><td>14,00</td></tr><tr><td>α [°]</td><td>34 ± 10'</td></tr><tr><td>t_{min} [mm]</td><td>15</td></tr><tr><td>Q [N]</td><td>300</td></tr><tr><td colspan="2">L_d = 2a + U_d</td></tr><tr><td colspan="2">L_a = 2a + U_a</td></tr></table>							d _d [mm]	127,32 ± 0,05	U _d [mm]	400	d _a [mm]	135,72 ± 0,05	b _d [mm]	14,00	α [°]	34 ± 10'	t _{min} [mm]	15	Q [N]	300	L _d = 2a + U _d		L _a = 2a + U _a		C																								
d _d [mm]	127,32 ± 0,05																																																	
U _d [mm]	400																																																	
d _a [mm]	135,72 ± 0,05																																																	
b _d [mm]	14,00																																																	
α [°]	34 ± 10'																																																	
t _{min} [mm]	15																																																	
Q [N]	300																																																	
L _d = 2a + U _d																																																		
L _a = 2a + U _a																																																		
D	 optibelt VB					<table><tr><td>4</td><td></td><td></td><td></td></tr><tr><td>3</td><td></td><td></td><td></td></tr><tr><td>2</td><td></td><td></td><td></td></tr><tr><td>1</td><td>Freigabe</td><td>08.03.2016</td><td>HGr</td></tr><tr><td>0</td><td>Erstellt</td><td>08.03.2016</td><td>MJR</td></tr><tr><td>Zust.</td><td>Änderungen</td><td>Datum</td><td>Name</td></tr></table> Profil B/17 Dateiname: Datenblatt_optibelt VB_17.pdf		4				3				2				1	Freigabe	08.03.2016	HGr	0	Erstellt	08.03.2016	MJR	Zust.	Änderungen	Datum	Name	D																		
4																																																		
3																																																		
2																																																		
1	Freigabe	08.03.2016	HGr																																															
0	Erstellt	08.03.2016	MJR																																															
Zust.	Änderungen	Datum	Name																																															
	1	2	3	4	5	6	7	8																																										

	1	2	3	4	5	6	7	8																														
A	<table><tr><th>Richtlänge Datum length [mm]</th><th>Längentoleranz Length tolerance [mm]</th><th>Satztoleranz Set tolerance [mm]</th></tr><tr><td>1290 < Ld ≤ 5000</td><td>± 2</td><td>4</td></tr><tr><td>5000 < Ld ≤ 8000</td><td>± 4</td><td>8</td></tr><tr><td>8000 < Ld ≤ 10000</td><td>± 6</td><td>12</td></tr><tr><td>10000 < Ld ≤ 12500</td><td>± 8</td><td>16</td></tr><tr><td>12500 < Ld ≤ 15000</td><td>± 10</td><td>20</td></tr><tr><td>15000 < Ld ≤ 20000</td><td>± 24</td><td>48</td></tr></table>		Richtlänge Datum length [mm]	Längentoleranz Length tolerance [mm]	Satztoleranz Set tolerance [mm]	1290 < Ld ≤ 5000	± 2	4	5000 < Ld ≤ 8000	± 4	8	8000 < Ld ≤ 10000	± 6	12	10000 < Ld ≤ 12500	± 8	16	12500 < Ld ≤ 15000	± 10	20	15000 < Ld ≤ 20000	± 24	48	Prinzip-Skizze Principle sketch 		<table><tr><th colspan="3">Profil / Section: B/17</th></tr><tr><th>b [mm]</th><th>h [mm]</th><th>α [°]</th></tr><tr><td>16,6 ± 0,8</td><td>11,0 +1,0/-0,5</td><td>38 ± 2</td></tr></table> Aufbau des Riemens: 1. Umhüllungsgewebe 2. SBR/NR Mischung 3. Polyester 4. SBR/NR Mischung V-Belt construction: 1. Standard cover fabric 2. SBR/NR compound 3. Polyester 4. SBR/NR compound			Profil / Section: B/17			b [mm]	h [mm]	α [°]	16,6 ± 0,8	11,0 +1,0/-0,5	38 ± 2	A
Richtlänge Datum length [mm]	Längentoleranz Length tolerance [mm]	Satztoleranz Set tolerance [mm]																																				
1290 < Ld ≤ 5000	± 2	4																																				
5000 < Ld ≤ 8000	± 4	8																																				
8000 < Ld ≤ 10000	± 6	12																																				
10000 < Ld ≤ 12500	± 8	16																																				
12500 < Ld ≤ 15000	± 10	20																																				
15000 < Ld ≤ 20000	± 24	48																																				
Profil / Section: B/17																																						
b [mm]	h [mm]	α [°]																																				
16,6 ± 0,8	11,0 +1,0/-0,5	38 ± 2																																				
B	Kennzeichnungsbeispiel / Marking example: <table><tr><td>-</td><td>Made in ...</td><td>optibelt-VB S=C plus</td><td>B 2040 L_d</td><td>17 x 2000 L_i</td><td>B 79</td><td>Antistatic ISO 1813</td><td>1 2</td><td>●</td></tr></table> Werkscod / Plant code								-	Made in ...	optibelt-VB S=C plus	B 2040 L _d	17 x 2000 L _i	B 79	Antistatic ISO 1813	1 2	●																					
-	Made in ...	optibelt-VB S=C plus	B 2040 L _d	17 x 2000 L _i	B 79	Antistatic ISO 1813	1 2	●																														