

1514494

<https://www.phoenixcontact.com/gb/products/1514494>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Power cable, 6-position, PUR halogen-free, black, Plug straight Size 15 Bayonet locking, on free cable end, cable length: 3 m, For alternating current up to 16 A/600 V

Your advantages

- Protection against mismatching, thanks to special coding

Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1514494       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | AF1CDQ        |
| Product key                          | AF1CDQ        |
| GTIN                                 | 4063151978235 |
| Weight per piece (including packing) | 680.9 g       |
| Weight per piece (excluding packing) | 680.9 g       |
| Customs tariff number                | 85444290      |
| Country of origin                    | DE            |

# SAC-6P-S15MS/ 3,0-PUR PE - Power cable



1514494

<https://www.phoenixcontact.com/gb/products/1514494>

## Technical data

### Product properties

|                      |              |
|----------------------|--------------|
| Product type         | Power cable  |
| Application          | Power supply |
| Number of positions  | 6            |
| No. of cable outlets | 1            |
| Shielded             | no           |

### Insulation characteristics

|                     |   |
|---------------------|---|
| Degree of pollution | 3 |
|---------------------|---|

### Material specifications

|                                        |                    |
|----------------------------------------|--------------------|
| Flammability rating according to UL 94 | V0                 |
| Material of grip body                  | PUR                |
| Contact material                       | Cu alloy           |
| Contact surface material               | Ag                 |
| Contact carrier material               | PA                 |
| Material for screw connection          | not available      |
| Outer sheath, material                 | PUR                |
| Conductor material                     | Bare Cu litz wires |

### Electrical properties

|                           |                  |
|---------------------------|------------------|
| Nominal voltage $U_N$     | 600 V AC (Power) |
|                           | 63 V (Signal)    |
| Nominal current $I_N$     | 16 A (Power)     |
|                           | 10 A (Signal)    |
| Max. conductor resistance | 7.98 $\Omega$ /m |

### Mechanical properties

#### Mechanical data

|                     |         |
|---------------------|---------|
| Max. bending cycles | 5000000 |
|---------------------|---------|

### Connector

#### Connection 1

|                     |                                       |
|---------------------|---------------------------------------|
| Type                | Plug straight Size 15 Bayonet locking |
| Number of positions | 6                                     |
| Locking type        | Bayonet locking                       |

#### Connection 2

|      |                |
|------|----------------|
| Type | free cable end |
|------|----------------|

### Cable/line

|              |     |
|--------------|-----|
| Cable length | 3 m |
|--------------|-----|

# SAC-6P-S15MS/ 3,0-PUR PE - Power cable



1514494

<https://www.phoenixcontact.com/gb/products/1514494>

## PUR halogen-free black [PUR]

|                                               |                                                                                                                 |
|-----------------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| Number of positions                           | 6                                                                                                               |
| Shielded                                      | no                                                                                                              |
| Cable type                                    | PUR halogen-free black [PUR]                                                                                    |
| AWG power supply                              | 14                                                                                                              |
| Conductor cross section                       | 6x 2.5 mm <sup>2</sup>                                                                                          |
| Wire diameter incl. insulation                | 2.85 mm ±5 %                                                                                                    |
| External cable diameter                       | 10.50 mm                                                                                                        |
| Outer sheath, material                        | PUR                                                                                                             |
| External sheath, color                        | black                                                                                                           |
| Conductor material                            | Bare Cu litz wires                                                                                              |
| Single wire, material                         | PP                                                                                                              |
| Single wire, color                            | black 1, black 2, black 3, black 4, black 5, green/yellow                                                       |
| Thickness, insulation                         | Core insulation                                                                                                 |
| Overall twist                                 | 6 wires, twisted around filler                                                                                  |
| Max. conductor resistance                     | max. 7.98 Ω/m                                                                                                   |
| Nominal voltage, cable                        | ≤ 1000 V                                                                                                        |
| Test voltage                                  | ≥ 10000 V                                                                                                       |
| Minimum bending radius, fixed installation    | 7.5 x D                                                                                                         |
| Minimum bending radius, flexible installation | 10 x D                                                                                                          |
| Smallest bending radius, fixed installation   | 79 mm                                                                                                           |
| Smallest bending radius, movable installation | 105 mm                                                                                                          |
| Dynamic load capacity (bending)               | Max. bending cycles: 5000000, Bending radius: 79 mm, Traversing rate: 3.3 m/s, Acceleration: 5 m/s <sup>2</sup> |
| Ambient temperature (operation)               | -50 °C ... 80 °C (cable, fixed installation)                                                                    |
|                                               | -25 °C ... 80 °C (Cable, flexible installation)                                                                 |

## Environmental and real-life conditions

### Ambient conditions


|                                 |                                  |
|---------------------------------|----------------------------------|
| Degree of protection            | IP65                             |
|                                 | IP67 (When plugged in)           |
| Ambient temperature (operation) | -30 °C ... 85 °C (Plug / socket) |

## Standards and regulations

|                          |                 |
|--------------------------|-----------------|
| Standards/specifications | IEC 61076-2-116 |
|--------------------------|-----------------|


## Drawings

Dimensional drawing



M15 male connector, straight

Schematic diagram



M15 male connector pin assignment, 6-pos., pin side view

# SAC-6P-S15MS/ 3,0-PUR PE - Power cable

1514494

<https://www.phoenixcontact.com/gb/products/1514494>



Circuit diagram



Contact assignment of the M15 connector

# SAC-6P-S15MS/ 3,0-PUR PE - Power cable



1514494

<https://www.phoenixcontact.com/gb/products/1514494>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27060311 |
| ECLASS-12.0 | 27060311 |
| ECLASS-13.0 | 27060327 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001855 |
|----------|----------|

# SAC-6P-S15MS/ 3,0-PUR PE - Power cable



1514494

<https://www.phoenixcontact.com/gb/products/1514494>

## Environmental product compliance

### EU RoHS

|                                         |      |
|-----------------------------------------|------|
| Fulfills EU RoHS substance requirements | Yes  |
| Exemption                               | 6(c) |

### China RoHS

|                                        |                                                                                                                                                                                                                                   |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Environment friendly use period (EFUP) | EFUP-50                                                                                                                                                                                                                           |
|                                        | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

### EU REACH SVHC

|                                     |                                      |
|-------------------------------------|--------------------------------------|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1)                 |
| SCIP                                | afe956b3-ec96-4cb7-b023-cbb9cd0586e8 |

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd  
Halesfield 13, Telford  
Shropshire, TF7 4PG  
01952 681700  
[info@phoenixcontact.co.uk](mailto:info@phoenixcontact.co.uk)