



EN ISO 20345:2011


 JUST GRIP
AUCKLAND
 98378-07L

S3 HRO HI SRC
Size: 38-48
Weight: 560 gr.

Fit: 11

Working Environment:
 ESD Areas, Logistics and Light Industry, Components and Automotive, Ho.Re.Ca.


FEATURES

UPPER

 Digitex Hydro Airy
 Digitex Hydro Airy
 MicroFiber Suede with Pro-tech
 SXT light 1,6-1,8 mm

LINING

 Breezy 3D, two-layers
 combination

ANTISLIP LINING
 DUALMICRO

INSOLE

Five 4 Fit

TOE CAP

Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION

KX Antiperforation PS

TYPE

Low Shoe

SOLE

PU-RUBBER VIBRAM "COLTELLO DESIGN"

 Light and comfortable PU
 midsole. VIBRAM, COLTELLO,
 rubber outsole, designed for
 particularly slippery and wet work
 conditions. Extraordinary grip
 performance and excellent
 comfort.

TECHNOLOGIES

Removable Insole


 Highly breathable and absorbent
 anatomic insole. Multilayer structure
 to take advantage of the peculiarities
 of each component. Dry and with a
 comfortable memory foam "pillow"

Protection elements


 RESISTANT
 TO 3.0 mm.
 NAILS

 Toecap "Alu Sxt 2.0" with
 differentiated thicknesses, resistant
 to 200J. Non metal perforation
 resistant Insert to over 1100 N with a
 3.0 mm truncated cone nail. Protection
 over the entire sole of the foot.
 Flexible and comfortable

Lateral stability

 dynamic **HC** control
 technology

 Ergonomic rigid internal structure. It
 houses the heel into the right seat,
 adjusting the foot support and control
 of the ankle sideways movements. It
 keeps the foot tight to the shoe,
 allowing the perfect fit.

Torsional stability


 Support made of rigid plastic
 material. It stabilizes the heel bone,
 the instep and tarsal joints, without
 altering energy absorption. A support
 for the natural movement of the foot;
 it provides comfort and greater
 stability.


SRC (SRA+SRB)


 SOLE 98
 PU - RUBBER

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	0.49 0.48
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	0.27 0.26

EN ISO 20344:2011

Electrical features


 ESD footwear discharge static
 electricity and avoid damaging
 surrounding objects; they are
 designed in compliance with the
 following standards: IEC EN
 61340-5-1:2016 - IEC EN
 61340-4-3:2018 - IEC EN
 61340-4-5:2018.

Other


 Created for those who work in the
 HORECA sector, H.ABC footwear has
 new antibacterial components
 subjected to analysis by accredited
 laboratories. The results confirm the
 constant elimination activity of over
 80% of bacterial load.
