

32.768kHz SMD Low Profile Crystal

ABS05

Request Samples



Check Inventory



1.6 x 1.0 x 0.5mm
RoHS/RoHS II Compliant
 MSL Level = N/A

Features

- Small form factor Tuning Fork Crystal (1.60 x 1.00 x 0.50 mm package)
- Low profile - ideal for height constraint designs
- Available with standard ± 20 ppm set-tolerance
- Extended temperature -40°C to +85°C for industrial applications

Applications

- Wireless Modules
- Internet of Things (IoT)
- Bluetooth / Bluetooth Low Energy (BLE)
- Commercial & Industrial Applications
- Low Power MCU's, SoC's, Transceivers
- Communication & Measuring Equipment

Electrical Specifications

Parameters	Minimum	Typical	Maximum	Units	Notes
Frequency	32.768			kHz	
Operation Mode	Flexural Mode (Tuning Fork)				
Operating Temperature	-40		+85	°C	
Storage Temperature	-55		+125	°C	
Frequency Tolerance @+25°C	-20		+20	ppm	Standard (See options if other than STD)
Temperature Coefficient:	-0.04	-0.03	-0.02	ppm/T ²	
Turn-over temperature:	+20	+25	+30	°C	
Equivalent series resistance (ESR)			90	k Ω	
Shunt capacitance (C0)		1.3		pF	
Load capacitance (CL)	12.5			pF	Standard (See options if other than STD)
Drive Level			0.5	μ W	
Aging @ +25°C \pm 3°C	-3		+3	ppm	First Year
Insulation Resistance	500			M Ω	@ 100Vdc \pm 15V

Part Identification

ABS05 – 32.768 kHz - - -

Load Capacitance
Blank: 12.5pF
9: 9pF
7: 7pF
6: 6pF
X: 4pF (*)

Frequency Tolerance
Blank: ± 20 ppm
1: ± 10 ppm (*)
3: ± 25 ppm
4: ± 30 ppm

(*) Contact Abracon for availability

Packaging
Blank: Bulk
T: Tape & Reel (3000pcs/reel)
T5: Tape & Reel (5000pcs/reel)

(*)
 "X: 4pF" option with ± 20 ppm set tolerance is only available in 5k units per tape and reel; part #: ABS05-32.768kHz-X-T5
 "X: 4pF" option with ± 25 ppm set tolerance is only available in 3k units per tape and reel; part #: ABS05-32.768kHz-X-3-T3



5101 Hidden Creek Ln Spicewood TX 78669
 Phone: 512-371-6159 | Fax: 512-351-8858
 For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 11-03-21

ABRACON IS
 ISO9001-2015
 CERTIFIED

32.768kHz SMD Low Profile Crystal

ABS05

Request Samples




Check Inventory




1.6 x 1.0 x 0.5mm
RoHS/RoHS II Compliant
MSL Level = N/A

Mechanical Dimensions



Recommended land pattern



Dimensions: mm



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 11-03-21

ABRACON IS
ISO9001-2015
CERTIFIED

32.768kHz SMD Low Profile Crystal

ABS05

Request Samples




Check Inventory




1.6 x 1.0 x 0.5mm
RoHS/RoHS II Compliant
MSL Level = N/A

Alternative Mechanical Dimensions #1



Recommended land pattern



Dimensions: mm



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 11-03-21

ABRACON IS
ISO9001-2015
CERTIFIED

32.768kHz SMD Low Profile Crystal

ABS05

Request Samples



Check Inventory



1.6 x 1.0 x 0.5mm
RoHS/RoHS II Compliant
MSL Level = N/A

Reflow Profile [JEDEC J-STD-020]




Table 1

SnPb Eutectic Process
Classification Temperatures (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2

Pb-Free Process
Classification Temperatures (T_c)

Package Thickness	Volume mm ³ <350	Volume mm ³ 350-2000	Volume mm ³ >2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 mm - 2.5 mm	260 °C	250 °C	245 °C
>2.5 mm	250 °C	245 °C	245 °C

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat / soak		
Temperature minimum (T_{smin})	100°C	150°C
Temperature maximum (T_{smax})	150°C	200°C
Time (T_{smin} to T_{smax}) (t_s)	60 - 120 sec.	60 - 120 sec.
Average ramp-up rate (T_{smax} to T_p)	3°C/sec. max	3°C/sec. max
Liquidous temperature (T_L)	183°C	217°C
Time at liquidous (t_L)	60 - 150 sec.	60 - 150 sec.
Peak package body temperature (T_p)*	see Table 1	see Table 2
Time (t_p)** within 5°C of the specified classification temperature (T_c)	20 sec.	30 sec.
Ramp-down rate (T_p to T_{smax})	6°C/sec. max	6°C/sec. max
Time 25°C to peak temperature	6 min. max	8 min. max
Reflow cycles	2 max	2 max

*Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

**Tolerance for time at peak profile temperature (t_p) is defined as supplier minimum and a user maximum.



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 11-03-21

ABRACON IS
ISO9001-2015
CERTIFIED

32.768kHz SMD Low Profile Crystal

ABS05

Request Samples



Check Inventory




1.6 x 1.0 x 0.5mm
RoHS/RoHS II Compliant
MSL Level = N/A

Packaging

T=Tape and reel (3,000pcs/reel)

T5=Tape and reel (5,000pcs/reel)



Dimensions: mm

ATTENTION: Abracon LLC's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependent Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon LLC is required. Please contact Abracon LLC for more information.



5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 11-03-21

ABRACON IS
ISO9001-2015
CERTIFIED