



Figure similar

line commutating reactor for rectifier; phases: 3; Un1(V): 400; I<sub>thmax</sub> 1(A) / F1(Hz): 20 / 50; I<sub>LN</sub> (A): 18; UK(%): 4; LN(MH): 1.12; temperature rise/insulation class: 40 /B; IP00; connection: screw connection; EN 61558-2-20 >reactor<

General technical data		
product designation		Kommut.-Drossel f. Stromrichter
phase number		3
type of voltage		AC
operating voltage rated value	V	400
operating frequency rated value	Hz	50
<ul style="list-style-type: none"> <li>• — operational current at AC rated value</li> <li>— current at AC maximum</li> <li>• current at DC rated value</li> </ul>	A	18
	A	20
	A	24.5
peak current	A	25
inductivity rated value	H	0.0011
relative inductive drop in voltage for rated value of the current, voltage and frequency	%	4
power loss [W] of the coil	W	39
power loss [W] of the iron core	W	7
Mechanical data		
type of electrical connection for main current circuit		screw-type terminals
width	m	0.148
height	m	0.126
depth	m	0.078
Ambient conditions		
thermal class according to IEC 60085		B
ambient temperature rated value	°C	40
protection class IP		IP00
Certificates/ approvals		
General Product Approval	other	Environment



[Confirmation](#)

[Environmental Confirmations](#)

### Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4EP3601-5DS00>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=4EP3601-5DS00>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/4EP3601-5DS00>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=4EP3601-5DS00&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=4EP3601-5DS00&lang=en)

---

last modified:

4/8/2025 