

## TECHNICAL DATA

1/2

### CRC AQUA MARKER PENS

5 different colors

Ref. : 32466

Aqua Marker Pens for multi surface use. Excellent coverage thanks to the use of correction fluid technology.

#### 2. FEATURES

---

- Water based formulation.
- Does not contain harmful solvents such as Xylene.
- Excellent coverage, even on black surfaces.
- Fast drying for efficient work flow.
- Durable tip with valve action to prevent excess of paint flow.
- Convenient, medium thickness point ( Ø 4,5 mm)
- Easy and clean application.
- No negative classifications for Health, Physical and Environment according to regulations: EC nr 1272/2008.

#### 3. APPLICATIONS

---

All markings in the industry:

Multi surface: can be used on: wood, metal, rubber, glass, textile, paper, enamel, plastic, cardboard, tiles,...

- Wood working
- Metal working
- Road construction
- Civil engineering
- Topography
- Machine construction
- logistic
- Electrical installations

#### 4. DIRECTIONS

---

- Shake the pen well with the cap on, until the agitator ball moves free.
- Take off the cap and press the tip several times or until the paint starts to flow.
- Always use in a well ventilated area.
- Replace the cap carefully after use and store in horizontal position.
- The color may fade when exposed to direct sunlight for an extended period.

***A safety data sheet (MSDS) according to EU directive 91/155/EEC and amendments is available for all CRC products.***

#### 5. TYPICAL PRODUCT DATA (without propellant)


---

Color	: 5 colors available Red, yellow, blue, white, black
Boiling point	: 100 ° C



Manufactured by :  
CRC Industries Europe BVBA  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
www.crcind.com





## TECHNICAL DATA 2/2

### CRC AQUA MARKER PENS 5 different colors

Ref. :32466

#### 6. PACKAGING

---

12 pens in box - 60 boxes per carton.

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com).

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 32466 03 0915 02

Date : 12 February 2016



Manufactured by :  
CRC Industries Europe BVBA  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)

