

Acti9 IC60 RCBO - auxiliary contact - 10F/SD - AC/DC

A9A19803

Main

range of product	Acti9	
Product or component type	OC or fault contact	
Device short name	iOF/SD	
Signal contacts composition	1 C/O	
[In] rated current	6 A at 24 V, DC	
	2 A at 60 V, DC	
	1.5 A at 110 V, DC	
	1 A at 250 V, DC	
	6 A at 24230 V, AC 50 Hz	
	3 A at 415 V, AC 50 Hz	
9 mm pitches	1	
Standards	EN/IEC 60947-5-1	

Complementary

Mounting mode	Clip-on	
Mounting support	DIN rail	
Height	86 mm	
Width	9 mm	
Depth	71 mm	
Net weight	36 g	
Colour	White	
Connections - terminals	Screw clamp terminal (bottom) 1 cable(s) 0.254 mm² - rigid Screw clamp terminal (bottom) 1 cable(s) 0.252.5 mm² - flexible Screw clamp terminal (bottom) 2 cable(s) 1.5 mm² - rigid Screw clamp terminal (bottom) 2 cable(s) 1.5 mm² - flexible Screw clamp terminal (bottom) 1 cable(s) 2.5 mm² - flexible with ferrule	
Wire stripping length	6 mm for bottom connection	
Tightening torque	0.6 N.m bottom	

Environment

Ambient air temperature for operation	-2560 °C
Ambient air temperature for storage	-4070 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	2.500 cm
Package 1 Width	8.500 cm
Package 1 Length	10.400 cm
Package 1 Weight	55.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	72
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	4.286 kg

Contractual warranty

Warranty 18 mois



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

∅ Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	A7b24ae6-2312-4e67-b7c9-56fce3e8c723
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture		
Circularity Profile	End of Life Information	
Take-back	No	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	