

RS- Lower Cost Leadfree No Clean Solder Wire Handypack #818-3204 (NZ)

RS Components

Chemwatch Hazard Alert Code: 2

Chemwatch: **5404-01** Version No: **2.1.1.1** Issue Date: **02/06/2020**Print Date: **30/06/2020**L.GHS.NZL.EN

Safety Data Sheet according to HSNO Regulations

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	RS- Lower Cost Leadfree No Clean Solder Wire Handypack #818-3204 (NZ)				
Synonyms	Not Available				
Other means of identification	Not Available				

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses So

Soldering.

Details of the supplier of the safety data sheet

Registered company name	RS Components			
Address	D Box 12-127 Penrose, Auckland New Zealand			
Telephone	27 4747122			
Fax	+64 9 579 1700			
Website	www.nz.rs-online.com			
Email	Not Available			

Emergency telephone number

Association / Organisation	CHEMWATCH EMERGENCY RESPONSE			
Emergency telephone numbers	+64 800 700 112			
Other emergency telephone numbers	+61 2 9186 1132			

Once connected and if the message is not in your prefered language then please dial 01

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification [1]	Skin Sensitizer Category 1
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	6.5B (contact)

Label elements

Hazard pictogram(s)



SIGNAL WORD WARNING

Hazard statement(s)

H317 May cause an allergic skin reaction.

Precautionary statement(s) Prevention

P280	Wear protective gloves/protective clothing/eye protection/face protection.				
P261	Avoid breathing dust/fumes.				
P272	Contaminated work clothing should not be allowed out of the workplace.				

Chemwatch: 5404-01 Page 2 of 11 Issue Date: 02/06/2020 Version No: 2.1.1.1 Print Date: 30/06/2020

RS- Lower Cost Leadfree No Clean Solder Wire Handypack #818-3204 (NZ)

Precautionary statement(s) Response

P321	Specific treatment (see advice on this label).			
P302+P352	N SKIN: Wash with plenty of water and soap.			
P333+P313	skin irritation or rash occurs: Get medical advice/attention.			
P362+P364	Take off contaminated clothing and wash it before reuse.			

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name		
Not Available		solder wire alloy consisting of		
7440-31-5	NotSpec	tin		
65997-05-9	NotSpec	rosin, polymerised		
7440-50-8	NotSpec	copper		
7440-48-4	NotSpec	cobalt		
Not Available		In use product produces soldering volaties as		
Not Available		rosin core solder decomposition products		
7440-31-5		tin fume		
7440-50-8.		copper fume		
7440-48-4		cobalt fume		

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. In case of burns: Immediately apply cold water to burn either by immersion or wrapping with saturated clean cloth. DO NOT remove or cut away clothing over burnt areas. DO NOT pull away clothing which has adhered to the skin as this can cause further injury. DO NOT break blister or remove solidified material. Quickly cover wound with dressing or clean cloth to help prevent infection and to ease pain. For large burns, sheets, towels or pillow slips are ideal; leave holes for eyes, nose and mouth. DO NOT apply ointments, oils, butter, etc. to a burn under any circumstances. Water may be given in small quantities if the person is conscious. Alcohol is not to be given under any circumstances. Reassure. Treat for shock by keeping the person warm and in a lying position. Seek medical aid and advise medical personnel in advance of the cause and extent of the injury and the estimated time of arrival of the patient.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ► Water spray or fog.
- ► Foam.
- Dry chemical powder.
- ▶ BCF (where regulations permit).

Chemwatch: 5404-01 Page 3 of 11 Issue Date: 02/06/2020 Version No: 2.1.1.1 Print Date: 30/06/2020

RS- Lower Cost Leadfree No Clean Solder Wire Handypack #818-3204 (NZ)

Fire Incompatibility None known Advice for firefighters Alert Fire Brigade and tell them location and nature of hazard. Product is not combustible. No special firefighting procedures required. Fire Fighting Use fire fighting procedures suitable for surrounding area. If safe to do so, remove containers from path of fire Will not burn but melts readily and may produces acrid fumes. ► Non combustible. ▶ Not considered a significant fire risk, however containers may burn. Fire/Explosion Hazard Decomposition may produce toxic fumes of: metal oxides Will not burn, but heat produces highly toxic fumes/vapours.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Sweep up. Place in suitable containers for disposal.
Major Spills	 Clean up all spills immediately. Secure load if safe to do so. Bundle/collect recoverable product. Collect remaining material in containers with covers for disposal.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Sate	handling

- ► Limit all unnecessary personal contact.
- ▶ Wear protective clothing when risk of exposure occurs.
- ► Use in a well-ventilated area.
- ► When handling **DO NOT** eat, drink or smoke.
- Other information
- Store under cover.
- Protect containers against physical damage.
- ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	▶ Packaging as recommended by manufacturer.
Storage incompatibility	 Avoid strong acids, acid chlorides, acid anhydrides and chloroformates. Avoid strong bases. Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

INOREDIENT DATA						
Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	tin	Tin metal	2 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	copper	Copper fume Dusts and mists, as Cu	0.2; 1 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	cobalt	Cobalt metal dust and fume, as Co	0.02 mg/m3	Not Available	Not Available	bio-Exposure can also be estimated by biological monitoring 6.7B-Suspected carcinogen (skin)-Skin absorption (dsen)- Dermal sensitiser (rsen)-Respiratory sensitiser
New Zealand Workplace Exposure Standards (WES)	tin fume	Tin metal	2 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	copper fume	Copper fume Dusts and mists, as Cu	0.2; 1 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	cobalt fume	Cobalt metal dust and fume, as Co	0.02 mg/m3	Not Available	Not Available	bio-Exposure can also be estimated by biological monitoring 6.7B-Suspected carcinogen (skin)-Skin absorption (dsen)- Dermal sensitiser (rsen)-Respiratory sensitiser

Page 4 of 11

Issue Date: 02/06/2020 Print Date: 30/06/2020 RS- Lower Cost Leadfree No Clean Solder Wire Handypack #818-3204 (NZ)

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
tin	Tin	6 mg/m3	67 mg/m3	400 mg/m3
copper	Copper	3 mg/m3	33 mg/m3	200 mg/m3
cobalt	Cobalt	0.18 mg/m3	2 mg/m3	20 mg/m3
tin fume	Tin	6 mg/m3	67 mg/m3	400 mg/m3
copper fume	Copper	3 mg/m3	33 mg/m3	200 mg/m3
cobalt fume	Cobalt	0.18 mg/m3	2 mg/m3	20 mg/m3

Ingredient	Original IDLH	Revised IDLH
tin	Not Available	Not Available
rosin, polymerised	Not Available	Not Available
copper	100 mg/m3	Not Available
cobalt	20 mg/m3	Not Available
rosin core solder decomposition products	Not Available	Not Available
tin fume	Not Available	Not Available
copper fume	100 mg/m3	Not Available
cobalt fume	20 mg/m3	Not Available

OCCUPATIONAL EXPOSURE BANDING

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
rosin core solder decomposition products	D	> 0.1 to ≤ 1 ppm
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

MATERIAL DATA

Exposure controls

Appropriate engineering controls

Excessively hot soldering irons with overuse of flux will cause generation of irritant fume. Control measures in the form of thermostat controlled irons and the use of wire with correct type and amount of flux may be required.

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment

Personal protection









Eye and face protection

- Safety glasses with side shields; or as required.
 - Chemical goggles.
 - Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.

Skin protection	See Hand protection below
Hands/feet protection	Wear physical protective gloves, e.g. leather Wear safety footwear.

Body protection

Overalls.

► Eyewash unit. Other protection

Ensure ready access to a burns first aid kit

See Other protection below

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computergenerated selection:

RS- Lower Cost Leadfree No Clean Solder Wire Handypack #818-3204 (NZ)

Material	СРІ
BUTYL	A
NEOPRENE	A
NEOPRENE/NATURAL	A
NITRILE	A
PE	A
PE/EVAL/PE	A

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

Version No: 2.1.1.1

Issue Date: 02/06/2020 Print Date: 30/06/2020 RS- Lower Cost Leadfree No Clean Solder Wire Handypack #818-3204 (NZ)

PVC	Α
TEFLON	Α
VITON	Α
NATURAL RUBBER	В
NATURAL+NEOPRENE	В

^{*} CPI - Chemwatch Performance Index

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or $hydrogen\ cyanide(HCN),\ B3 = Acid\ gas\ or\ hydrogen\ cyanide(HCN),\ E = Sulfur$ dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organiccompounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Dark grey solid with characteristic odour; insoluble in water.		
Physical state	Solid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	>226
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	227	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	>115	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Fumes evolved during welding operations may be irritating to the upper-respiratory tract and may be harmful if inhaled. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.
Ingestion	Overexposure is unlikely in this form. Considered an unlikely route of entry in commercial/industrial environments
Skin Contact	Molten material is capable of causing burns. Skin contact does not normally present a hazard, though it is always possible that occasionally individuals may be found who react to substances usually regarded as inert.
Eye	Molten material is capable of causing burns. The vapour is discomforting

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

Page 6 of 11

Chemwatch: 5404-01 Version No: 2.1.1.1

RS- Lower Cost Leadfree No Clean Solder Wire Handypack #818-3204 (NZ)

Issue Date: 02/06/2020 Print Date: 30/06/2020

Chronic

Chronic exposure to tin dusts and fume results in "stannosis" a mild form of pneumoconiosis. Chest symptoms develop several years after breathing difficulties (dyspnae) occur. No case of massive fibrosis from over-exposure to tin has been reported. Metallic dusts generated by the industrial process give rise to a number of potential health problems. The larger particles, above 5 micron, are

nose and throat irritants. Smaller particles however, may cause lung deterioration. Particles of less than 1.5 micron can be trapped in the lungs and, dependent on the nature of the particle, may give rise to further serious health consequences.

RS- Lower Cost Leadfree No ean Solder Wire Handypack	TOXICITY	IRRITATION
#818-3204 (NZ)	Not Available	Not Available
	TOXICITY	IRRITATION
tin	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (rat) LD50: >2000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
	TOXICITY	IRRITATION
rosin, polymerised	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (rat) LD50: >1000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
copper	Inhalation (rat) LC50: 0.733 mg/l4 h ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
	Oral (rat) LD50: 300-500 mg/kg ^[1]	
	TOXICITY	IRRITATION
cobalt	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: adverse effect observed (irritating) ^[1]
	Oral (rat) LD50: ~550 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
rosin core solder	TOXICITY	IRRITATION
decomposition products	Not Available	Not Available
	TOXICITY	IRRITATION
tin fume	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (rat) LD50: >2000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
copper fume	Inhalation (rat) LC50: 0.733 mg/l4 h ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
	Oral (rat) LD50: 300-500 mg/kg ^[1]	
	TOXICITY	IRRITATION
cobalt fume	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: adverse effect observed (irritating) ^[1]
	Oral (rat) LD50: ~550 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
Legend:	Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

COPPER

Symptoms are tiredness, influenza like respiratory tract irritation with fever.

for copper and its compounds (typically copper chloride):

Acute toxicity: There are no reliable acute oral toxicity results available. In an acute dermal toxicity study (OECD TG 402), one group of 5 male rats and 5 groups of 5 female rats received doses of 1000, 1500 and 2000 mg/kg bw via dermal application for 24 hours. The LD50 values of copper monochloride were 2,000 mg/kg bw or greater for male (no deaths observed) and 1,224 mg/kg bw for female. Four females died at both 1500 and 2000 mg/kg bw, and one at 1,000 mg/kg bw.

rosin core solder decomposition products

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS.

The material may produce respiratory tract irritation. Symptoms of pulmonary irritation may include coughing, wheezing, laryngitis, shortness of breath, headache, nausea, and a burning sensation.

Unlike most organs, the lung can respond to a chemical insult or a chemical agent, by first removing or neutralising the irritant and then repairing the damage (inflammation of the lungs may be a consequence).

The repair process (which initially developed to protect mammalian lungs from foreign matter and antigens) may, however, cause further damage to the lungs (fibrosis for example) when activated by hazardous chemicals. Often, this results in an impairment of gas exchange, the primary function of the lungs. Therefore prolonged exposure to respiratory irritants may cause sustained breathing difficulties

COBALT FUME

Substance has been investigated as a tumorigen: Tumorigenic-neoplastic in laboratory animals by RTECS criteria.

Chemwatch: **5404-01**Version No: **2.1.1.1**

RS- Lower Cost Leadfree No Clean Solder Wire Handypack #818-3204 (NZ)

Issue Date: **02/06/2020**Print Date: **30/06/2020**

TIN & ROSIN, POLYMERISED & TIN FUME

No significant acute toxicological data identified in literature search.

COBALT & rosin core solder decomposition products & COBALT FUME

COBALT & COBALT FUME

The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important.

Allergic reactions which develop in the respiratory passages as bronchial asthma or rhinoconjunctivitis, are mostly the result of reactions of the allergen with specific antibodies of the IgE class and belong in their reaction rates to the manifestation of the immediate type. In addition to the allergen-specific potential for causing respiratory sensitisation, the amount of the allergen, the exposure period and the genetically determined disposition of the exposed person are likely to be decisive. Factors which increase the sensitivity of the mucosa may play a role in predisposing a person to allergy. They may be genetically determined or acquired, for example, during infections or exposure to irritant substances.

Particular attention is drawn to so-called atopic diathesis which is characterised by an increased susceptibility to allergic rhinitis, allergic bronchial

Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T lymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure.

WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

asthma and atopic eczema (neurodermatitis) which is associated with increased IgE synthesis.

Acute Toxicity	×	Carcinogenicity	x
Skin Irritation/Corrosion	×	Reproductivity	X
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	X

Legend:

X - Data either not available or does not fill the criteria for classification

Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

S- Lower Cost Leadfree No	ENDPOINT	TEST DURATION (HR)	SPECIES		VALUE	SOURCE
ean Solder Wire Handypack #818-3204 (NZ)	Not Available	Not Available	Not Available		Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VAL	UE	SOURCE
	LC50	96	Fish	>0.0	1124mg/L	2
tin	EC50	48	Crustacea	0.00	018mg/L	5
	EC50	72	Algae or other aquatic plants	0.00	9-0.846mg/L	2
	NOEC	72	Algae or other aquatic plants	0.00	1-mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES		VALUE	SOURCE
	LC50	96	Fish		>1-mg/L	2
rosin, polymerised	EC50	48	Crustacea		>2-mg/L	2
	EC50	96	Algae or other aquatic plants		0.031mg/L	2
	NOEC	96	Algae or other aquatic plants		0.013mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VAL	.UE	SOURCE
	LC50	96	Fish	0.00	1-0.09mg/L	2
	EC50	48	Crustacea	0.00	1mg/L	2
copper	EC50	72	Algae or other aquatic plants	0.0	3335mg/L	4
	BCF	960	Fish	200	mg/L	4
	EC25	6	Algae or other aquatic plants	0.00	150495mg/L	4
	NOEC	96	Crustacea	0.00	008mg/L	4
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALU	JE	SOURC
	LC50	96	Fish	0.001	-0.406mg/L	2
1 . 16	EC50	48	Crustacea	0.002	-0.618mg/L	2
cobalt	EC50	96	Algae or other aquatic plants	0.071	-0.314mg/L	2
	BCF	1344	Fish	0.99r	ng/L	4
	NOEC	96	Crustacea	0.001	-0.2819mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES		VALUE	SOURC
rosin core solder decomposition products	Not Available	Not Available	Not Available		Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VAL	UE	SOURC
tin fume	LC50	96	Fish	>0.0	124mg/L	2

Version No: 2.1.1.1

RS- Lower Cost Leadfree No Clean Solder Wire Handypack #818-3204 (NZ)

Issue Date: 02/06/2020 Print Date: 30/06/2020

		I	1	1	I _
	EC50	48	Crustacea	0.00018mg/L	5
	EC50	72	Algae or other aquatic plants	0.009-0.846mg/L	2
	NOEC	72	Algae or other aquatic plants	0.001-mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.001-0.09mg/L	2
	EC50	48	Crustacea	0.001mg/L	2
copper fume	EC50	72	Algae or other aquatic plants	0.013335mg/L	4
	BCF	960	Fish	200mg/L	4
	EC25	6	Algae or other aquatic plants	0.00150495mg/L	4
	NOEC	96	Crustacea	0.0008mg/L	4
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.001-0.406mg/L	2
	EC50	48	Crustacea	0.002-0.618mg/L	2
cobalt fume	EC50	96	Algae or other aquatic plants	0.071-0.314mg/L	2
	BCF	1344	Fish	0.99mg/L	4
	NOEC	96	Crustacea	0.001-0.2819mg/L	2
Legend:			egistered Substances - Ecotoxicological Info PA, Ecotox database - Aquatic Toxicity Data		
	Data 6. NITE (J.	apan) - Bioconcentration Data 7. METI (Jap	pan) - Bioconcentration Data 8. Vendor Data		

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air	
	No Data available for all ingredients	No Data available for all ingredients	

Bioaccumulative potential

Ingredient	Bioaccumulation	
1	No Data available for all ingredients	

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- ▶ Bury residue in an authorised landfill.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Issue Date: **02/06/2020**Print Date: **30/06/2020**

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002624	N.O.S. (Subsidiary Hazard) Group Standard 2017
HSR002535	Gas Under Pressure Mixtures (Subsidiary Hazard) Group Standard 2017
HSR002596	Laboratory Chemicals and Reagent Kits Group Standard 2017
HSR002530	Cleaning Products (Subsidiary Hazard) Group Standard 2017
HSR002585	Fuel Additives (Subsidiary Hazard) Group Standard 2017
HSR002519	Aerosols (Subsidiary Hazard) Group Standard 2017
HSR002521	Animal Nutritional and Animal Care Products Group Standard 2017
HSR002606	Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary Hazard) Group Standard 2017
HSR002644	Polymers (Subsidiary Hazard) Group Standard 2017
HSR002647	Reagent Kits Group Standard 2017
HSR002670	Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2017
HSR002638	Photographic Chemicals (Subsidiary Hazard) Group Standard 2017
HSR002565	Embalming Products (Subsidiary Hazard) Group Standard 2017
HSR002578	Food Additives and Fragrance Materials (Subsidiary Hazard) Group Standard 2017
HSR002558	Dental Products (Subsidiary Hazard) Group Standard 2017
HSR002684	Water Treatment Chemicals (Subsidiary Hazard) Group Standard 2017
HSR002573	Fire Fighting Chemicals Group Standard 2017
HSR100425	Pharmaceutical Active Ingredients Group Standard 2017
HSR002600	Leather and Textile Products (Subsidiary Hazard) Group Standard 2017
HSR002571	Fertilisers (Subsidiary Hazard) Group Standard 2017
HSR002648	Refining Catalysts Group Standard 2017
HSR002653	Solvents (Subsidiary Hazard) Group Standard 2017
HSR002544	Construction Products (Subsidiary Hazard) Group Standard 2017
HSR002549	Corrosion Inhibitors (Subsidiary Hazard) Group Standard 2017
HSR100757	Veterinary Medicine (Limited Pack Size, Finished Dose) Standard 2017
HSR100758	Veterinary Medicines (Non-dispersive Closed System Application) Group Standard 2017
HSR100759	Veterinary Medicines (Non-dispersive Open System Application) Group Standard 2017
HSR002612	Metal Industry Products (Subsidiary Hazard) Group Standard 2017
HSR002503	Additives, Process Chemicals and Raw Materials (Subsidiary Hazard) Group Standard 2017
HSR002552	Cosmetic Products Group Standard 2017

TIN IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC) New Zealand Workplace Exposure Standards (WES)

ROSIN, POLYMERISED IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Inventory of Chemicals (NZIoC)

COPPER IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

COBALT IS FOUND ON THE FOLLOWING REGULATORY LISTS

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B : Possibly carcinogenic to humans

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) $\mathop{\rm Act}\nolimits$ - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

ROSIN CORE SOLDER DECOMPOSITION PRODUCTS IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

TIN FUME IS FOUND ON THE FOLLOWING REGULATORY LISTS

Chemwatch: 5404-01
Version No: 2.1.1.1

PS Lower Cost Loadfree No Cl

Page 10 of 11 RS- Lower Cost Leadfree No Clean Solder Wire Handypack #818-3204 (NZ)

Issue Date: **02/06/2020**Print Date: **30/06/2020**

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification

of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)
New Zealand Workplace Exposure Standards (WES)

New Zealand Workplace Exposure Standards (WES)

COPPER FUME IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

COBALT FUME IS FOUND ON THE FOLLOWING REGULATORY LISTS

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B : Possibly carcinogenic to humans

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (tin; rosin, polymerised; copper; cobalt; tin fume; copper fume; cobalt fume)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (tin; copper; cobalt; tin fume; copper fume; cobalt fume)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (rosin, polymerised)
Vietnam - NCI	Yes
Russia - ARIPS	No (rosin, polymerised)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	02/06/2020
Initial Date	02/06/2020

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

Chemwatch: 5404-01 Page 11 of 11 Issue Date: 02/06/2020 Version No: 2.1.1.1 Print Date: 30/06/2020

RS- Lower Cost Leadfree No Clean Solder Wire Handypack #818-3204 (NZ)

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit $_{\circ}$

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.