

Floor standing polyester enclosure, PanelSeT PLA, plain door, open bottom, 1500x1250x320mm, IP54, IK10

NSYPLAZ15123G

EAN Code: 3606480775734

Price: 2.042,00 EUR

Main

| Range | PanelSeT | |
|---------------------------|---|--|
| product name | PanelSeT PLA | |
| Enclosure type | Multi-purpose | |
| Product or component type | Suitable enclosure | |
| Version | PLAZ | |
| Nominal height | 1500 mm | |
| Nominal width | 1250 mm | |
| Nominal depth | 320 mm | |
| Enclosure mounting | Floor-standing | |
| Device composition | 1 top part 1 bottom part 2 side part 2 door 2 rear panel 1 plinth | |

Complementary

| Body type | Sealed top and open bottom part assembled with side parts | |
|-----------------------------|---|--|
| Door type | Plain front | |
| Number of doors | 2 door(s) | |
| Door opening side | Right and left (120 °) | |
| Lock type | 4 points lock, handle with 5 mm double bar insert | |
| Accessibility for operation | Rear Bottom Front | |
| Removable parts | Door by hinges Rear panel by fixing element | |
| Material | Polyester reinforced with fibreglass | |
| Colour | Grey (RAL 7035) | |
| Standards | IEC 62208 | |
| Product certifications | Veritas | |
| Electrical insulation class | Class II | |

Environment

Rates duty January 2016

| IP degree of protection | IP54 conforming to IEC 60529 (plinth type open bottom) | | |
|-------------------------------------|--|--|--|
| IK degree of protection | IK10 conforming to IEC 62262 (plain door) | | |
| Fire resistance | 960 °C conforming to IEC 62208 | | |
| Ambient air temperature for storage | -3590 °C | | |

Packing Units

| _ | |
|------------------------------|------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 37.000 cm |
| Package 1 Width | 132.000 cm |
| Package 1 Length | 156.000 cm |
| Package 1 Weight | 70.500 kg |
| Unit Type of Package 2 | PAL |
| Number of Units in Package 2 | 2 |
| Package 2 Height | 169.000 cm |
| Package 2 Width | 100.000 cm |
| Package 2 Length | 132.000 cm |
| Package 2 Weight | 154.000 kg |



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

| ∇ Environmental footprint | |
|---|-------------------------------|
| Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) | 548 |
| Environmental Disclosure | Product Environmental Profile |

Use Better

| Materials and Substances | |
|--|--------------------------------------|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| SCIP Number | 1341ad4e-77b9-40e3-bab0-32043fbc5959 |

Use Again

| ○ Repack and remanufacture | |
|----------------------------|--|
| Circularity Profile | No need of specific recycling operations |
| Take-back | No |