## Product datasheet Characteristics

## ZBVB6

# blue light block for head Ø22 integral LED 24V screw clamp terminals



Price\*: 6.50 GBP



#### Main

Wall		4
Range of product	Harmony XB4 Harmony XB5	
Product or component type	Light block	9
Device short name	ZBV	<del></del> ‡
Sale per indivisible quantity	5	<u></u>
Connections - terminals Screw clamp terminals, $<= 2 \times 1.5 \text{ mm}^2 \text{ with cable end conforming to EN 60947-1}$ Screw clamp terminals, $>= 1 \times 0.22 \text{ mm}^2 \text{ without cable end conforming to EN 60947-1}$		<u> </u>
Signalling type	Steady	: :
Light source	Protected LED	ں وے ای
Bulb base	Integral LED	.i.
Light block supply	Direct	- <del>-</del>
Light source colour	Blue	
[Us] rated supply voltage	24 V AC/DC at 50/60 Hz	9

#### Complementary

- Complementary		
Net weight	0.017 kg	
Tightening torque	0.81.2 N.m conforming to EN 60947-1	
Shape of screw head	Cross compatible with Philips no 1 screwdriver Cross compatible with pozidriv No 1 screwdriver Slotted compatible with flat Ø 4 mm screwdriver Slotted compatible with flat Ø 5.5 mm screwdriver	
Supply voltage limits	19.230 V DC 21.626.4 V AC	
Current consumption	18 mA	
Service life	100000 h at rated voltage and 25 °C	
Surge withstand	1 kV conforming to IEC 61000-4-5	
Mounting of block	Front mounting	
Electrical composition code	M1 M2	

Nov 29, 2019

Device presentation	Dagic cicinent	
Device presentation	Basic element	
	PF1	
	P2	
	P1	
	MF1	
	M10	
	M6	
	M5	
	M4	
	M3	

#### Environment

Protective treatment	TH		
Ambient air temperature for storage	-4070 °C		
Ambient air temperature for operation	-4070 °C		
IP degree of protection	IP20 conforming to IEC 60529		
Standards	JIS C8201-5-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-1 CSA C22.2 No 14 UL 508 EN/IEC 60947-5-5 JIS C8201-1		
Product certifications	CSA UL listed		
Resistance to fast transients	2 kV conforming to IEC 61000-4-4		
Resistance to electromagnetic fields	10 V/m conforming to IEC 61000-4-3		
Resistance to electrostatic discharge	6 kV on contact (on metal parts) conforming to IEC 61000-4-2 8 kV in free air (in insulating parts) conforming to IEC 61000-4-2		
Electromagnetic emission	Class B conforming to IEC 55011		

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection never end up in rubbish bins	

#### Contractual warranty

\	40	
Warranty	18 months	
•		