



magnetic coil 380 V AC, 50/60 Hz, for contactors 3RT2023-.A, 3RT2024-.A and 3RT2025-.A

product brand name	SIRIUS
product category	Solenoid coils
product designation	Magnet coil
product type designation	3RT29
General technical data	
power loss [V·A] of magnet coil at AC typical	7.6 VA
Substance Prohibittance (day/month/year)	10/01/2009
Net Weight	0.073 kg
type of voltage of the control supply voltage	AC
control supply voltage 1 at AC - at 50 Hz rated value - at 60 Hz rated value	380 V 380 V
operating range factor control supply voltage rated value of magnet coil at AC - at 50 Hz - at 60 Hz	0.8 ... 1.1 0.85 ... 1.1
apparent pick-up power of magnet coil at AC - at 50 Hz - at 60 Hz	65 VA 73 VA
inductive power factor with closing power of the coil - at 50 Hz - at 60 Hz	0.82 0.76
apparent holding power of magnet coil at AC - at 50 Hz - at 60 Hz	7.6 VA 7.2 VA
inductive power factor with the holding power of the coil - at 50 Hz - at 60 Hz	0.25 0.28

Approvals Certificates			
Environment	General Product Approval	EMV	Maritime application

[Environmental Conformations](#)



Maritime application	other
----------------------	-------



[Confirmation](#)

[Miscellaneous](#)



Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2924-5AU21>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2924-5AU21>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2924-5AU21>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2924-5AU21&lang=en

last modified:

4/18/2025