



# 中国国家强制性产品认证证书

证书编号: 2010010307434394

### 委托人名称、地址

Siemens AG, GWA  
Werner-von-Siemens-Strasse 48, D-92220 Amberg, Germany

### 生产者(制造商)名称、地址

Siemens AG, GWA  
Werner-von-Siemens-Strasse 48, D-92220 Amberg, Germany

### 生产企业名称、地址

Siemens AG, GWA  
Werner-von-Siemens-Strasse 29, D-93413 Cham, Germany

### 产品名称和系列、规格、型号

塑料外壳式断路器

3RV20, 3RV21, 3RV23, 3RV24, 3RV27, 3RV28, 3RV60, 3RV63, 3RV64 型号参数详见附录

### 产品标准和技术要求

GB 14048.2-2008, GB 14048.4-2010

上述产品符合强制性产品认证实施规则  
CNCA-C03-02:2014的要求, 特发此证。

发证日期: 2015年03月04日

有效期至: 2020年03月04日

证书有效期内本证书的有效性依据发证机构的定期监督获得保持。

本证书为变更证书, 证书首次颁发日期: 2010年09月30日

本证书的相关信息可通过国家认监委网站www.cnca.gov.cn查询



主任:

## 中国质量认证中心

中国·北京·南四环西路188号9区100070

<http://www.cqc.com.cn>



Q 1090625



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

No. : 2010010307434394

## NAME AND ADDRESS OF THE APPLICANT

Siemens AG, GWA  
Werner-von-Siemens-Strasse 48, D-92220 Amberg, Germany

## NAME AND ADDRESS OF THE MANUFACTURER

Siemens AG, GWA  
Werner-von-Siemens-Strasse 48, D-92220 Amberg, Germany

## NAME AND ADDRESS OF THE FACTORY

Siemens AG, GWA  
Werner-von-Siemens-Strasse 29, D-93413 Cham, Germany

## NAME, MODEL AND SPECIFICATION

Moulded Case Circuit Breaker

3RV20, 3RV21, 3RV23, 3RV24, 3RV27, 3RV28, 3RV60, 3RV63, 3RV64 See the Appendix

## THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB 14048. 2-2008, GB 14048. 4-2010

This is to certify that the above mentioned products have met the requirements of implementation rules for compulsory certification(REF NO. CNCA-C03-02:2014).

Date of issue: Mar.04,2015      Date of expiry: Mar.04,2020

Validity of this certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original certification: Sep.30,2010

This certificate can be verified through CNCA's website: [www.cnca.gov.cn](http://www.cnca.gov.cn)



President:

  
Wang Kejiao



**CHINA QUALITY CERTIFICATION CENTRE**

Section 9, No.188, Nansihuan Xilu, Beijing 100070 P.R.China

<http://www.cqc.com.cn>

Q 1090625



# 中国国家强制性产品认证证书

附录:

第 1 页 共 14 页

证书编号: 2010010307434394

纸号: 1090625

3RV20,3RV21,3RV23,3RV24, 3RV27,3RV28,3RV60,3RV63,3RV64

Ue: AC400/690V;Ui:690V;

In: 0.16 ~ 40A;

过电流脱扣器类型: 热磁式;

(3RV2.1/3RV6.1) AC400V:Ics:100kA(up to 12.5A),30kA(16A/15A);Icu:100kA(up to 12.5A),55kA(16A/15A);

AC690V:Ics:100kA(up to 1.6A),10kA(2-3.2A),4kA(4-16A);

Icu:100kA(up to 1.6A),10kA(2-3.2A),6kA(4-12.5A),

4kA(16A/15A);

(3RV2.2/3RV6.2) AC400V:Ics:100kA(up to 12.5A),25kA(16-32A),10kA(36-40A);

Icu:100kA(up to 12.5A),55kA(16-32A),20kA(36-40A);

AC690V:Ics:100kA(up to 1.6A),10kA(2-3.2A),4kA(4-12.5A),

2kA(16-40A);

Icu:100kA(up to 1.6A),10kA(2-3.2A),6kA(4-12.5A),

4kA(16-32A),3kA(36-40A);

(3RV2023) AC690V:Ics:4kA(12.5A),2kA(16-25A);Icu:6kA(12.5A),4kA(16-25A);

脱扣级别:10(除了 3RV23,3RV63,3RV27,3RV28);

使用类别: A 类; 极数: 3P;

配用的辅助触头:见下表

3RV2901-.A,3RV2901-.B,3RV2901-.C,3RV2901-.J,3RV2921-.M,3RV6901-.A,

3RV6901-.B,3RV6901-.C,3RV6901-.J,3RV6921-.M:

Ith:10A

注: 此附录与证书同时使用时有效。



主任:

中国质量认证中心

中国 · 北京 · 南四环西路 188 号 9 区 100070

<http://www.cqc.com.cn>





# 中国国家强制性产品认证证书

附录:

第 2 页 共 14 页

证书编号: 2010010307434394

纸号: 1090625

AC-15: 24V/6A,220V/4A,230V/4A,400V/3A,690V/1A

AC-12: 690V/10A

DC-13: 24V/2A,110V/0.5A,220V/0.25A,230V/0.25A,400V/0.1A

3RV2901-.D,3RV6901-.D:

Ith:10A

AC-15: 24V/4A,230V/3A

AC-12:230V/10A

DC-13: 24V/1A,220V/0.1A

3RV2901-.E,3RV2901-.F,3RV6901-.E,3RV6901-.F:

Ith:2.5A

AC-15: 24V/2A,230V/0.5A

AC-12:230V/2.5A

DC-13: 24V/1A,48V/0.3A,60V/0.15A

3RV2901-.G,3RV6901-.G:

Ith:0.3A

AC-14: 60V/0.3A

DC-13: 60V/0.3A

3RV21:

Ith:4A

AC-15: 24V/1.5A,230V/1.5A

DC-13: 24V/1A,230V/0.11A

注: 此附录与证书同时使用时有效。



主任:

中国质量认证中心

中国·北京·南四环西路188号9区100070

<http://www.cqc.com.cn>





# 中国国家强制性产品认证证书

附录:

第 3 页 共 14 页

证书编号: 2010010307434394

纸号: 1090625

型号的解释:

<u>3RV20</u>	<u>21</u>	<u>-4A</u>	<u>A</u>	<u>1</u>	<u>5</u>	<u>-0DA0</u>
I	II	III	IV	V	VI	VII

## I. Basic Type 基本型号

- 3RV20 - Sirius Innovation Circuit Breaker for motor protection with overload and short circuit protection Sirius Innovation 电机保护断路器系列, 有过载和短路保护功能
- 3RV21 - Sirius Innovation Circuit Breaker for motor protection with short circuit protection, overload tripping is indicated by an attached tripping module (only up to 32A) Sirius Innovation 电机保护断路器系列, 有短路保护功能, 过载脱扣倍数见附件(仅适用于电流值不大于 32A)
- 3RV23 - Sirius Innovation Circuit Breaker for starter combination with short circuit protection only Sirius Innovation 起动器组合断路器系列, 仅有短路保护功能
- 3RV24 - Sirius Innovation Circuit Breaker for transformer protection with overload and short circuit protection (only up to 25A) Sirius Innovation 变压器断路器系列, 有过载和短路保护功能(仅适用于电流值不大于 25A)
- 3RV60 - Circuit Breaker for motor protection with overload and short circuit protection 电机保护断路器系列, 有过载和短路保护功能
- 3RV63 - Circuit Breaker for starter combination with short circuit protection only 起动器组合断路器系列, 仅有短路保护功能
- 3RV64 - Circuit Breaker for transformer protection with overload and short circuit protection (only up to 25A) 变压器断路器系列, 有过载和短路保护功能(仅适用于电流值不大于 25A)

## II. Size of terminal for main circuit 主回路端子尺寸

- 11 - Up to 16 A 至 16A
- 21 - up to 40 A 至 40A
- 23 - Devices rated 690V only (only for setting ranges 12.5 up to 25A)

注: 此附录与证书同时使用时有效。



主任:

## 中国质量认证中心

中国 · 北京 · 南四环西路 188 号 9 区 100070

<http://www.cqc.com.cn>





# 中国国家强制性产品认证证书

附录:

第 4 页 共 14 页

证书编号: 2010010307434394

纸号: 1090625

III. Setting Ranges	电流设置范围		Fixed Current (A)
Suffix	From (A)	To (A)	固定电流
前缀	从	到	
			ONLY for 3RV23, 3RV63 仅适用于 3RV23, 3RV63 型号
-0A	0.11	0.16	0.16
-0B	0.14	0.2	0.2
-0C	0.18	0.25	0.25
-0D	0.22	0.32	0.32
-0E	0.28	0.4	0.4
-0F	0.35	0.5	0.5
-0G	0.45	0.63	0.63
-0H	0.55	0.8	0.8
-0J	0.7	1	1
-0K	0.9	1.25	1.25
-1A	1.1	1.6	1.6
-1B	1.4	2	2
-1C	1.8	2.5	2.5
-1D	2.2	3.2	3.2
-1E	2.8	4	4
-1F	3.5	5	5
-1G	4.5	6.3	6.3
-1H	5.5	8	8
-1J	7	10	10
-1K	9	12.5	12.5
3RV2 only: -4A	10	16	16
3RV6 only: -4A	11	16	16
3RV2 only: -4B	13	20	20
3RV6 only: -4B	14	20	20
3RV2 only: -4C	16	22	22

注: 此附录与证书同时使用时有效。



主任:

## 中国质量认证中心

中国 · 北京 · 南四环西路 188 号 9 区 100070

<http://www.cqc.com.cn>





# 中国国家强制性产品认证证书

附录:

第 5 页 共 14 页

证书编号: 2010010307434394

纸号: 1090625

3RV6 only: -4C	17	22	22
3RV2 only: -4D	18	25	25
3RV6 only: -4D	20	25	25
-4N	23	28	28
-4E	27	32	32
-4P	30	36	36
-4F	34	40	40

#### IV.Tripping Class 脱扣等级

A -setting ranges with instantaneous tripping and overload tripping Class 10

瞬间脱扣级别 10, 具有电流设置范围

C – with instantaneous tripping and without overload tripping(only for 3RV23 and 3RV63)(仅适用于 3RV23 and 3RV63 型号)

#### V.Type of Terminals 接线端子形式

1 -Screw Terminal 螺丝接线端子

2 -spring terminals (only up to 32A) 弹簧接线端子(电流不大于 32A)

4 -Ring lug terminals (only up to 32A) 环形压片接线端子(电流不大于 32A)

#### VI.Auxiliary Switches 辅助开关 (3RV29..., 3RV69 有 CCC 证书....)

(Combinations with certified accessories Type 3RV29... or 3RV69...)

0 -without 没有辅助开关

1 -1NO + 1NC, side mounted 1 常开+1 常闭, 侧面安装

2 -2NO, side mounted 2 常开, 侧面安装

3 -2NC, side mounted 2 常闭, 侧面安装

4 -1NO/NC Changeover, top mounted 1 常开/1 常闭转化触头, 顶部安装

5 -1NO + 1NC, top mounted 1 常开+1 常闭, 顶部安装

6 - 2NO, top mounted 2 常开, 顶部安装

#### VII.Others (optional) 其他(可选项)

注: 此附录与证书同时使用时有效。



主任:

## 中国质量认证中心

中国 · 北京 · 南四环西路 188 号 9 区 100070

<http://www.cqc.com.cn>





# 中国国家强制性产品认证证书

附录:

第 6 页 共 14 页

证书编号: 2010010307434394

纸号: 1090625

.. - Manufacturer's identification 制造商识别

例如 -0DA0 special marking 特殊表明

-0KH0 special Mounting on Din Rail 特别为 DIN 铁路安装

3RV2711	-	0A	D	1	0
I			II III	IV	V

## I. Basic type 基本型号

3RV2711 -circuit Breaker up to 15A, same as 3RV2011, just with fixed current setting  
断路器, 与 3RV2011 相同, 固定电流设置

3RV2811 -circuit Breaker up to 15A, same as 3RV2411, just with fixed current setting  
断路器, 与 3RV2411 相同, 固定电流设置

3RV2721 -circuit Breaker(20 and 22A only), same as 3RV2021, just with fixed current setting

断路器, 与 3RV2021 相同, 固定电流设置

3RV2821 - circuit Breaker(20 and 22A only), same as 3RV2421, just with fixed current setting

断路器, 与 3RV2421 相同, 固定电流设置

## II. Rated Current 额定电流

-0A -	0.16 A	-1A -	1.6 A
-0B -	0.2 A	-1B -	2.0 A
-0C -	0.25 A	-1C -	2.5 A
-0D -	0.32 A	-1D -	3.2 A
-0E -	0.4 A	-1E -	4.0 A
-0F -	0.5 A	-1F -	5.0 A
-0G -	0.63 A	-1G -	6.3 A
-0H -	0.8 A	-1H -	8.0 A
-0J -	1.0 A	-1J -	10 A

注: 此附录与证书同时使用时有效。



主任:

## 中国质量认证中心

中国 · 北京 · 南四环西路 188 号 9 区 100070

<http://www.cqc.com.cn>







# 中国国家强制性产品认证证书

附录:

第 7 页 共 14 页

证书编号: 2010010307434394

纸号: 1090625

-0K -	1.25 A	-1K -	12.5 A
-4A -	15 A	-4B -	20 A
-4C -	22 A		

III.Tripping Class	脱扣等级
D -Circuit Breaker	断路器
IV.Type of Terminal	接线端子形式
1 -Screw Terminals	螺丝接线端子
V.Auxiliary Switches	辅助开关
0 -without	没有辅助开关

注: 此附录与证书同时使用时有效。



主任:

## 中国质量认证中心

中国 · 北京 · 南四环西路 188 号 9 区 100070

<http://www.cqc.com.cn>





# 中国国家强制性产品认证证书

附录:

第 8 页 共 14 页

证书编号: 2010010307434394

纸号: 1090625

## Accessories:

Following components are considered as accessories auxiliary contact blocks for use with 3RV20, 3RV21, 3RV23, 3RV24, 3RV27, 3RV28, 3RV60, 3RV63, 3RV64 series. Such components are assembled already to the 3RV20, 3RV21, 3RV23, 3RV24, 3RV27, 3RV28, 3RV60, 3RV63, 3RV64 or are available as single parts with CCC marking, refer to CCC certificate No.: 2014010305701374 or 2014010305698897.

### Auxiliary contacts: 辅助触头

3RV2901	-1	A
I	II	III

#### I - Basic type

3RV2901 -	Auxiliary contact blocks for 3RV2
3RV2921 -	Alarm switch for 3RV2
3RV6901 -	Auxiliary contact blocks for 3RV6
3RV6921 -	Alarm switch for 3RV6

#### II - Type of terminals

-1 -	Screw Terminal
-2 -	Spring terminals
-4 -	Ring lug terminals

#### III - Contact arrangements

A -	1NO + 1NC, side-mounting
B -	2NO, side-mounting
C -	2NC, side-mounting
D -	1NO + 1NC changeover, top-mounting
E -	1NO + 1NC, top-mounting
* F -	2NO, top-mounting
G -	1NO + 1NC changeover, top-mounting, micro switch
J -	2NO + 2NC, side-mounting
M -	2NO + 2NC, side-mounting, alarm switch

注: 此附录与证书同时使用时有效。



主任:

## 中国质量认证中心

中国 · 北京 · 南四环西路 188 号 9 区 100070

<http://www.cqc.com.cn>





# 中国国家强制性产品认证证书

附录:

第 9 页 共 14 页

证书编号: 2010010307434394

纸号: 1090625

Following components are considered as accessories for use with 3RV20, 3RV21, 3RV23, 3RV24, 3RV27, 3RV28, 3RV60, 3RV63, 3RV64 series. Such components are assembled already to the 3RV20, 3RV21, 3RV23, 3RV24, 3RV27, 3RV28, 3RV60, 3RV63, 3RV64 or are available as single parts without CCC marking.

Undervoltage trip units, Shunt releases: 欠压,分励脱扣器

3RV2902	-1	A	B4
I	II	III	IV

I - Basic type

3RV2902 -	Undervoltage trip units, Shunt releases for 3RV2
3RV2922 -	Undervoltage trip unit with leading auxiliary contacts for 3RV2
3RV6902 -	Undervoltage trip units, Shunt releases for 3RV6
3RV6922 -	Undervoltage trip unit with leading auxiliary contacts for 3RV6

II - Type of terminals

-1 -	Screw Terminal
-2 -	Spring terminals
-4 -	Ring lug terminals

III - Type of Accessory

A -	Undervoltage trip unit
C -	Undervoltage trip unit with leading auxiliary contacts
D -	Shunt trip unit

IV - Rated voltage for Undervoltage trip unit

B4 -	24V, dc
B0 -	24V, 50Hz
F0 -	110V, 50Hz; 120V, 60Hz
M1 -	208V, 60Hz

注: 此附录与证书同时使用时有效。



主任:

中国质量认证中心

中国 · 北京 · 南四环西路 188 号 9 区 100070

<http://www.cqc.com.cn>





# 中国国家强制性产品认证证书

附录:

第 10 页 共 14 页

证书编号: 2010010307434394

纸号: 1090625

P0 -	230V, 50Hz; 240V, 60Hz
V0 -	400V, 50Hz; 440V, 60Hz
V1 -	415V, 50Hz; 480V, 60Hz
S0 -	500V, 50Hz; 600V, 60Hz
G6 -	100V, 50 Hz; 110V, 60Hz
N0 -	220V, 50Hz
N6 -	200V, 50Hz; 220V, 60Hz
Q0 -	380V, 50Hz
U0 -	240V, 50Hz

IV - Rated voltage for Shunt trip unit

B0 -	20-24V, 50/60Hz
F0 -	90-110V, 50/60Hz
P0 -	210-240V, 50/60Hz
V0 -	350-415V, 50/60Hz
S0 -	500V, 50/60Hz

Door-Coupling Rotary mechanism: 旋转门锁机械装置

3RV1926-0 -B  
I II

I Basic type

3RV1926-0 - Door coupling rotary mechanism for use with 3RV1.2,3RV1.3, or 3RV1.4, 3RV2.1 or 3RV2.2 or 3RA6

3RV2926-0 - Door coupling rotary mechanism for use with 3RV1.2,3RV1.3, 3RV1.4, 3RV2.1, 3RV2.2 or 3RA6

3RV6926-0 - Door coupling rotary mechanism for use with 3RV6.1 or 3RV6.2,

II Assembly

注: 此附录与证书同时使用时有效。



主任:

中国质量认证中心

中国 · 北京 · 南四环西路 188 号 9 区 100070

<http://www.cqc.com.cn>





# 中国国家强制性产品认证证书

附录:

第 11 页 共 14 页

证书编号: 2010010307434394

纸号: 1090625

- B - shaft 130 mm / standard handle, black
- C - shaft 130 mm / emergency stop handle, red-yellow
- D - shaft 330 mm / without handle
- K - shaft 330 mm / standard handle, black
- L - shaft 330 mm / emergency stop handle, red-yellow
- M - same as -0B inclusive trip marking

3RV1926-2 B  
I II

I Basic type

3RV1926-2 - Door coupling rotary mechanism with metal frame

Or 3RV2926-2 for use with 3RV1.2, 3RV2.1 or 3RV2.2 – pad-lockable inside and outside of control enclosures

II Assembly

B - shaft 300 mm / standard handle, grey

C - shaft 300 mm / emergency stop handle, red-yellow

Other:

3RV2928-1A

Isolator Module

3RV2928-1K

Type E Adapter

3RV2928-0P

Sealing Cap

3RV2901-0H

Cover

3RV2928-4AA00

Cover for ring-lug-terminals (main terminals)

3RV2908-4AA10

Cover for ring-lug-terminals (auxiliary switch, top mounting)

3RV2928-0B

Plug-in lugs for screw mounting

8US1251-5DS10

Adapter for SIRIUS Circuit breaker, Size S00, screw terminals, 200mm

8US1251-5DT10

Adapter for SIRIUS Circuit breaker, Size S00, screw terminals, 260mm

8US1251-5NT10

Adapter for SIRIUS Circuit breaker, Size S0, screw terminals, 260mm

8US1251-5DT11

Adapter for SIRIUS Circuit breaker Size S00, spring terminals, 260mm

注: 此附录与证书同时使用时有效。



主任:

中国质量认证中心

中国 · 北京 · 南四环西路 188 号 9 区 100070

<http://www.cqc.com.cn>





# 中国国家强制性产品认证证书

附录:

第 12 页 共 14 页

证书编号: 2010010307434394

纸号: 1090625

8US1251-5NT11	Adapter for SIRIUS Circuit breaker Size S0, spring terminals, 260mm
8US1251-5DS10	Fastbus Adapter Direct Starter, Size S00, screw terminals
8US1251-5NT10	Fastbus Adapter Direct Starter, Size S0, screw terminals
8US1251-5DS10	Fastbus Adapter Reversing Starter, Size S00, screw terminals
8US1250-5AS10	Support for Reversing Starter, Size S00, screw terminals
8US1251-5NT10	Fastbus Adapter Reversing Starter, Size S0, screw terminals
8US1250-5AT10	Support for Reversing Starter, Size S0, screw terminals
8US1251-5DT11	Fastbus Adapter Direct Starter, Size S00, spring terminals
8US1251-5NT11	Fastbus Adapter Direct Starter, Size S0, spring terminals
8US1251-5DT11	Fastbus Adapter Reversing Starter, Size S00, spring terminals
8US1250-5AT10	Support for Reversing Starter, Size S00, spring terminals
8US1251-5NT11	Fastbus Adapter Reversing Starter, Size S0, spring terminals
8US1250-5AT10	Support for Reversing Starter, Size S0, spring terminals
8US1998-1CA10	Vibration & Shock Kit
3RV2928-1H	Terminal Block
3RV2925-5AB	3-phase Line-Side Terminal
3RV2925-5EB	3-phase Line-Side Terminal for Self-protected Motor Starter
3RV1915-1AB	3-phase busbar for 2 devices 45mm distance
3RV1915-1BB	3-phase busbar for 3 devices 45mm distance
3RV1915-1CB	3-phase busbar for 4 devices 45mm distance
3RV1915-1DB	3-phase busbar for 5 devices 45mm distance
3RV1915-2AB	3-phase busbar for 2 devices 55 mm distance
3RV1915 2BB	3-phase busbar for 3 devices 55 mm distance
3RV1915-2CB	3-phase busbar for 4 devices 55 mm distance
3RV1915-2DB	3-phase busbar for 5 devices 55 mm distance
3RV1915-3AB	3-phase busbar for 2 devices 63 mm distance
3RV1915-3CB	3-phase busbar for 4 devices 63 mm distance
3RV2915-5B	3-phase Line-Side Terminal, connection from below

注: 此附录与证书同时使用时有效。



主任:

中国质量认证中心

中国 · 北京 · 南四环西路 188 号 9 区 100070

<http://www.cqc.com.cn>





# 中国国家强制性产品认证证书

附录:

第 13 页 共 14 页

证书编号: 2010010307434394

纸号: 1090625

- 3RV1915-6AB Cover for tags
- 3RA1921-1D Link Module between Circuit Breaker and Contactor Size S00, screw terminals, 10 pieces
- 3RA1921-1DA00 Link Module between Circuit Breaker and Contactor Size S00, screw terminals, 1 piece
- 3RA2921-1A Link Module between Circuit Breaker and Contactor Size S0, AC-Coil, screw terminals, 10 pieces
- 3RA2921-1AA00 Link Module between Circuit Breaker and Contactor Size S0, AC-Coil, screw terminals, 1 piece
- 3RA2921-1B Link Module between Circuit Breaker and Contactor Size S0, DC-Coil, screw terminals, 10 pieces
- 3RA2921-1BA00 Link Module between Circuit Breaker and Contactor Size S0, DC-Coil, screw terminals, 1 piece
- 3RA2911-2A Link Module between Circuit Breaker and Contactor Size S00, spring terminals, 10 pieces
- 3RA2911-2AA00 Link Module between Circuit Breaker and Contactor Size S00, spring terminals, 1 piece
- 3RA2921-2A Link Module between Circuit Breaker and Contactor Size S0, spring terminals, 10 pieces
- 3RA2921-2AA00 Link Module between Circuit Breaker and Contactor Size S0, spring terminals, 1 piece
- 3RA2921-2F Link Module between Circuit Breaker, screw terminals and Contactor Size S0, spring terminals, 10 pieces
- 3RA2921-2FA00 Link Module between Circuit Breaker, screw terminals and Contactor Size S0, spring terminals, 1 piece
- 3RA2921-2G Link Module between Circuit Breaker, spring terminals and Soft starter Size S0, spring terminals, 10 pieces
- 3RA2921-2GA00 Link Module between Circuit Breaker, spring terminals and Soft starter Size S0, spring terminals, 1 piece
- 3RA2922-1A Mounting rail adapter, 5 pieces
- 3RA2922-1AA00 Mounting rail adapter, 1 piece

注: 此附录与证书同时使用时有效。



主任:

## 中国质量认证中心

中国 · 北京 · 南四环西路 188 号 9 区 100070

<http://www.cqc.com.cn>





# 中国国家强制性产品认证证书

附录:

第 14 页 共 14 页

证书编号: 2010010307434394

纸号: 1090625

3RA2911-1C	Spacer module, 5 pieces
3RA2911-1CA00	Spacer module, 1 piece
3RV1923-1DA01	Cast aluminum enclosures for surface mounting, 72mm
3RV1923-1CA00	Molded-plastic enclosures for surface mounting, 54mm
3RV1923-1DA01	Molded-plastic enclosures for surface mounting, 72mm
Infeed system:	
3RV2917-1A	Infeed, left side with 2 sockets
3RV2917-1E	Infeed, right side with 2 sockets
3RV2917-4A	Expansion module with 2 sockets
3RV2917-4B	Expansion module with 3 sockets
3RV2917-5CA00	Plug for 3RV2, Screw terminal Size S00
3RV2917-5AA00	Plug for 3RV2, Spring terminal Size S00
3RV2927-5AA00	Plug for 3RV2, Screw terminal Size S0
3RV2927-5AA00	Plug for 3RV2, Spring terminal Size S0
3RV2927-7AA00	Contactor Base
3RV2917-5BA00	Extension plug
3RV2917-5E	Broadened Extension plug
3RV2917-5D	Terminal Block for integration of external components
3RV2917-6A	End Cover

注: 此附录与证书同时使用时有效。



主任:

中国质量认证中心

中国 · 北京 · 南四环西路 188 号 9 区 100070

<http://www.cqc.com.cn>

