

Parker Product Datasheet



Parker offers standard needle valves and needle valves with a reverse free-flow check. Parker's needle valves are non-compensated adjustable orifices capable of flows up to 225 lpm (60 gpm) and pressures as high as 420 bar (6000 psi).

PART NUMBER: J02B2ZN

FLOW RATE: 8 GAL/MIN, 30 L/MIN

SEAL MATERIAL: Nitrile

MAXIMUM INLET PRESSURE RATING: 6000 PSI, 420 BAR

ADJUSTMENT MECHANISM: Tamper Resistant

NEEDLE TYPE: Fine

PRODUCT OVERVIEW

Parker's family of needle valves feature a highly contamination tolerant design that allows for fine metering with manual adjustment to create and orifice and control flow. These valves can operate with hydraulic system flows as high as 225 lpm and pressures up to 420 bar with the option of an integrate reverse free-flow check valve. Parker's needle valves or needle-check valves are ideal for cylinder or motor control and/or bleed-off applications within a broad range of markets, such as the agriculture, construction, material handling, industrial, oil & gas, and several more.

Markets:

- Agriculture
- Construction Equipment
- Material Handling Equipment
- Miscellaneous Industrial
- Miscellaneous Mobile

- Oil & Gas

Features/Benefits:

- High flow capacity from a small cavity
- Manual shutoff with extremely low leakage
- Fine adjustment control/sensitivity
- Very tolerant to contamination
- Tamperproof options available
- Free-flow reverse check available
- All external parts zinc plated

Applications:

- Accumulator bleed-off
- Motor speed control
- Cylinder speed control

Additional Technical Insight:

Needle valves offer economical solutions for applications that require basic adjustable control of hydraulic flow. The effective orifice size inside the valve is varied with screw or knob adjustments and the valve can be made tamper resistant with the addition of an optional cap. Shutoff can be achieved when the valve is adjusted completely closed. Once the adjustment is set, the valve acts as a fixed orifice. Like all fixed orifices, any changes in pressure will cause changes in flow.

If constant flow is required regardless of system or load pressure, please consider Parker's pressure compensated flow controls. Parker's J02A2, NVH081, NVH101, and J06A2 cartridges are standard 2-port needle valves with fine adjustment options available. The orifice will meter in both directions, but flow from port 2 to 1 is preferred. If unrestricted reverse flow is required, an additional check valve will need to be used with these needle valve versions. Parker also offers J02B2, FV101, and FV102 needle valves with internal reverse free flow checks in order to reduce manifold size and component quantities.

TECH SPECIFICATIONS

MAXIMUM OPERATING TEMPERATURE

+121 °C

MAXIMUM OPERATING TEMPERATURE

+250 °F

DIVISION

Hydraulic Valve Systems Division

DIVISION	Hydraulic Valve Systems Division Europe
MAXIMUM OPERATING PRESSURE	6000 psi
MAXIMUM OPERATING PRESSURE	420 bar
FLOW RATE	30 L/min
FLOW RATE	8 gal/min
MINIMUM OPERATING TEMPERATURE	-30 °F
MINIMUM OPERATING TEMPERATURE	-34 °C
FOR FLUID TYPE	Mineral-based or synthetic hydraulic fluids
CONNECTION TYPE	N/A
CONNECTION SIZE	N/A
BODY MATERIAL	N/A
SEAL MATERIAL	Nitrile
WEIGHT	0.24 lb
WEIGHT	0.11 kg
OPERATING TEMPERATURE	-34 to +121 °C
OPERATING TEMPERATURE	-30 to +250 °F
MAXIMUM FLOW RATE	8 gal/min
MAXIMUM FLOW RATE	30 L/min
FUNCTION	2-Way
ACTUATION TYPE	Manual
OPERATION TYPE	Manually operated
LEAK RATE	5 @ 1450 PSI (100 BAR) drops/min
CONFIGURATION	Needle w/Reverse Check
MAXIMUM KINEMATIC VISCOSITY	45-2000 SSU (6 to 420 cSt)
FILTER EFFICIENCY RATING	ISO 4406 18/16/13, SAE Class 4

MAXIMUM INLET PRESSURE RATING	420 bar
MAXIMUM INLET PRESSURE RATING	6000 psi
ADJUSTMENT MECHANISM	Screw
VALVE MATERIAL	All parts steel. All operating parts hardened steel
NEEDLE TYPE	Fine
CAVITY SIZE	C08-2
INSTALLATION TORQUE	30 lb-ft
INSTALLATION TORQUE	40 Nm