




1. MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: REDUCED DIAMETER WIRE SEAL
- 3. SPECIFICATIONS:
  - 3.1 CURRENT RATING: 13 AMPS
  - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
  - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
  - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
  - 3.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION)
  - 3.6 MATING CYCLE DURABILITY: 100 CYCLES
  - 3.7 RoHS COMPLIANT
- 4. MATING PART: AT06-4S\* PLUG (\* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.



CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL	
SIZE	O.D.	O.D.	WIRE RANGE	
16	1.35 mm (.053 in)	3.05 mm (.120 in)	14 - 20 AWG	



PART NUMBER CHART				
COLOR	PART NUMBER			
GREY	AT04-4P-RD01			
BLACK	AT04-4P-RD01BLK			
BLUE	AT04-4P-RD01BLU			
BROWN	AT04-4P-RD01BRN			
GREEN	AT04-4P-RD01GRN			
RED	AT04-4P-RD01RED			
WHITE	AT04-4P-RD01WHT			
YELLOW	AT04-4P-RD01YEL			

REVISIONS					
REV	ECO	DESCRIPTION	DATE	BY	APPR
А3	-	RELEASE NEW DWG FORMAT	25DEC13	DRP	

REQUIRES CONTACT RETENTION WEDGE AW4P



STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLORS SHOWN IN PART NUMBER CHART ARE AVAILABLE VIA SPECIAL ORDER.

	SEE PART N	UMBER CHART						٦
	PART NUMBER			DESCRIPTION		ITEN	vi	
QUANTITY	TY MATERIALS LIST							
All dimensions are in metric(mm).		SIGNATURE	S DATE	- AMNNANAI		Ī	٦	
		D.PARKS	25DEC13			ł		
		CHECKED:						
		ENGINEER:						
		APPROVAL:					4	
		CUSTOMER:		RECEPTACLE, 4 PIN, AT SERIES,				
					UCED DIAMETER	WIRE SEA	L	
		REFORMANCE DATA E PROPERTY OF ATION, NO RIGHTS IMPLIED, ALL	B C-	AT04-4P-RE	O01XXX	A3		
NEXT ASS'Y:	MANUFACTURING VARIATIONS.		SCALE NONE		SHEET 1	or 1	٦	