

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: CASSIDA GREASE GTX 2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Lubricating grease

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier FUCHS LUBRICANTS (UK) PLC.
New Century Street
ST1 5HU Hanley
Telephone: +44 (0) 1782 203700

Contact Person: Product Safety department
E-mail: product.safety@fuchs.com
Telephone: +44 (0) 1782 203700

1.4 Emergency telephone number: UK NHS: Dial 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

The product has not been classified as hazardous, but needs to be labelled according to regulation GB-CLP.

Classification according to GB-CLP.

Hazard summary

Physical Hazards: No data available.

2.2 Label Elements

EUH208: Contains Calcium Sulfonate. May produce an allergic reaction.

EUH210: Safety data sheet available on request.

2.3 Other hazards:

By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product name: CASSIDA GREASE GTX 2

General information: Lubricating grease: Thickener system and additives in synthetic base oil.

Chemical name	Identifier	Concentration *	UK-REACH Registration No.	Notes
Calcium Sulfonate	EINECS: 263-093-9	5,00% - <10,00%		
Calcium Sulfonate	EINECS: 271-529-4	5,00% - <10,00%		
Ca Sulfonate	EINECS: 274-263-7	5,00% - <10,00%		
Amine aromatic , alkylated	EINECS: 270-128-1	1,00% - <3,00%		
Ca Sulphonate	EINECS: 247-557-8	1,00% - <2,50%		

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Classification

Chemical name	Identifier	Classification	
Calcium Sulfonate	EINECS: 263-093-9	GBCLP:	Skin Sens. 1B;H317
Calcium Sulfonate	EINECS: 271-529-4	GBCLP:	Skin Sens. 1B;H317
Ca Sulfonate	EINECS: 274-263-7	GBCLP:	Skin Sens. 1B;H317
Amine aromatic , alkylated	EINECS: 270-128-1	GBCLP:	Repr. 2;H361f
Ca Sulphonate	EINECS: 247-557-8	GBCLP:	Acute Tox. 4;H302, Skin Irrit. 2;H315, Eye Dam. 1;H318, Aquatic Chronic 4;H413

GB-CLP

specific concentration limit

Chemical name	Identifier	specific concentration limit	Hazard class	Hazard Category	Hazard statements
Calcium Sulfonate	EINECS: 263-093-9	>= 10 %	Skin sensitizer	1B	H317
Calcium Sulfonate	EINECS: 271-529-4	>= 10 %	Skin sensitizer	1B	H317
Ca Sulfonate	EINECS: 274-263-7	>= 10 %	Skin sensitizer	1B	H317

For the wording of the listed hazard statements refer to section 16.

SECTION 4: First aid measures

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Promptly wash eyes with plenty of water while lifting the eye lids.

Skin Contact: Wash with soap and water.

Ingestion: Rinse mouth thoroughly.

4.2 Most important symptoms and effects, both acute and delayed: May cause skin and eye irritation.

Product name: CASSIDA GREASE GTX 2

4.3 Indication of any immediate medical attention and special treatment needed Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: CO₂, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

Unsuitable extinguishing media: Water with a full water jet.

5.2 Special hazards arising from the substance or mixture: During fire, gases hazardous to health may be formed.

5.3 Advice for firefighters

Special fire-fighting procedures: Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures: Not required.

6.2 Environmental Precautions: Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.

6.3 Methods and material for containment and cleaning up: Scrape up spillage or absorb with absorbing material. Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.

6.4 Reference to other sections: See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling: Provide adequate ventilation. Observe good industrial hygiene practices. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products.

Product name: CASSIDA GREASE GTX 2

7.2 Conditions for safe storage, including any incompatibilities:	Local regulations concerning handling and storage of waterpolluting products have to be followed.
7.3 Specific end use(s):	No data available.
Storage Class:	11, Combustible solids

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

None of the components have assigned exposure limits.

8.2 Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information:

Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.

Eyeface protection:

Avoid contact with skin and eyes. Goggles/face shield are recommended. If risk of splashing, wear safety goggles or face shield.

Skin protection

Hand Protection:

Material: Nitrile butyl rubber (NBR).
Min. Breakthrough time: ≥ 480 min
Recommended thickness of the material: $\geq 0,38$ mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Other:

Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.

Respiratory Protection:

Not relevant, due to the form of the product.

Thermal hazards:

Not known.

Product name: CASSIDA GREASE GTX 2

Hygiene measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

Environmental Controls: No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	solid
Form:	Paste
Color:	Yellow
Odor:	Mild
pH:	substance/mixture is non-soluble (in water)
Drop Point:	not determined
Boiling Point:	not determined
Flash Point:	> 180 °C (DIN 51755)
Evaporation Rate:	Not applicable for mixtures
Flammability (solid, gas):	not determined
Explosion Limit - Upper (%):	Not applicable for mixtures
Explosion Limit - Lower (%):	Not applicable for mixtures
Vapor pressure:	Not applicable for mixtures
Relative vapor density:	Not applicable for mixtures
Density:	0,95 - 1,05 g/cm ³ (25 °C)

Solubility(ies)

Solubility in Water:	Practically Insoluble
Solubility (other):	No data available.

Partition coefficient (n-octanol/water):	Not applicable for mixtures
---	-----------------------------

Auto-ignition temperature:	not determined
-----------------------------------	----------------

Decomposition Temperature:	not determined
-----------------------------------	----------------

NLGI:	2
--------------	---

Explosive properties:	Value not relevant for classification
------------------------------	---------------------------------------

Oxidizing properties:	Value not relevant for classification
------------------------------	---------------------------------------

Particle characteristics:	Study technically not feasible
----------------------------------	--------------------------------

9.2 Other information No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity: Stable under normal use conditions.

10.2 Chemical Stability: Stable under normal use conditions.

10.3 Possibility of hazardous reactions: Stable under normal use conditions.

10.4 Conditions to avoid: Stable under normal use conditions.

Product name: CASSIDA GREASE GTX 2

10.5 Incompatible Materials: Strong oxidizing substances. Strong acids. Strong bases.

10.6 Hazardous Decomposition Products: Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s)

Calcium Sulfonate LD 50 (Rat): > 16.000 mg/kg

Calcium Sulfonate LD 50 (Rat): > 5.001 mg/kg

Ca Sulfonate LD 50 (Rat): > 5.000 mg/kg (OECD 401)

Ca Sulphonate LD 50 (Rat): 1.300 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s)

Calcium Sulfonate LD 50 (Rat): > 5.001 mg/kg

Calcium Sulfonate LD 50 (Rabbit): > 5.001 mg/kg

Ca Sulfonate LD 50 (Rabbit): > 5.000 mg/kg (OECD 402)

Inhalation

Product: Not classified for acute toxicity based on available data.

Skin Corrosion/Irritation:

Product: Based on available data, the classification criteria are not met.

Specified substance(s)

Calcium Sulfonate OECD 404 (Rabbit):
Not irritant.

Calcium Sulfonate OECD 404 (Rabbit):
Not irritant.

Ca Sulfonate OECD 404 (Rabbit):
Not irritant.

Ca Sulphonate (Rabbit, 4 h):
Skin irritation.

Product name: CASSIDA GREASE GTX 2

Serious Eye Damage/Eye Irritation:

Product: Based on available data, the classification criteria are not met. Based on available data, the classification criteria are met.

Specified substance(s)

Calcium Sulfonate
OECD 405 (Rabbit):
Not irritant.

Respiratory or Skin Sensitization:

Product: Skin sensitizer: Based on available data, the classification criteria are not met.
Respiratory sensitizer: Based on available data, the classification criteria are not met.

Specified substance(s)

Calcium Sulfonate
May cause sensitization by skin contact.

Calcium Sulfonate
May cause sensitization by skin contact.

Ca Sulfonate
May cause sensitization by skin contact.

Germ Cell Mutagenicity

Product: Based on available data, the classification criteria are not met.

Carcinogenicity

Product: Based on available data, the classification criteria are not met.

Reproductive toxicity

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product: Based on available data, the classification criteria are not met.

Aspiration Hazard

Product: Based on available data, the classification criteria are not met.

Other adverse effects: No data available.

SECTION 12: Ecological information

General information: Not applicable

12.1 Toxicity

Acute toxicity

Product: Based on available data, the classification criteria are not met.

Fish

Specified substance(s)

Calcium Sulfonate
LC 50 (Fish, 96 h): > 10.000 mg/l (OECD 203)

Product name: CASSIDA GREASE GTX 2

Calcium Sulfonate LL 50 (Cyprinodon variegatus, 96 h): > 10.000 mg/l (OECD 203)

Ca Sulfonate LC 50 (Fish, 96 h): > 1.001 mg/l (OECD 203)

Ca Sulphonate LC 50 (Fish, 96 h): 22 mg/l (OECD 203)

Aquatic Invertebrates**Specified substance(s)**

Calcium Sulfonate EC 50 (Water Flea, 48 h): > 100 mg/l (OECD 202)

Calcium Sulfonate EL50 (Daphnia magna, 48 h): > 1.000 mg/l

Ca Sulfonate EC 50 (Water Flea, 48 h): > 1.001 mg/l

Ca Sulphonate EC 50 (Water Flea, 48 h): 2,5 mg/l (OECD 202)

Chronic Toxicity**Product:**

Based on available data, the classification criteria are not met.

Toxicity to Aquatic Plants**Specified substance(s)**

Calcium Sulfonate EL50 (Algae (Pseudokirchneriella subcapitata), 96 h): > 1.000 mg/l

Ca Sulfonate EC 50 (Alga, 72 h): > 1.000 mg/l

12.2 Persistence and Degradability**Biodegradation****Product:**

Not applicable for mixtures

Specified substance(s)

Calcium Sulfonate 8,6 % (28 d) Not easily biodegradable

Ca Sulphonate 73 % (28 d) Readily biodegradable

12.3 Bioaccumulative potential**Product:**

Not applicable for mixtures

12.4 Mobility in soil:**Product:**

Not applicable for mixtures

12.5 Results of PBT and vPvB assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other adverse effects:

No data available.

Water Hazard Class (WGK):

WGK 1: slightly water-endangering.

Product name: CASSIDA GREASE GTX 2

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information: Dispose in accordance with all applicable regulations.

Disposal methods: Do not empty into drains; dispose of this material and its container in a safe way. When storing used products, ensure that the waste categories and mixing instructions are observed.

List of Waste (LoW) Codes

12 01 12*: spent waxes and fats

SECTION 14: Transport information

ADR/RID

14.1 UN number or ID number:	—
14.2 UN Proper Shipping Name:	—
14.3 Transport Hazard Class(es)	
Class:	Non-dangerous goods
Label(s):	—
Hazard No. (ADR):	—
Tunnel restriction code:	—
14.4 Packing Group:	—
14.5 Environmental hazards:	—
14.6 Special precautions for user:	—

IMDG

14.1 UN number or ID number:	—
14.2 UN Proper Shipping Name:	—
14.3 Transport Hazard Class(es)	
Class:	Non-dangerous goods
Label(s):	—
EmS No.:	—
14.3 Packing Group:	—
14.5 Environmental hazards:	—
14.6 Special precautions for user:	—

IATA

14.1 UN number or ID number:	—
14.2 Proper Shipping Name:	—
14.3 Transport Hazard Class(es):	
Class:	Non-dangerous goods
Label(s):	—
14.4 Packing Group:	—
14.5 Environmental hazards:	—
14.6 Special precautions for user:	—

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable.

Product name: CASSIDA GREASE GTX 2

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

GB Regulations

The Ozone-Depleting Substances and Fluorinated Greenhouse Gases (Amendment etc.) (EU Exit) Regulations 2019:

none

The Ozone-Depleting Substances and Fluorinated Greenhouse Gases (Amendment etc.) (EU Exit) Regulations 2019:

none

The Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020:

none

The Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020:

none

15.2 Chemical safety assessment:

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information: Vertical lines in the margin indicate an amendment.

Wording of the H-statements in section 2 and 3

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H361f	Suspected of damaging fertility.
H413	May cause long lasting harmful effects to aquatic life.

Other information: The classification complies with the current GB lists; however, it has been supplemented with expert literature information and information provided by/about our company. The following evaluation methods were used: On the basis of test data; Calculation Method; Bridging Principle "Substantially similar mixtures"; Expert Judgement

Revision Date: 26.07.2024

Product name: CASSIDA GREASE GTX 2

Disclaimer:

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.