

Label - EML-D (40X15)R - 1054876

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Label, detectable, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting type: adhesive, lettering field size: 40 x 15 mm, Number of individual labels: 1000

Your advantages

- ✓ Self-adhesive EML-D ... device markers for marking various types of operating equipment in control, system, and control cabinet applications in the food industry
- ✓ The EML-D features a continuous aluminum foil strip that makes the label detectable.
- ✓ Thanks to its great adhesive strength, this label can be placed on rough, textured, and low-energy surfaces.
- ✓ When combined with the TM-RIBBON 110-EX ink ribbon, the printing is highly resistant to solvents, aggressive cleaning agents, acetone, and ethanol.
- ✓ The material used has been tested and approved by ISEGA for use in the food industry.



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 690735
GTIN	4055626690735
Weight per Piece (excluding packing)	22.220 g
Custom tariff number	39269097
Country of origin	Germany
Sales Key	BG2411

Technical data

Dimensions

Length (b)	15 mm
Width (a)	40 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 100 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

Label - EML-D (40X15)R - 1054876

Technical data

General

Note	Due to the differing detection properties of metal detectors, the installer/end user is to check suitability for the actual application
	Items are approved for smooth and textured stainless-steel surfaces as well as for surfaces that have been coated with hammer-finish paint.
Color	white
Components	free from silicone and halogen
Material	Polyester
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Number of individual labels	1000
Marking mounting type	adhesive

Classifications

eCl@ss

eCl@ss 10.0.1	27400629
eCl@ss 11.0	27281103
eCl@ss 5.0	27149100
eCl@ss 6.0	27149100
eCl@ss 7.0	27149129
eCl@ss 9.0	27400629

ETIM

ETIM 6.0	EC001288
ETIM 7.0	EC001288

Accessories

Accessories

Ink ribbon

Ink ribbon - TM-RIBBON 110-EX - 0803211



Ink ribbon, for roll printer for printing product group EML-EX..., width: 110 mm, color: black