

# Eaton 1319334

Catalog Number: 1319334

Eaton Drive coupling, for shaft, 10x10 mm

## General specifications



### Product Name

Eaton Accessory Connection piece for  
shaft extension

### Catalog Number

1319334

### EAN

8711426715479

### Product Length/Depth

200 mm

### Product Height

10 mm

### Product Width

120 mm

### Product Weight

0.084 kg

### Compliances

CE

## Product specifications

### Type

Adapters for shaft  
extensions  
Drive coupling

### 10.10 Temperature rise

Not applicable.

### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.7 Inscriptions

Meets the product standard's requirements.

### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

## Resources

### Catalogs

[Eaton-industrial-switch-disconnectors-catalogue-ca008011en-en-gb.pdf](#)

[Product Range Catalog Industrial switch-disconnectors](#)

#### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### Ambient operating temperature - max

55 °C

#### Ambient operating temperature - min

-25 °C

#### Equipment heat dissipation, current-dependent P<sub>vid</sub>

0 W

#### Heat dissipation capacity P<sub>diss</sub>

0 W

#### Heat dissipation per pole, current-dependent P<sub>vid</sub>

0 W

#### Rated operational current for specified heat dissipation (I<sub>n</sub>)

0 A

#### Static heat dissipation, non-current-dependent P<sub>vs</sub>

0 W

#### Degree of protection

NEMA Other

#### Shaft diameter

10 x 10 mm



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)