

# **Features**

#### **WE Series**

- 4-row recirculating ball bearing guide
- 45° contact angle of the ball tracks
- High torque capacity
- Low assembly height

## **RS PRO Linear Guide Rails**

RS Stock No.: 0345398



RS PRO is the own brand of RS. The RS PRO Seal of Approval is your assurance of professional quality, a guarantee that every part is rigorously tested, inspected, and audited against demanding standards. Making RS PRO the Smart Choice for our customers.

Product Description Page 1 of 3

## **Linear Guide Rails**



#### **Features of WE Series:**

• The WE series features equal load ratings in the radial, reverse radial and the lateral direction with contact points at 45 degrees. This along with the wide rail, allows the guideway to be rated for high loads, moments and rigidity. By design, it has a self- aligning capacity that can absorb most installation errors and can meet high accuracy standards. The ability to use a single rail and to have the low profile with a low centre of gravity is ideal where space is limited and/or high moments are required.

#### **Advantages:**

- Compact and economical design caused by high torque capacity
- High efficiency due to low frictional looses
- The large mounting surface of the block supports the transmission of higher torques
- High load capacity in all directions by contact points at 45°

#### **Typical Applications:**

- Automation devices
- High-speed transportation equipment
- Precision measuring equipment
- Semiconductor manufacturing equipment
- Blow moulding machines
- Single axis robot-robotics
- Single axis equipment with high anti-rolling requirement


## **General Specifications**

Manufacturer Series	WE
Model Type	WER-R
Туре	Interchangeable
Block Mounting Type	Mounting From Top
Rail Length	300mm
Rail Width	33mm
Materials	Carbon Steel
Size	17mm
Accuracy Class	H - High



## **Construction**

### Construction of WE Series



- 4-row recirculating ball bearing guide
- 45° contact angle of the ball tracks
- The ball retainers prevent the balls from falling out when the carriage is removed
- Lower assembly height
- Wide guideway for high torque capacity
- Large mounting surface on the block

<sup>\*\*\*</sup> Please see our complete RS PRO WE Series product guide for detailed specifications