

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By -

ALL RIGHTS RESERVED.

LOC

J

DIST

REVISIONS

変更

P	LTR	DESCRIPTION	DATE	DWN	APVD
	L1	REVISED PER ECO-11-005030	11MAR11	RK	HMR

2.1

2.9

3.7

4.9

14

2.1

2.9

3.7

4.9

14

0.8 ± 0.1

0.8 ± 0.1

2.5 TYP

ピッチ PITCH

A

B

C

2

回路番号

CIRCUIT NO.

3~12極

POS

2.1

2.9

3.7

4.9

14

2.1

2.9

3.7

4.9

14

0.8 ± 0.1

0.8 ± 0.1

2.5 TYP

ピッチ PITCH

A

B

C

1.5

回路番号

CIRCUIT NO.

2極

POS

0.9

4

6.7

2極

POS

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
単位: 耗
mm

TOLERANCES UNLESS
OTHERWISE SPECIFIED:
一般公差

0 PLC ± -

1 PLC ± -

2 PLC ± -

3 PLC ± -

4 PLC ± -

ANGLES ± -

FINISH
仕上

GENERAL TOLERANCE
一般公差

10 ≥ : ±0.2

30 ≥ > 10: ±0.25

100 ≥ > 30: ±0.3

ANGLES: ±3°

MATERIAL
材料

66 NYLON
(UL94-0)

DWN
H.HOSHINO
12JUN97

CHK
J.TANIGAWA
12JUN97

APVD
S.KUBOUCHI
03OCT97

PRODUCT SPEC
製品規格
108-5118

APPLICATION SPEC
取付適用規格

WEIGHT

CUSTOMER DRAWING

SCALE
尺度 4:1

SHEET
1 OF 1

REV
L1

NAME
名称

HOUSING
AMP EI SERIES CONNECTOR

SIZE
A3

CAGE CODE
00779

DRAWING NO
番号
C-171822

RESTRICTED TO
-

1 使用するコンタクトは 170262 又は 170263.

2 ロッキング凸部位置は長手方向の中央。

1 CONTACTS, 170262 & 170263 ARE USED.

2 LOCKING PROTRUSION IS PLACED ON THE CENTER OF HOUSING.

1470-19 (3/11)