
# Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications





KSA1000DLC401

EAN Code: 3606489602093

# Main

Range of product	Canalis	
product name	KS	
Device short name	KSA	
Offer type	Classic	
Product or component type	Elbow	
Busbar description	Standard	
Product compatibility	Canalis KSA busbar trunking 5001000 A	
Device application	Change direction	
Conductors material	Aluminium	
Busbar trunking polarity	3L + N + PE	
[le] rated operational current	1000 A at 35 °C	
IP degree of protection	IP55 conforming to IEC 60529	
[Ue] rated operational voltage	230690 V	
Network frequency	50/60 Hz	
Operating angle	90 °	
Direction change type	direction 1: edgewise to right - direction 2: edgewise to left -	
Colour	White (RAL 9001)	
Dimension type	Fix	

# Complementary

Length	290 mm for side A 290 mm for side B	
Width	113 mm	
Height	146 mm	
Net weight	15 kg	
Mounting location	On trunking	
Mounting position	Any position	
Electrical connection	Lubricated sliding contact	
Mounting mode	By screws	
Standards	IEC 61439-1 IEC 61439-6	

## **Environment**

IK degree of protection IK08 conforming to IEC 62262

# **Packing Units**

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.5 cm
Package 1 Width	39.5 cm
Package 1 Length	46.5 cm
Package 1 Weight	15.475 kg
Unit Type of Package 2	P06
Number of Units in Package 2	6
Package 2 Height	105.0 cm
Package 2 Width	80.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	98.4 kg

# **Logistical informations**

Country of origin

# **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

### Environmental Data explained >

How we assess product sustainability

<i>a</i>				
Environmental footprint	footprint	ntal	Environn	$\sigma$

Environmental Disclosure

Product Environmental Profile

### **Use Better**

Recycled metal content at CR level	0
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

# **Dimensions Drawings**

## **Dimensions**

