

Eaton 266616

Catalog Number: 266616

Eaton Moeller series NZM - Molded Case Circuit Breaker. Door coupling rotary handle, lockable on the handle+switch

General specifications



Product Name

Eaton Moeller series NZM operating element

Catalog Number

266616

EAN

4015082666163

Product Length/Depth

230 mm

Product Height

130 mm

Product Width

230 mm

Product Weight

1.934 kg

Compliances

UL/CSA
IEC
RoHS conform

Certifications

UL489
CSA (File No. 22086)
CE marking
UL (File No. E140305)
CSA-C22.2 No. 5-09
UL (Category Control Number DIHS)
UL listed
CSA certified
CSA (Class No. 1437-01)
IEC60947

Product specifications

Used with

NZM4(-4), N(S)4(-4)

Type

Accessory Door coupling rotary handle

Special features

Door coupling rotary handle for operating the switch through a closed control panel door External warning plate/designation label can be clipped on. Complete including rotary drive and coupling parts Extension shaft additionally required.

Features

Lockable

Standard: black / gray

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Resources

Brochures

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

Catalogs

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

Declarations of conformity

[DA-DC-03_NZM4](#)

Drawings

[eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-011.eps](#)

[eaton-circuit-breaker-padlock-nzm-rotary-handle-dimensions.eps](#)

[eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-007.eps](#)

[eaton-circuit-breaker-door-nzm-rotary-handle-3d-drawing-005.eps](#)

Installation instructions

[IL01210003Z](#)

Installation videos

[The new digital NZM Range](#)

[Introduction of the new digital circuit breaker NZM](#)

mCAD model

[DA-CD-nzm4_xtvd](#)

[DA-CS-nzm4_xtvd](#)

Technical data sheets

[eaton-nzm-technical-information-sheet](#)

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Color

Black

Fitted with:

Padlock

Frame

NZM4

Suitable for

Switch disconnecter

Power circuit breaker

Cover/door type

Door interlock can be modified in the unlocked ON position

Door can be opened in OFF

Door interlock not defeated in the locked OFF and ON positions

Door interlock can be modified such that it can be defeated from the outside using a screwdriver

Lock number

Double lockable

Locking facility

Modifiable on handle in I position as well

Lockable on the handle on the switch using up to 3 padlocks

With door interlock

Degree of protection / NEMA enclosure type

IP66

4X. 12



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia