

SIMATIC CFU DIQ with aluminum enclosure, bundle consisting of: 1x SIMATIC CFU DIQ (6ES7655-5PX31-1XX0), 1x aluminum enclosure with cable glands, shield busbar, shield terminals, preassembled and checked



General information	
Product type designation	DIQ with aluminum enclosure
Firmware version	V2.0
<ul style="list-style-type: none"> FW update possible 	Yes
Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	060FH
Number of channels	16
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> Isochronous mode 	No
<ul style="list-style-type: none"> The user can configure digital channels as input/output as required 	Yes
<ul style="list-style-type: none"> Digital channels can be parameterized 	Yes
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version 	V19 Update 2
<ul style="list-style-type: none"> STEP 7 configurable/integrated from version 	STEP 7 V5.7.1.4
<ul style="list-style-type: none"> PCS 7 configurable/integrated from version 	V9.1 SP2 UC7
<ul style="list-style-type: none"> PROFIBUS from GSD version/GSD revision 	- / -
<ul style="list-style-type: none"> PROFINET from GSD version/GSD revision 	GSDML V2.43 2024.02.08
Operating mode	
<ul style="list-style-type: none"> Counter 	Yes
Installation type/mounting	
Mounting	For horizontal and vertical mounting
Mounting position	Horizontal, vertical
Supply voltage	
Type of supply voltage	24 V DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Short-circuit protection	Yes
Redundant power supply	Yes
Mains buffering	
<ul style="list-style-type: none"> Mains/voltage failure stored energy time 	5 ms; For communication
Input current	
Current consumption (rated value)	5.12 A
Current consumption, max.	5.13 A
Inrush current, max.	4.8 A
I^2t	0.073 A ² ·s

Encoder supply	
Number of outputs	16
Output voltage, min.	18.2 V
Short-circuit protection	Yes; Electronic
Output current	
• up to 60 °C, max.	5 A
• up to 70 °C, max.	4 A
Power loss	
Power loss, typ.	2.88 W; Depending on the type of BusAdapter used (typ. RJ45)
Address area	
Address space per station	
• Address space per station, max.	1 440 byte; Dependent on configuration
Digital inputs	
Number of digital inputs	16
Sourcing/sinking input	Yes; P-reading
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input characteristic curve in accordance with IEC 61131, type 2	No
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Pulse extension	No
Number of simultaneously controllable inputs	
horizontal installation	
— up to 60 °C, max.	16; Total current must be observed, see DQ
— up to 70 °C, max.	16; Total current must be observed, see DQ
vertical installation	
— up to 60 °C, max.	16; Total current must be observed, see DQ
Digital input functions, parameterizable	
• Counter	Yes
— Number, max.	2
— Counting frequency, max.	1 kHz
— Counting width	32 bit
— Counting direction up/down	Yes; Up
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-30 to +5 V
• for signal "1"	+11 to +30V
Input current	
• for signal "1", typ.	2.5 mA; Typical
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", max.	3.2 ms; for counter function 0,1 ms
— at "1" to "0", max.	3.2 ms; for counter function 0,1 ms
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Digital outputs	
Type of digital output	Transistor
Number of digital outputs	16
Current-sinking	No
Current-sourcing	Yes
Short-circuit protection	Yes
• Response threshold, typ.	0.7 to 1.3 A
Limitation of inductive shutdown voltage to	Typ. L+ (-50 V)
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	5 W
Load resistance range	
• lower limit	48 Ω
• upper limit	12 kΩ

Output voltage	
• Type of output voltage	DC
• for signal "1", min.	Ue minus 1 V
Output current	
• for signal "1" rated value	0.5 A
• for signal "0" residual current, max.	0.1 mA
Output delay with resistive load	
• "0" to "1", max.	50 µs
• "1" to "0", max.	100 µs
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	No
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	2 Hz
• on lamp load, max.	10 Hz
Total current of the outputs	
• Current per channel, max.	0.5 A
horizontal installation	
— up to 60 °C, max.	5 A
— up to 70 °C, max.	4 A
vertical installation	
— up to 60 °C, max.	5 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interfaces	
Number of PROFINET interfaces	1
Number of PROFIBUS interfaces	0
1. Interface	
Interface type	PROFINET
Isolated	Yes
Interface types	
• Number of ports	2
• integrated switch	Yes
• BusAdapter (PROFINET)	Yes
Protocols	
• PROFINET IO Device	Yes
• PROFIBUS DP device	No
Interface types	
RJ 45 (Ethernet)	
• 100 Mbps	Yes
• Autonegotiation	Yes
• Autocrossing	Yes
Protocols	
Supports protocol for PROFINET IO	Yes
Redundancy mode	
• PROFINET system redundancy (S2)	Yes; Type S2
Media redundancy	
— MRP	Yes
Open IE communication	
• LLDP	Yes
Interrupts/diagnostics/status information	
Status indicator	Yes
Alarms	Yes

Diagnostics function	Yes	
Diagnoses		
• Monitoring of encoder power supply	Yes	
• Wire-break	Yes	
• Short-circuit	Yes	
Diagnostics indication LED		
• RUN LED	Yes; green LED	
• ERROR LED	Yes; red LED	
• MAINT LED	Yes; Yellow LED	
• Monitoring of the supply voltage (PWR-LED)	Yes	
• Status indicator digital input (green)	Yes	
• Status indicator digital output (green)	Yes	
Potential separation		
between the channels and PROFINET	Yes	
Potential separation digital inputs		
• between the channels	No	
• between the channels and the power supply of the electronics	No	
Potential separation digital outputs		
• between the channels	No	
• between the channels and the power supply of the electronics	No	
Isolation		
Isolation tested with	1 500 V AC between PROFINET and electronics	
Degree and class of protection		
IP degree of protection	IP66	
Ambient conditions		
Ambient temperature during operation		
• min.	-40 °C	
• max.	60 °C	
• horizontal installation, min.	-40 °C	
• horizontal installation, max.	60 °C; Max. 4 A load current; up to 50 °C max. 5 A load current	
• vertical installation, min.	-40 °C	
• vertical installation, max.	50 °C	
Ambient temperature during storage/transportation		
• min.	-40 °C	
• max.	70 °C	
Relative humidity		
• Operation, max.	95 %	
Connection method		
Design of electrical connection	Connection plug	
Dimensions		
Width	414 mm	
Height	266 mm	
Depth	111 mm	
Weights		
Weight, approx.	5.5 kg	
Classifications		
	Version	Classification
eClass	14	27-24-26-90
eClass	12	27-24-26-90
eClass	9.1	27-24-26-90
eClass	9	27-24-26-90
eClass	8	27-24-92-90
eClass	7.1	27-24-92-90
eClass	6	27-24-92-90
ETIM	10	EC002584

ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584

Approvals / Certificates

General Product Approval	EMV	For use in hazardous locations
--------------------------	-----	--------------------------------



[Miscellaneous](#)



For use in hazardous locations

[Type Examination Certificate](#)



last modified:

3/12/2025