

PRODUCT-DETAILS

# ZLS201E82

## ZLS201E82 Busbar



### General Information

Extended Product Type	ZLS201E82
Product ID	2CCF800195R0001
EAN	7612270017010
Catalog Description	ZLS201E82 Busbar
Long Description	Busbar 125A L1, L2, L3, N or PE 10x3mm galvanic plated for SMISLINE TP-Touch proof system PLE82

### Technical

Standards	IEC/EN 61439-6
Product Name	Busbar
Type of Residual Current	standard version
Rated Operational Voltage	690/1000 V AC/DC
Rated Current (I <sub>n</sub> )	125 A
Options Provided	Busbar LLL,N, N,PE
Model Number	Flat

### Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Environmental Information	2CCY451206D0201

---

## Dimensions

Product Net Width	10 mm
Product Net Height	10 mm
Product Net Depth / Length	1472 mm
Product Net Weight	408 g
Product Net Length	1472 mm

---

## Container Information

Package Level 1 Units	carton 1 piece
Package Level 1 Width	20 mm
Package Level 1 Height	10 mm
Package Level 1 Depth / Length	1476 mm
Package Level 1 Gross Weight	408 g
Package Level 1 EAN	7612270017010

---

## Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85389030
Country of Origin	Switzerland (CH)
Selling Unit of Measure	piece

---

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	9AKK107991A9646
Environmental Information	2CCY451206D0201
Instructions and Manuals	9AKK107680A2315
RoHS Information	9AKK107991A9646

---

## Popular Downloads

Data Sheet, Technical Information	9AKK107492A6192
Instructions and Manuals	9AKK107680A2315
Dimension Diagram	9AKK107492A6192

---

## Classifications

ETIM 6	EC001522 - Busbar
ETIM 7	EC001522 - Busbar
ETIM 8	EC001522 - Busbar
EPLAN Catalog Tree	Mechanics / Busbars / General
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85389030
Object Classification Code	W

---

---

## Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems Accessories → Accessories for Plug-in Distribution Systems 125A

