


## RJ45 connector - CUC-V14-C1ZNI-S/R4IE10G8 - 1149841

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Push-pull ADVANCE connector (version 14), die-cast zinc, with RJ45 connector insert, 8-pos., 10 Gbps, CAT6<sub>A</sub> (IEC 11801:2017), with IDC fast connection technology, for AWG 26 - 24 1-wire, 7-wire, and 19-wire conductors, for cable diameter of 5.5 mm ... 10 mm

### Your advantages

- ✓ Easy and time-saving assembly with IDC fast connection technology
- ✓ Future-proof due to CAT6<sub>A</sub> with 10 Gbps
- ✓ 360° shielding ensures reliable transmission, even in industrial applications
- ✓ Ideal companion for servicing or repairs in the field: no special tools required for mounting
- ✓ Locking system to prevent inadvertent release



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 063151 145842
GTIN	4063151145842
Weight per Piece (excluding packing)	89.050 g
Custom tariff number	85366990
Country of origin	Poland
Sales Key	ABNEAC

### Technical data

#### Mechanical characteristics

Connection method	IDC fast connection
Minimum external conductor diameter	5.5 mm
Maximum external conductor diameter	10 mm
Overvoltage category	I
AWG solid min.	26
AWG solid max.	24
AWG multi-stranded min.	26

# RJ45 connector - CUC-V14-C1ZNI-S/R4IE10G8 - 1149841

## Technical data

### Mechanical characteristics

AWG multi-stranded max.	24
Tightening torque max	2.5 Nm
Insertion/withdrawal cycles	≥ 750
Number of positions	8
Degree of protection	IP20
Degree of pollution	2
Cable outlet	straight
No. of cable outlets	1
Locking type	Push Pull
Weight	89.05 g
Flammability rating according to UL 94	V0

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (assembly)	-10 °C ... 40 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

### Material data

Contact surface material	Au/Ni
Contact material	Cu/Sn
Contact carrier material	PC
Cable gland material	CuZn
Seal material	CR
	NBR
	NBR
Seal material, O-ring	NBR
Seal material cable seal	CR
Seal material	NBR
Width	22.4 mm
Height	34 mm
Length	95 mm
Wrench size	20.00 mm
Housing surface material 1	Cu/Ni

### Electrical characteristics

Transmission speed	10 Gbps
Resistance	500 MΩ
Connection cross section AWG	26 ... 24 (solid)
	26 ... 24 (flexible)
Rated current	1.75 A
Test voltage Core/Core	1000 V
Test voltage Core/Shield	1500 V

# RJ45 connector - CUC-V14-C1ZNI-S/R4IE10G8 - 1149841

## Technical data

### Electrical characteristics

Degree of protection when not plugged in	IP20
--	------

### Standards and Regulations

Standards/specifications	IEC 61076-3-117
--------------------------	-----------------

### Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

## Classifications

### eCl@ss

eCl@ss 10.0.1	27440101
eCl@ss 11.0	27440101
eCl@ss 9.0	27440101

### ETIM

ETIM 7.0	EC002636
----------	----------

## Approvals

### Approvals


#### Approvals

EAC / cULus Recognized

#### Ex Approvals

### Approval details

EAC		B.01687
-----	---	---------

cULus Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> E335024-20170228
Nominal voltage UN	56.5 V	
Nominal current IN	0.175 A	

## RJ45 connector - CUC-V14-C1ZNI-S/R4IE10G8 - 1149841

### Accessories

#### Accessories

#### Electronics pliers

##### Diagonal cutter - MICROFOX-SP-1 - 1212487



Electronic diagonal cutter, tapered head, without chamfer, with opening spring, non-reflective phosphate-treated surface, punched version

---

### Panel mounting frame

#### Panel mounting frames - CUC-V14-F1ZNI-EM/R4F8 - 1413961



RJ45 panel mounting frame, IP67, for push-pull interlocking, metal, for rectangular mounting cutout, with seal and mounting screws, incl. RJ45 insert with IDC cable connection

---

#### Panel mounting frames - CUC-V14-F1ZNI-EM/R4B8 - 1413962



RJ45 panel mounting frame, IP67, for push-pull interlocking, metal, for rectangular mounting cutout, with seal and mounting screws, incl. RJ45 coupling module

---

#### Panel mounting frames - CUC-V14-F1ZNI-EM/R4O - 1413963



RJ45 panel mounting frame, IP67, for push-pull interlocking, metal, for PCB connection, for square panel cutout, with grommet and mounting screws

---

#### Stripping tool - VS-CABLE-STRIP-VARIO - 1657407



Stripping tool, for the multi-level stripping of shielded cables

