

DIN-rail time switches

Features

- Backlight
- PIN-Code
- Hour counter with service function
- External input
- 12h/24h time setting
- Switching state display
- Weekly program (ON/OFF, pulse, cycle)
- Holiday program (ON/OFF, pulse, cycle, OFF)
- Data transmission (talento taxi)
- Shortest switching time: 1 sec.
- Autom. summertime / wintertime changeover: automatic / free selectable / OFF
- Manual switch: Automatic / Override / fix ON/OFF
- Free weekday block formation
- Random generator
- Sealable
- Non-volatile memory (EEPROM)

Applications

- Advertising signs
- Street lighting
- Shop window lighting
- Home & work environment
- Devices, motors and pumps control
- Shutters control
- Simulation of home presence

**talento 471 pro (1 channel)**

24 V AC/DC, 110-230 V AC	041991	03.98.0001.1	DE, FR, IT, CS, HU
24 V AC/DC, 110-230 V AC	042387	03.98.0009.1	EN, ES, PT, NL, PL
24 V AC/DC, 110-230 V AC	042806	03.98.0017.1	NO, SV, DA, FI

talento 472 pro (2 channels)

24 V AC/DC, 110-230 V AC	042004	03.98.0002.1	DE, FR, IT, CS, HU
24 V AC/DC, 110-230 V AC	042394	03.98.0010.1	EN, ES, PT, NL, PL
24 V AC/DC, 110-230 V AC	042813	03.98.0018.1	NO, SV, DA, FI
12 V AC/DC	042011	03.98.0003.1	DE, FR, IT, CS, HU
12 V AC/DC	042400	03.98.0011.1	EN, ES, PT, NL, PL
12 V AC/DC	042820	03.98.0019.1	NO, SV, DA, FI

talento 471 pro, talento 472 pro

- 100 Memory spaces

**talento 791 pro (1 channel)**

24 V AC/DC, 110-230 V AC	042028	03.98.0004.1	DE, FR, IT, CS, HU
24 V AC/DC, 110-230 V AC	042417	03.98.0012.1	EN, ES, PT, NL, PL
24 V AC/DC, 110-230 V AC	042837	03.98.0020.1	NO, SV, DA, FI

talento 792 pro (2 channels)

24 V AC/DC, 110-230 V AC	042035	03.98.0005.1	DE, FR, IT, CS, HU
24 V AC/DC, 110-230 V AC	042424	03.98.0013.1	EN, ES, PT, NL, PL
24 V AC/DC, 110-230 V AC	042844	03.98.0021.1	NO, SV, DA, FI

talento 791 pro, talento 792 pro

- 100 Memory spaces
- Astro program

**talento 881 pro (1 channel)**

24 V AC/DC, 110-230 V AC	042042	03.98.0006.1	DE, FR, IT, CS, HU
24 V AC/DC, 110-230 V AC	042431	03.98.0014.1	EN, ES, PT, NL, PL
24 V AC/DC, 110-230 V AC	042851	03.98.0022.1	NO, SV, DA, FI

talento 882 pro (2 channels)

24 V AC/DC, 110-230 V AC	042059	03.98.0007.1	DE, FR, IT, CS, HU
24 V AC/DC, 110-230 V AC	042448	03.98.0015.1	EN, ES, PT, NL, PL
24 V AC/DC, 110-230 V AC	042868	03.98.0023.1	NO, SV, DA, FI
12 V AC/DC	042066	03.98.0008.1	DE, FR, IT, CS, HU
12 V AC/DC	042455	03.98.0016.1	EN, ES, PT, NL, PL
12 V AC/DC	042875	03.98.0024.1	NO, SV, DA, FI

talento 881 pro, talento 882 pro

- 400 Memory spaces
- Astro program
- Annual program (ON/OFF, pulse, cycle)

Technical data

	talento 471/472 pro		talento 791/792 pro		talento 881/882 pro	
Dimensions H x W x D (mm)	45 x 35 x 60					
Width	2 modules					
Distributor cut-out (mm)	46 x 36					
Installation type	DIN-rail					
Weight (g) approx.	170					
Connection voltage	24 V AC/DC / 110 - 230 V AC / 50-60 Hz					
Power consumption at 230 V~ (AC)	1 VA					
Switch contacts	1 CO	1 CO + 1 NO	1 CO	1 CO + 1 NO	1 CO	1 CO + 1 NO
Switching output	phase-independent (zero cross switching)					
Opening width	< 3 mm					
Lamp type	16 A / 250 V, cos φ = 1 10 A / 250 V, cos φ = 0,6 2600 W 1000 VA 1000 VA 730 VA (80 µF) 1000 VA 2600 W 22x7 W, 18x11 W, 16x15 W, 16x20 W, 14x23 W 37x7 W, 30x11 W, 26x15 W, 26x20 W, 11x23 W					
– Resistive						
– Inductive						
– Incandescent						
– Fluorescent						
Uncorrected						
Serial corrected						
Parallel corrected						
Lead-lag (duo)						
– Halogen lamp load						
– Compact fluorescent lamp						
– Energy saving lamps 230 V						
Rated load AC1/AC15	4000 VA / 750 VA					
Min. switching load	300 mW					
DC Switching capacity (24V-/50V-/220V-)	800 mA / 300 mA / 150 mA					
Housing and insulation material	high-temperature resistant, self-extinguishing thermoplastic					
Ambient temperature	-25°C* ... +55°C					
Protection class (EN60730-1)	II					
Type of protection (EN60529)	IP 20					
Accuracy	Typ ± 0,3 sec./day at +20°C					
Time basis	Quartz					
Power reserve	10 years ex works at +20°C (Replaceable battery CR2450)					
Max. terminal capacity	1 - 4 mm²					
Connection type	Captive ± screw terminal					
Battery type	CR2450					
Accessories						
Handheld programming device / PC-software	see page 20					
Assembly accessories	see page 28					

* Limited display readability possible, however full functionality guaranteed.

Dimensional drawings /
circuit diagrams:

