XBP48RM1U-LI APC Smart-UPS 48V 585 Wh LI Battery Pack



Overview	Havally in Ctack	
Lead time	Usually in Stock	
General		
Provided equipment	4 post rail kit	
Tromada aqarpinani	Communication cable	
	Grounding cable	
	Installation guide Rack mounting brackets	
	Rack mounting brackets	
Physical		
Colour	Black with silver front bezel	
Depth	52.1 cm	
Height	4.3 cm	
Net weight	13.02 kg	
Number of rack unit	1U	
Width	43.2 cm	
Conformance		
Standards	UL 1973	
Environmental		
Ambient air temperature for operation	040 °C	
Operating altitude	010000 ft	
Relative humidity	095 % non-condensing	
	-1545 °C	
Ambient air temperature for storage		
Ambient air temperature for storage Storage altitude	0.0015240.00 m	
	0.0015240.00 m	
Storage altitude	0.0015240.00 m	
	0.0015240.00 m	

Device mounting

Rack mount

Battery voltage	48 V		
Battery type	Li-lon (Lithium-lon)		
Packing Units			
Package 1 Weight	18.64 kg		
Package 1 Height	20 cm		
Package 1 width	60 cm		
Package 1 Length	85 cm		
Number of Units in Package 3	8		

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
	and the contract of the contra

Contractual warranty

	Warranty	5 year repair or replace
--	----------	--------------------------